

# INDEX

---

Entries from footnotes are indicated by page numbers in italics.

- 1-second mapped spectral acceleration, 61
- 50-year earthquake, 44
- AASHTO, 54, 201
- Abutment, 209
- Acceleration
  - effective peak ground, 15, 20, *20*
  - ground, vertical, 88
  - mapped spectral, 61
  - peak ground, 12
  - response period, 78
  - spectral, 21, 37
  - spectral, pseudo, *21*
  - vertical, 13
- Accelerogram, 15
  - El Centro earthquake, A-219
- Accelerograph, 15
- Accelerometer, 15
- Accidental
  - eccentricity, 46
  - torsion, 89
- Acronyms, seismic, A-220
- Act
  - Field, 51
  - Riley, 51
- Action
  - bent, 43
  - diaphragm, 107
- Active
  - chord, 117
  - fault, 12
  - mass damper, 163
  - pulse system, 164
  - tendon system, 164
- Added damping and stiffness element, 164
- Adjustment factor, A-231
  - wood, 155
- Alaska earthquake, *20*, 55
- Allowable
  - connector strength, 155
  - shear stress, masonry, 147
  - stress, 105
  - stress, design, 56
  - stress, method, 105
- Alluvium, 54
- Alum Rock earthquake, A-216
- Amplification
  - factor, component, 96
  - factor, seismic force, 63, 74
  - soil, 59
- Analysis
  - dynamic, 23, 104, 203
  - Fourier, *16*
  - static, 23
- Anchorage (*see also* Connection)
  - to concrete wall, 131
- Angular frequency, 26
- Architectural
  - considerations, 164
  - failure, *43*
- Area, projected, method, 56
- Arvin-Tehachapi earthquake, A-215
- Attachments, 95
- Attenuation, 12
  - equation, 12
  - ground motion, 14
- Authority, 199
- Bandages, 165
- Base, A-212
  - isolation, 161
  - shear, 21, 31, 57
  - shear, calculating, 80
  - shear, coefficient, 51
  - shear, distribution, 85, 87
- Bay length, 143
- Bays, number in a shear wall, 66
- Beam, 110, 114
  - center link, 144
  - column, concrete, 135
  - hinge failure mode, 205
  - link, 143
- Beams, concrete, 132
- Bearing
  - isolation, 161
  - wall system, 64, 171, A-212
- Belting, 165
- Bending, cross-grain, 156
- Bent action, 43
- Blocking, 114, 153
- Blue Book, 53, *72*
- Body-friction damping, 27
- Bolt
  - dimensions, A-232
  - lag, dimensions, A-233
  - shear, design value, A-236–A-240
- Bolted connection, 140
- Bolts, 154
- Boundary elements, concrete, 131
- Box system (*see also* Bearing wall system), 171
- Brace, 114
- Braced
  - frame, 64, 142, A-212
  - frame, eccentric, 143
  - tube building, 49
- Bracing
  - diagonal, 142
  - K-, 142
  - V-, 142
  - X-, 45, 139, 142
- Bridge, 54, *100*, 201
  - period, 54
- Bridging, 114
- Building
  - Code, International, 54
  - composite, 49
  - damping ratio, 28
  - frame system, 64
  - high-rise, 49, 170
  - irregular, 68, 202
  - mass, 77
  - period, 21, 72
  - regular, 68
  - rigid frame, 49
  - separation, 92
  - tube, 14, 49
  - tube-in-tube, 49
  - weight, 77
- Bulge, Palmdale, *16*
- Bullion Mountains earthquake, A-216
- Calibration earthquake, 11
- California
  - Administrative Code, 53
  - concrete, 129
  - earthquake, 1
  - earthquakes, A-215, A-216
  - faults, 5, 6

- CALTRANS, 54, 201
- Cantilever
  - displacement, 43
  - method, 124
  - pier, 25
- Capacity, distributed excess, 169
- Carbon fiber, 165
- Category
  - occupancy, 58
  - seismic design, 63
- Center link, 143
  - beam, 144
- Center of mass, 45, 89
- Center of rigidity, 45
- Characteristics,
  - earthquake, 17
  - site, 17
  - spectral, 21
  - structural, 17
- Chile earthquake, 15
- Chimney, 100
- Chord, 117, A-212
  - active, 117
  - drift, 43
  - force, 118
  - passive, 117
  - size, 118
- Chord-splice slip, 116
- Circular frequency, 26
- Cladding, 96
- Closed tie, 176
- CMU (*see also* Concrete masonry unit)
  - connection to, 206, 207
- Code, 53
  - International Building, 54
- Coefficient
  - base shear, 51
  - damping, 28
  - damping, critical, 28
  - design, A-221
  - seismic response, 60, 78
  - site, 61
  - stability, 45, 93
- Collector, 114, A-212
  - element, concrete, 130
  - force, 114
- Column
  - concrete, 135
  - flexible diaphragm, 115
  - steel, 138
  - retrofit, 165
- Column-girder joint
  - restraint, 141
  - steel, 208
- Column-hinge failure mode, 205
- Combination
  - CQC, 33
  - load, 74
  - SRSS, 33
- Combinations
  - load, masonry, 145
  - loads, steel, 137
- Combined
  - load, 57
  - loadings, 132
- Compatibility, deformation, 103
- Complete quadratic combination, 33
- Compliance, 24
- Component
  - amplification factor, 96
  - nonstructural, 95
  - response modification factor, 96
- Composite building, 49
- Compression wave, 7
- Concrete
  - California, 129
  - confined, 175, A-212
  - construction, 129
  - ductile, 129, 175
  - masonry unit, 146
  - pedestal, 104
  - properties, 25
  - special, 129, 175
  - strength, 132
  - wall, anchorage to, 131
- Configuration, 68
- Confined concrete, 175, A-212
- Confinement, concrete, 129
- Connection
  - between portions, 100
  - bolted, 140
  - diaphragm-wall, 155
  - dry, 130
  - mechanical, 134
  - to CMU, 206, 207
  - type I, 137
  - type II, 138
  - welded, 140
  - wet, 130
- Connections to concrete wall, 131
- Connector strength, 154
  - allowable, 155
  - nominal, 155
- Considered earthquake, maximum, 20
- Constant
  - Lame's, 8
  - spring, 24
- Construction
  - concrete, 129
  - cost, 204
  - flexible diaphragm, 115
  - masonry, 145
  - steel, 137
  - tilt-up, 159
  - wood, 149
- Content, frequency, 16
- Continental drift, 2
- Continuity, 100
  - concrete, 129
  - plate, 139
  - ties, 153, 154
- Conversion factors, A-211
- Cost of construction, 204
- Coulomb friction, 27
- Counter, scintillation, 16
- Crawl space, 157
- Credible earthquake, maximum, 54
- Creep, 7
  - fault, A-212
  - tectonic, A-214
- Creepmeter, 16
- Cripple wall, 157
- Criteria
  - life-safety, 55
  - survivability, 54
- Critical damping, 28, 170, A-212
  - coefficient, 28
- Critically damped system, 28
- Cross-grain
  - bending, 156
  - tension, 156
- Crosstie, 131
  - supplementary, A-214
- Crust, ocean, 2
- Dam, 100
- Damage, 17
- Damped period, 29
- Damper
  - active mass, 163
  - friction, 163
  - passive, 163
  - tuned mass, 163
  - visco-elastic, 163
- Dampers, 27
- Damping, 27, A-212
  - body-friction, 27
  - coefficient, 28
  - critical, 28, 170, A-212
  - external viscous, 27
  - hysteresis, 28, 41
  - internal viscous, 27, 28
  - ratio, 28, 170, 171, 205
  - ratio, building, 28
  - ratio, seismometer, 15
  - radiation, 27
  - system, 163
- Dashpot, 27
- Dead load, 74, 77
- Decay
  - decrement, 28
  - envelope, 28
- Decoupling, 161
- Decrement
  - decay, 28
  - logarithmic, 28
- Deep earthquake, 2
- Definitions, A-212
- Deflection
  - diaphragm, 116, 117
  - permissible, wood, 149
  - static, 24, 29
- Deformation
  - compatibility, 103, 104
  - concrete, 130
  - reversal, 41
- Degree of freedom, 24
  - multiple, 32
  - single, 21, 24
- Depth
  - diaphragm, 116
  - focal, 1
- Design
  - allowable stress, 56
  - coefficient, A-221
  - criteria, survivability, 54
  - displacement, 163
  - ductility factor, 42
  - eccentricity, 89
  - load, 74
  - load and resistance factor design, 56
  - procedure, seismic, 57
  - redundant, 169
  - response spectrum, 38, 42
  - inelastic, 41, 42
  - service level stress, 56
  - shear, nail, A-230
  - ultimate strength, 56
  - value, shear, bolt, A-236–A-240
  - working stress, 56
- Diagonal
  - bracing, 142
  - sheathing, 149
- Diaphragm, 107
  - action, 107
  - concrete, 136
  - deflection, 116, 117
  - depth, 116
  - factor, 155
  - flexible, 45, 71, 114, 203
  - force, 107, 108
  - horizontal, 107

- irregularity, 71
- normal stress, 116
- opening, 156
- ratio, 117, 153, 203
- rigid, 45, 109
- shear stress, 115
- span, 116
- wall connection, 155
- Dilatation, 7
- Dilatational source theory, 1
- Dilatometer, 16
- Dimensions
  - bolts, A-232
  - lag screws, A-233
  - nails, A-234
  - wood screws, A-234
- Dip, A-212
  - slip, A-212
  - slip fault, 5
- Direction, earthquake, 88
- Discontinuity, in-plane, 70
- Displacement, 12
  - cantilever, 43
  - design, 163
  - ductility, 40
  - fault, A-212
  - maximum inelastic response, 44, 89
  - spectral, 21
- Dissipation, energy, system, 161
- Distortion
  - flexural, 116
  - nail, 116
  - shear, 116
- Distributed excess capacity, 169
- Distribution
  - of base shear, 85, 87
  - Poisson, 14
- Doubler plate, 139, 177, A-212
- Dowel-type fastener, A-232
- Drag strut, 114
- Drift, 43, 169
  - chord, 43
  - continental, 2
  - limit, 26, 43, 173
  - limitation, 89, 90
  - maximum, total, 89, 90
  - shear, 43
  - story, 35, 43
  - story, maximum, 89, 90
  - ratio, interstory, maximum, 163
- Dry connection, 130
- Dual system, 65
- Ductile
  - concrete, 129, 175
  - frame, 164
  - framing, 169
  - moment-resisting frame, 171, 138, A-212
- Ductility, 40, 63, 168
  - displacement, 40
  - factor, 40–42, 168, 169
  - factor, design, 42
  - risk reduction factor, 54
  - swing, 41
- Duhamel's integral, 30
- Duration of shaking, 16
- Dynamic analysis, 23, 104, 203
  - lateral-force procedure, 80
  - procedure, 104
- Earthquake
  - 50-year, 44
  - Alaska, 20, 55
  - Alum Rock, A-216
  - Arvin-Tehachapi, A-215
  - Bullion Mountains, A-216
  - calibration, 11
  - California, 1
  - characteristics, 17
  - Chile, 15
  - deep, 2
  - direction, 88
  - energy release, 4
  - El Centro, 15, 39, 51, A-215, A-219
  - generation, 1
  - Gorda Plate, A-216
  - great, 4, 10
  - Hector Mine, A-216
  - Imperial Valley, 52, A-215
  - intermediate, 1
  - Kern County, A-215
  - Kobe, 52
  - Loma Prieta, 15, 16, 20, 30, 37, 52, 59, A-215
  - load, 74
  - Long Beach, 51, A-215
  - major, 167
  - maximum, considered, 20
  - maximum, credible, 54
  - maximum, probable, 20
  - Mexico City, 15, 20, 30, 55, 59
  - moderate, 10
  - Napa, A-216
  - nature of, 1
  - Niigata, 20, 55
  - Northridge, 52, 147, A-216, A-241
  - oblique, 88
  - Parkfield, 52, A-215
  - prediction, 16
  - San Fernando, 53, A-215
  - San Francisco, A-215
  - San Simeon, A-216
  - Santa Barbara, 31, 51, A-215
  - shallow, 1, 4
  - Sylmar, A-215
  - Whittier, A-215
  - Yountville, A-216
- Earthquakes, California, A-215, A-216
- EBF, 143
- Eccentric braced frame, 143
- Eccentricity, 45
  - accidental, 46
  - design, 89
- Edge nailing, 153, A-212
- Effect
  - P-delta, 44, 45, 97, 169
  - secondary, 44
- Effective
  - peak ground acceleration, 15, 20, 20
  - peak velocity, 20
  - seismic weight, 78
  - stress, 21
- El Centro earthquake, 15, 39, 51, A-215, A-219
- Elastic
  - rebound theory, 1, A-212
  - response, 37
  - response spectra, 37
- Elasticity, modulus of, 25
- Element
  - added damping and stiffness, 164
  - horizontal, 201
  - vertical, 201
- Elements of a structure, 95
- End-grain factor, 155
- End link, 143
- EBF, 143
- Energy
  - dissipation system, 161
  - release, 11
  - earthquake, 4
  - reserve, A-213
  - strain, 1, 4, 41
- Engineer, geotechnical, 201
- Engineering authority, 199
- Envelope, decay, 28
- EPA, 15, 20
- Epicenter, 1
  - locating, 8
- Equation (*see also* Formula)
  - attenuation, 12
- Equipment, 95
- Equivalent lateral force, 23
  - procedure, 57
  - static, force, 51
  - static, lateral-force procedure, 80, 83
  - static, load, A-212
- Essential facility, 58, 59, A-212
- Estimated maximum earthquake force, 74
- Exterior cladding panel, 96
- External viscous damping, 27
- Extreme soft story, 69
- Facility
  - essential, 58, 59, A-212
  - hazardous, 58, 59
  - standard occupancy, 59
- Factor
  - adjustment, A-231
  - adjustment, wood, 155
  - amplification, component, 99
  - amplification, seismic force, 63, 74
  - component modification, 96
  - design ductility, 42
  - diaphragm, 155
  - ductility, 40–42, 168, 169
  - ductility, risk reduction, 54
  - end-grain, 155
  - importance, seismic, 59
  - load duration, 155
  - magnification, 29
  - mode shape, 34
  - near-source, 60
  - overstrength, 63
  - participation, 35
  - reliability/redundancy, 60, 66
  - response modification, 63
  - scale, 39
  - strength reduction, 131
  - structure deflection ductility, 42
  - temperature, 155
  - toe-nail, 155
- Factors, conversion, 211
- Failure
  - architectural, 43
  - beam-hinge mode, 205
  - column-hinge mode, 205
  - weak beam mode, 205
  - weak column mode, 205
  - weak story mode, 205
- Fascia, 204
- Fault, 4, A-212
  - active, 12
  - creep, A-212
  - dip-slip, 5
  - displacement, A-212
  - gouge, A-212
  - left-lateral, 5
  - major, 201
  - normal, A-213

- oblique, 5
- reverse, 5, A-213
- right-lateral, 5
- sag, A-212
- San Andreas, 5
- scarp, A-212
- slip (*see* Slip)
- strike-slip, 5, A-213
- thrust, 5
- transcurrent, A-214
- wrench, 5, A-214
- Faults, California, 5, 6
- Fiber
  - carbon, 165
  - Kevlar, 165
- Field Act, 51
- Field nailing, 153, A-212
- Fire, ring of, 2
- First mode, 32
- Fixed pier, 24
- Flat-bottom tank, 100
- Flexibility, 24, 168
- Flexible diaphragm, 45, 71, 114, 203
  - column, 115
  - construction, 115
  - torsion, 115
- Flexural
  - distortion, 116
  - members, concrete, 132
- Floor
  - force, 35
  - live load, 74
- Focal depth, 1
- Focus, 1
- Force
  - chord, 118
  - collector, 114
  - diaphragm, 107, 108
  - equivalent lateral, 23
  - floor, 35
  - normal, method, 56
  - seismic, 21, 93
  - seismic, amplification factor, 63, 74
  - story, 85
  - top, 85, 93
  - wall, 108
- Forced system, 29
- Forcing function, 29
- Formula (*see also* Equation)
  - recurrence, 14
- Fourier analysis, 16
- Fracture, A-212
  - zone, Mendocino, 7
- Frame, 64, A-212
  - braced, 64, 142, A-212
  - building, system, 64
  - concrete, 130
  - ductile, 164
  - dictile, moment-resisting, 171, A-212
  - eccentric braced, 143
  - intermediate moment-resisting, 65
  - member sizing, 126
  - members, concrete, 132
  - moment-resisting, 64, 171, A-213
  - ordinary moment, 138
  - ordinary moment-resisting, 65
  - rigid, A-213
  - space, 64, A-213
  - special, ductile, A-213
  - special, moment-resisting, 65, 139, 171
  - steel, 137
  - vertical load-carrying, 64
- Framed tube, 49
- Framing
  - ductile, 169
  - wood, 150
- Freedom
  - degree of, 24
  - multiple degree of, 32
- Frequency, 25, 171
  - angular, 26
  - circular, 26
  - content, 16
  - occurrence, 14
- Friction
  - damper, 163
  - Coulomb, 27
- Function
  - forcing, 29
  - impulse, 29
  - step, 29
- Fundamental
  - mode, 32
  - period, structure, 78
- Gauge
  - resistivity, 16
  - strain, 16
- Generation, earthquake, 1
- Geometric irregularity, vertical, 70
- Geotechnical engineer, 201
- Girder, 114
  - column joint
  - column joint, restraint, 141
  - column joint, steel, 139
  - open-web, 164
  - quadrangular, 164
  - transfer, 13
  - Vierendeel, 164
- Global seismicity, 2
- Glomar Challenger, 2
- Gorda Plate earthquake, A-216
- Gouge, A-212
  - fault, A-212
- Governing load, 57
- Graben, A-212
- Graph, log tripartite, 39
- Great earthquake, 4, 10
- Ground
  - acceleration, peak, 12
  - acceleration, vertical, 88
  - motion attenuation, 14
  - supported tank, 100
- Harmonic
  - motion, simple, 23
  - oscillator, simple, 24
- Hazardous facility, 58, 59
- Hector Mine earthquake, A-216
- Hex lag screws, dimensions, A-233
- High-rise building, 49, 170
- Hinge, plastic, 171, A-213
- Holdown, A-212, A-225
- Holzer method, 35
- Hook, seismic, A-213
- Hooke's law, 1, 24
- Hooks, seismic, 131
- Hoop, 131, 176, A-212
- Horizon, soil, 59
- Horizontal
  - diaphragm, 107
  - earthquake load, 74
  - element, 201
  - structural irregularity, 71
- Hypocenter, 1, A-212
  - locating, 8
- Hypothesis (*see also* Theory)
  - seismic bay, 16
- Hysteresis
  - damping, 28, 41
  - loop, 41
- Hysteretic damping, 41
- ICC, 53
- Igneous rock, A-212
- Imperial Valley earthquake, 52, A-215
- Importance factor, seismic, 59
- Impulse, 30
  - function, 29
  - response, 30
- Inelastic
  - design response spectrum, 41, 42
  - region, 41
  - response displacement, 89
  - response displacement, maximum, 44
  - response spectra, 41
- Inertia, polar moment of, 46
- In-plane discontinuity, 70
- Inspection
  - special, A-213
  - special, masonry, 145
- In-structure component amplification
  - factor, 96
- Integral, Duhamel's, 30
- Intensity, 9, A-213
  - scale, Mercalli, 9
- Interaction, shear wall-frame, system, 66
- Intermediate
  - earthquake, 1
  - moment-resisting frame, 65
- Internal viscous damping, 27, 28
- International
  - Building Code, 53, 54
  - Code Council, 53
- Interstory drift ratio, maximum, 163
- Interval, recurrence, 39
- Inverted pendulum building system, 65
- Irregular building, 68, 202
- Irregularity
  - diaphragm, 71
  - horizontal, 71
  - mass, 70
  - penalty, 104
  - plan, 71
  - reentrant corner, 71
  - torsional, 71
  - vertical, 68, 69
  - vertical, geometric, 70
  - weight, 70
- Isolation
  - bearing, 161
  - base, 161
  - seismic, 163
- Isoseismal, A-213
  - map, 10
- Jacket, steel, 165
- Joint
  - column, 136
  - girder-column, steel, 139
  - shear, A-213
- Joist, 114, 156
- K-bracing, 142
- Kern County earthquake, A-215
- Kevlar fiber, 165
- Kobe earthquake, 52

- Lag screws, dimensions, A-233  
Lame's constant, 8  
Landslide, 201  
Lap splice, tension, 133  
Laser, 16  
Lateral force  
  equivalent, 23  
  procedure, 80  
  procedure, simplified, 84  
  -resisting system, A-213  
Law  
  Hooke's, 1, 24  
  Newton's second, 20  
Ledger, 117, 155  
Left  
  -lateral fault, 5  
  -normal slip, A-213  
  slip, A-213  
Length  
  active fault, 12  
  bay, 143  
  fault slip, 12  
  story, 70  
Life-safety criteria, 55  
Limit  
  drift, 26, 43, 173  
  Richter magnitude, 167  
  upper, magnitude, 10  
Limitation, drift, 89, 90  
Linear natural frequency, 25  
Link, 143  
  beam, 143  
  center, 143  
  end, 143  
Liquefaction, 20, 201, A-213  
Lithosphere, 2  
Live load  
  floor, 74  
  roof, 74  
Load (*see also type*)  
  combination, 74  
  combinations, masonry, 145  
  combinations, steel, 137  
  combined, 57  
  duration factor, 155  
  paths, multiple, 169  
  resistance factor design, 56  
  dead, 74  
  design, 74  
  earthquake, 74  
  equivalent static, A-212  
  governing, 57  
  horizontal, earthquake, 74  
  roof, 57  
  snow, 56, 74  
  vertical, earthquake, 74  
  wind, 56, 74  
Loading, wind, 51  
Loadings, combined, 132  
Log tripartite graph, 39  
Logarithmic decrement, 28  
Loma Prieta earthquake, 15, 16, 20, 30, 37, 52, 59, A-215  
Long Beach earthquake, 51, A-215  
Long period transition period, 78  
Longitudinal wave, 7  
Loop, hysteresis, 41  
Love wave, 8  
LRFD, 56  
Lumped mass, 24  
L-wave, 8  
Magnetite, 2  
Magnetometer, 15  
Magnification factor, 29  
Magnitude, 9  
  limit, Richter, 167  
  Richter, 10, 11  
  upper limit, 10  
Major  
  earthquake, 167  
  fault, 201  
Map, isoseismal, 10  
Mapped spectral acceleration, 61  
Masonry  
  allowable shear stress, 147  
  construction, 145  
  load combinations, 145  
  moment-resisting wall frame, 146  
  unit, concrete, 146  
  wall, anchorage to, 131  
  properties, 25  
Mass, 77  
  center of, 45, 89  
  damper, active, 163  
  irregularity, 70  
  lumped, 24  
Maximum  
  considered earthquake, 20  
  credible earthquake, 54  
  earthquake force, estimated, 74  
  inelastic response displacement, 44, 89  
  interstory drift ratio, 163  
  probable earthquake, 20  
  total drift, 89, 90  
MDOF system, 32  
Mechanical connection, 134  
Member  
  sizing, 126  
  strength, 138  
Mendocino fracture zone, 7  
Mercalli Intensity scale, 9  
Method  
  A, 72  
  allowable stress, 105  
  B, 73  
  cantilever, 124  
  CQC, 33  
  Holzer, 35  
  normal force, 56  
  portal, 123, 170  
  projected area, 56  
  Rayleigh, 34, 73, 170  
  spurr, 126  
  SRSS, 33  
  Stodola, 35  
Mexico City earthquake, 15, 20, 30, 55, 59  
Microearthquake, 10  
Microzone, 17  
Microzonification, 20  
Mid-ocean (*see also* Submarine)  
  ridges, 2  
MM scale, 9  
MMI, 9  
Mode, 32  
  shape, 32, 34, 35  
  shape, factor, 34  
  first, 32  
  fundamental, 32  
Moderate earthquake, 10  
Modification factor, response, 63  
Modified Mercalli Intensity scale, 9  
Modulus of  
  elasticity, 25  
  resilience, 41  
  rupture, 41  
  toughness, 41  
Moment  
  -frame, truss, special, 139  
  of inertia, polar, 46  
  overturning, 45, 48, 93, 118  
  primary, 45  
  -resisting frame, 64, 171, A-213  
  -resisting frame, intermediate, 65  
  -resisting frame, ordinary, 65  
  -resisting frame, special, 65, 138, 139  
  -resisting wall frame, masonry, 146  
  restoring, 45  
  secondary, 45  
Mortar types, 146  
Motion  
  attenuation, 14  
  simple harmonic, 23  
Mountain, San Gabriel, 5  
Multiple  
  degree of freedom, 32  
  load paths, 169  
Nail  
  design shear, A-230  
  distortion, 116  
  slip, 117  
  withdrawal strength, A-235  
Nailer, 155  
Nailing  
  edge, 153, A-212  
  field, 153, A-212  
Nails, 154  
  dimensions, A-234  
Napa earthquake, A-215  
Natural  
  frequency, 25  
  period, 21, 25, 169  
Nature of earthquake, 1  
Near-source factor, 60  
Negative torsional shear stress, 47, 170  
NEHRP, 53  
Newton's second law, 21  
Niigata earthquake, 20, 55  
Nominal connector strength, 155  
Nonbuilding structure, 100  
  rigid, 100  
Nonparallel system, 71  
Nonstructural component, 95  
Normal  
  fault, A-213  
  force method, 56  
  slip, A-213  
  stress, diaphragm, 116  
Normalized response spectrum, 42  
Northridge earthquake, 52, 147, A-216, A-241  
Oblique  
  earthquake, 88  
  fault, 5  
  slip, A-213  
Observation, structural, A-213  
Occupancy category, 58  
Occurrence  
  frequency, 14  
  probability, 14  
Offset, out-of-plane, 71  
Offshore platform, 100  
Opening, diaphragm, 156  
Openings, stacked, 108  
Open-web girder, 164

- Ordinary
  - moment frame, 138
  - moment-resisting frame, 65
- Orthogonal effect, concrete, 130
- Oscillator, 26
  - simple harmonic, 24
- OTM, 48
- Out-of-plane offset, 71
- Overdamped system, 28
- Overstrength, 63
  - factor, 63
- Overturning moment, 45, 48, 93, 118
  
- Paleoclimatology, 2
- Paleomagnetism, 2
- Palmdale bulge, 16
- Panel
  - cladding, exterior, 96
  - zone, 139, A-213
- Parapet, 109, A-213
- Parkfield earthquake, 52, A-215
- Part, force on, 95
- Participation factor, 35
- Particleboard, 150
- Parts and portions, 95
- Pass, Tejon, 7
- Passive
  - chord, 117
  - damper, 163
- P*-delta effect, 44, 45, 93, 169
- Peak ground acceleration, 12, 20
  - effective, 15, 20
- Peak velocity, effective, 20
- Pedestal, concrete, 104
- Penalty, structural irregularity, 104
- Pendulum, inverted, 65
- Penetration, standard, 59
- Period
  - acceleration, 78
  - bridge, 54
  - building, 21
  - building, 72
  - damped, 29
  - fundamental, structure, 78
  - long period transition, 78
  - natural, 21, 25, 169
  - site, 20
  - soil, 20
  - velocity response, 78
- Permissible deflection, wood, 149
- PGA, 12
- Pier, 24, 25, 110
  - cantilever, 25
  - fixed, 24
  - wall, 160
- Piers, rigidity, A-217, A-218
- Pilaster, 118
- Plan irregularity, 71
- Plastic hinge, 171, A-213
- Plate
  - continuity, 139
  - doubler, 139, 177, A-212
  - sill, A-213
  - size, 139
  - tectonics, 2, 3
- Plates, 2
- Plywood (*see* Wood structural panel)
- Poisson distribution, 14
- Polar moment of inertia, 46
- Pond, sag, A-213
- Pore pressure, 20
- Portal method, 123, 170
- Portion, force on, 95
- Pounding, 202
- Prediction, earthquake, 16
  - displacement, maximum inelastic, 89
  - elastic, 37
  - modification factor, 63
  - modification factor, component, 96
  - spectra, 39
  - spectra, elastic, 37
  - spectra, inelastic, 41
  - spectrum, 37, 170
  - spectrum, design, 38, 42
  - to impulse, 30
- Premonitory sign, 16
- Pressure
  - pore, 20
  - wind, 56
- Primary
  - moment, 45
  - stress, 201
  - wave, 7
- Probability, occurrence, 14
- Probable earthquake, maximum, 20
- Procedure
  - dynamic analysis, 104
  - equivalent lateral force, 57
  - lateral force, 80
  - lateral force, simplified, 84
  - seismic design, 57
  - simplified lateral-force, 80, 84
  - static lateral force, 57
- Profile, soil, 43, 59
- Projected area method, 56
- Properties
  - concrete, 25
  - masonry, 25
  - steel, 25, 138
- Protected zone, 141
- Pseudo acceleration, spectral, 21
- Pure tube building, 49
- Purlin, 114, 156
- P*-wave, 7, 16
  
- Quadrangular girder, 164
- Quadratic combination, 33
  
- Radiation damping, 27
- Radio wave, ultra-low frequency, 16
- Radon, 16
- Ratio
  - damping, 28, 170, 171, 205
  - damping, building, 28
  - diaphragm, 117, 153, 203
  - story drift, 44
  - strength, 139
  - width-thickness, 142
- Rayleigh
  - method, 34, 73, 170
  - wave, 8
- Rebound theory, elastic, 1
- Recommended lateral force requirements, 53
- Recurrence
  - formula, 14
  - interval, 39
- Reduction factor, strength, 131
- Redundancy, 66, 67, 169, 119
  - factor, 66
- Redundant design, 169
- Reentrant corner irregularity, 71
- Region, inelastic, 41
- Regular building, 68
- Reinforcement
  - bottom, 133
  - masonry, 146
  - steel, 132
- Reinforcement, top, 133
- Relative rigidity, 24, 110, 168
- Release, energy, 11
- Reliability/redundancy factor, 60, 66
- Reserve energy, A-213
- Resilience, modulus, 41
- Resistivity gauge, 16
- Resonance, 20, 30, 37, A-213
- Response, 32, 37
  - coefficient, 42, 43
  - coefficient, seismic, 60, 78
- Restoring moment, 45
- Restraint, joint, girder-column, 141
- Retrofit, 165
  - column, 165
- Reversal deformation, 41
- Reverse fault, 5, A-213
- Richter magnitude, 10, 11
  - limit, 167
- Ridges
  - mid-ocean, 2
  - submarine, 2, 3
- Right
  - slip, A-213
  - lateral fault, 5
  - normal slip, A-213
- Rigid
  - diaphragm, 45, 109
  - frame, 49, A-213
  - frame, building, 49
  - nonbuilding structure, 100
- Rigidity, 24, 110, 168,
  - center of, 45
  - of piers, A-217, A-218
  - relative, 24, 110, 168
- Riley Act, 51
- Ring of fire, 2
- Risk
  - microzone, 17
  - reduction factor, ductility, 54
  - zone, 17
- Rock, igneous, A-212
- Roof
  - live load, 74
  - load, 57
- Rossi-Forel scale, 9
- Rupture, modulus of, 41
  
- Sag
  - fault, A-212
  - pond, A-213
- Salton Sea, 7
- San
  - Andreas fault, 5
  - Fernando earthquake, 53, A-215
  - Francisco earthquake, A-215
  - Gabriel Mountains, 5
  - Simeon earthquake, A-216
- Santa Barbara earthquake, 31, 51, A-215
- Scale
  - factor, 39
  - intensity, 9
  - MM, 9
  - Rossi-Forel, 9
- Scaling factor, 104
- Scarp, fault, A-212
- Scintillation counter, 16
- Screws, wood, dimensions, A-234
- SDOF system, 21, 24
- Sea
  - Salton, 7
  - wave, 4
- Seafloor spreading, 2

- Secondary
  - effect, 44
  - moment, 45
  - stress, 201
  - wave, 8
- Segment, special, 139
- Seismic
  - acronyms, A-220
  - bay hypothesis, 16
  - design, category, 63
  - design, procedure, 57
  - force, 21
  - force, amplification factor, 63, 74
  - force, of parts, 95
  - hook, A-213
  - importance factor, 59
  - isolation, 163
  - response coefficient, 60, 78
  - sea wave, 4
  - wave, 1, 7
  - weight, effective, 78
  - zone, 17
- Seismicity, global, 2
- Seismogram, 15
- Seismograph, 15
- Seismometer, 15
  - damping ratio, 15
- Separation, building, 92
- Service level stress design, 56
- Setback, 205
- Settlement, 201
- SH wave, 13
- Shaking
  - duration, 16
  - strong-phase, 12
- Shallow earthquake, 1, 4
- Shape, mode, 32, 34, 35
- Shear
  - base, 21, 31, 57
  - base, calculating, 80
  - design, nail, A-230
  - design value, bolt, A-236–A-240
  - distortion, 116
  - drift, 43
  - joint, A-213
  - story, 35, 85
  - strength, soil, 21
  - strength, undrained, 59
  - stress, allowable, masonry, 147
  - stress, diaphragm, 115
  - negative torsional, 47, 170
  - torsional, 45, 170
  - wall, 64, A-213
  - wall-frame interaction system, 66
  - wall, masonry, 146
  - wall, number of bays, 66
  - wall, special, A-213
  - wall, wood structural panel, 151
  - wave, 8
  - wave, velocity, 59
- Sheathing, 114
  - diagonal, 149
- Short period mapped spectral acceleration, 61
- SidePlate, 139
  - connection technology, 139
- Sign, 100
  - premonitory, 16
- Sill, 155
  - plate, A-213
- Silo, 100
- Simple harmonic motion, 23
- oscillator, 24
- Simplified lateral force procedure, 80, 84
- Simpson Strong-Tie Company, A-225–A-229
- Single degree of freedom, 21, 24
- Site
  - characteristics, 17
  - coefficient, 61
  - period, 20
- Size, chord, 118
- Sizing frame members, 126
- Skyscraper (*see* High-rise building)
- Slip, 2, 5, 10, A-213
  - chord-splice, 116
  - dip, A-212
  - left, A-213
  - left-normal, A-213
  - length, 12
  - nail, 117
  - normal, A-213
  - oblique, A-213
  - right, A-213
  - right-normal, A-213
- Sloshing, 102
- Snow load, 56, 74
- Soft story, 69, 202
  - extreme, 69
- Soil
  - horizon, 59
  - liquefaction, 20
  - period, 20
  - profile, 43, 59
  - shear strength, 21
  - type, 59
- Source theory, dilatational, 1
- Space
  - crawl, 157
  - frame, 64, A-213
  - frame, ductile moment-resisting, 138
- Span, diaphragm, 116
- Special
  - concrete, 129, 175
  - ductile frame, A-213
  - inspection, A-213
  - inspection, masonry, 145
  - moment-resisting frame, 65, 138, 171
  - segment, 139
  - shear wall, A-213
  - truss moment-frame, 139
- Specification for Structural Steel Buildings, 56
- Spectra
  - elastic response, 37
  - response, 39
  - response, inelastic, 41
- Spectral
  - acceleration, 21, 37
  - acceleration, mapped, 61
  - characteristics, 21
  - displacement, 21
  - pseudo acceleration, 21
  - velocity, 21
- Spectrum
  - design response, 42
  - response, 37, 170
- Spike (*see* Nail)
- Splice
  - tension lap, 133
  - welded, 134
- Spreading, seafloor, 2
- Spring constant, 24
- Spurr method, 126
- Square root of the sum of the squares, 33
- SRSS method, 33
- Stability coefficient, 45, 93
- Stacked openings, 108
- Standard penetration, 59
- Static
  - analysis, 23
  - deflection, 24, 29
  - force, equivalent, 51
  - lateral-force procedure, 57, 80, 83
- Static (equivalent) lateral-force procedure, 80, 83
- Steel
  - column, 138
  - construction, 137
  - frame, 137
  - jacket, 165
  - properties, 25, 138
  - reinforcement, 132
  - masonry, 146
  - stud wall system, 144
- Step function, 29
- Stiffness, 24, 168
- Stirrup tie, A-213
- Stodola method, 35
- Story
  - drift, 35, 43, 89
  - drift ratio, 144
  - extreme soft, 69
  - force, 85
  - length, 70
  - shear, 35, 85
  - soft, 69, 202
  - weak, 70, 202
- Strain
  - energy, 1, 4, 41
  - gauge, 16
- Strap, A-225–A-229
- Strength
  - allowable, connector, 155
  - concrete, 132
  - design, 56
  - maximum masonry, 146
  - member, 138
  - nominal, connector, 155
  - ratio, 139
  - reduction factor, 131
  - shear strength, soil, 21
  - shear, undrained, 59
- Stress
  - allowable, 105
  - effective, 21
  - normal, diaphragm, 116
  - primary, 201
  - secondary, 201
  - shear, diaphragm, 115
  - shear, negative torsional, 47
  - torsional shear, 45, 170
  - wall, shear, 108
- Strike, A-213
- Strike-slip, A-213
  - fault, 5, A-213
- Strong motion seismometer, 15
- Strong phase, 15
- Strong-phase shaking, 12
- Structural
  - characteristics, 17
  - irregularity, 68
  - irregularity, penalty, 104
  - observation, A-213
  - regularity, 68
  - system, 64, 202
  - deflection ductility factor, 42

- Structure
  - element of, 95
  - miscellaneous, 59
  - nonbuilding, 100
  - nonbuilding, rigid, 104
- Strut, 114
  - drag, 114
- Stud, steel, wall system, 144
- Subdiaphragm, 118, 153
- Subduction, 3
  - zone, 2
- Submarine
  - ridges, 2, 3
  - trenches, 2, 3
- Sub-purlin, 114
- Subsidence, 201
- Sum of the squares method, 32
- Supplementary crosstie, A-214
- Surface wave, 8
- Survivability design criteria, 54
- SV wave, 13
- S-wave, 8
- Swing, ductility, 41
- Sylmar earthquake, A-215
- Symbols, welding, A-224
- System
  - active pulse, 164
  - active tendon, 164
  - bearing wall, 64, 171, A-212
  - box, 171, A-212
  - building frame, 64
  - critically damped, 28
  - damping, 163
  - dual, 65
  - energy dissipation, 161
  - forced, 29
  - interaction shear wall-frame, 66
  - lateral force-resisting, A-213
  - MDOF, 32
  - nonparallel, 71
  - overdamped, 28
  - SDOF, 21, 24
  - structural, 64, 202
  - undefined structural, 66
  - underdamped, 28
- Tank, 100, 204
  - uplift, 102
- Tectonic, A-214
  - creep, A-214
- Tectonics, 2, 3
  - plate, 2
- Tejon Pass, 7
- Temperature factor, 155
- Tension
  - cross-grain, 156
  - lap splice, 133
- Theory (*see also* Hypothesis)
  - dilatational source, 1
  - elastic rebound, 1, A-212
- Thrust fault, 5
- Tidal wave, 4
- Tie, 100, 114, A-225–A-229
  - closed, 176
  - stirrup, A-213
- Tierod, 208
- Ties
  - concrete, 130
  - continuity, 153, 154
- Tiltmeter, 15
- Tilt-up construction, 159
- Title, 24, 53
- Toe-nail factor, 155
- Toe-nailing, 153, 154
- Top force, 85, 93
- Torsion, 89
  - accidental, 89
  - flexible diaphragm, 115
- Torsional
  - irregularity, 71
  - shear stress, 45, 170
  - shear stress, negative, 47, 170
- Total seismic dead load, 77
- Toughness, modulus of, 41
- Tower, 100
- Transcurrent fault, A-214
- Transfer girder, 13
- Transition period, long period, 78
- Transverse
  - wall, 109
  - wave, 8
- Trenches, submarine, 2, 3
- Tripartite graph, log, 39
- Truss
  - moment-frame, special, 139
  - Vierendeel, 139
- Tsunami, 4
- Tube
  - building, 14, 49
  - framed, 49
  - in-tube building, 49
- Tuned
  - damper, 163
  - mass damper, 163
- Type
  - (a) EBF, 143
  - (b) EBF, 144
  - I connection, 137
  - II connection, 138
  - soil, 59
- UBC, 53
- ULF radio wave, 16
- Ultimate strength design, 56
- Ultra-low frequency radio wave, 16
- Undefined structural system, 66
- Underdamped system, 28
- Undrained shear strength, 59
- Uniform Building Code, 53
- Unit, concrete masonry, 146
- Uplift, 93
- Uplift, tank, 102
- Upper limit, magnitude, 10
- V-bracing, 142
- Velocity
  - effective peak, 20
  - response period, 78
  - shear wave, 59
  - spectral, 21
- Vertical
  - acceleration, 13
  - earthquake load, 74
  - element, 201
  - geometric irregularity, 70
  - ground acceleration, 88
  - irregularity, 68
  - load-carrying frame, 64
  - structural irregularity, 69
- Vierendeel
  - bandage, 165
  - girder, 164
  - truss, 139
- Visco-elastic damper, 163
- Viscous damping
  - external, 27
  - internal, 27, 28
- Vlasovian bandage, 165
- Wall
  - cripple, 157
  - diaphragm connection, 155
  - force, 108
  - frame, masonry, moment-resisting, 146
  - pier, 160
  - rigidity, 110
  - shear stress, 108
  - system, steel stud, 144
  - shear, 65, A-213
  - special shear, A-213
  - transverse, 109
- Warehouse loading, 173
- Wave
  - compression, 7
  - L-, 8
  - longitudinal, 7
  - love, 8
  - P-, 7, 16
  - primary, 7
  - radio, ultra-low frequency, 16
  - Rayleigh, 8
  - S-, 8
  - sea, 4
  - secondary, 8
  - seismic, 1, 7
  - SH-, 13
  - shear, 8
  - shear, velocity, 59
  - surface, 8
  - SV-, 13
  - tidal, 4
  - transverse, 8
- Weak
  - beam failure mode, 205
  - column failure mode, 205
  - story, 70, 202
  - story, failure mode, 205
- Weight, 77
  - building, 77
  - effective seismic, 78
  - irregularity, 70
- Welded
  - connection, 140
  - splice, 134
- Welding symbols, A-224
- Wet connection, 130
- Whittier earthquake, A-215
- Width-thickness ratio, 142
- Wind
  - load, 56, 74
  - loading, 51
  - pressure, 56
- Withdrawal strength, nail, A-235
- Wood
  - construction, 149
  - screws, dimensions, A-234
  - structural panel, 150
  - structural panel, shear wall, 151
- Working stress design, 56
- Wrench fault, 5, A-214
- X-bracing, 45, 139, 142
- Yountville earthquake, A-215
- Zone
  - Mendocino fracture, 7
  - micro-, 17
  - of subduction, 2
  - panel, A-213
  - protected, 141
  - seismic, 17

# INDEX OF FIGURES AND TABLES

---

- Abbreviations and acronyms, A-220
- Abutment, bridge, 209
- Acceleration and Mercalli intensity, 13
- Acceleration
  - map, 18-19
  - peak ground, 13
- Accelerogram, A-219
- Accidental eccentricity, 46
- Acronyms and abbreviations, A-220
- Action, rigid diaphragm, 109
- Active California faults, 6
- Adjustment factor, timber, A-231
- Allowable
  - lateral loads, nail, A-230
  - shear load, bolt, A-236-A-239
  - shear, plywood diaphragm, 151, 152
- Analogy, girder/diaphragm, 116
- Analytical procedures, permitted, 81
- Angle section, 142
- Architectural components, coefficients, 97
- Authority, engineer, 135
- Base
  - isolation, 161
  - shear, design, simplified, 84
- Beam
  - bending equations, 25
  - center link, 144
  - end link, 144
- Beam-column
  - connection repair, A-246
  - connection, steel, 141
  - failures, Northridge earthquake, A-242
  - reinforcement, 135
  - transverse confinement, 135
- Bearing
  - wall system, 64
  - isolation, 162
- Bending
  - beam, 25
  - cross-grain, 156
- Bolt
  - allowable shear load, A-236-A-239
  - dimensions, A-232
- Boundary member, concrete, 131
- Box nail, A-230, A-234
- Braced frame
  - eccentric, 143
  - types, 143
- Bridge abutment, 209
- Building
  - and roof diaphragm, 107
  - frame system, 64
  - separation, 92
- California faults, 6
- Cantilever
  - method, 124
  - piers, 25
- Cantilevered-column system, 65
- Category, occupancy, 59
- Center link beam, 144
- Chord, 117
  - diaphragm, 150
- Chronology, California earthquakes, A-215
- Circular section, 142
- Class
  - site, 60
  - site, seismic coefficient, 62
- Coefficient
  - for architectural components, 97
  - design v. structural system, A-221
  - seismic, minimum, 78
  - seismic v. site class, 62
  - stability, 94
- Column
  - carrying discontinuous wall, 135
  - reinforcement, 135
  - transverse confinement, 135
- Combinations of loads, 75
- Commercial straps and ties, A-225-A-229
- Components, architectural, coefficients, 97
- Concrete
  - ductile joint, 129
  - flexural member, 133
- Confinement, transverse, 134, 135
- Connection
  - beam-column, steel, 141
  - beam-column, steel, obsolete, A-241
  - failures, steel, Northridge earthquake, A-242
  - repair, steel, A-246
  - SidePlate, 138
- Construction
  - eccentric link, 143
  - tilt-up, 159
- Conversion factor, A-211
- Correlation
  - intensity/acceleration, 13
  - magnitude/acceleration, 13
  - magnitude/duration, 13
- Critically damped motion, 28
- Cross-grain
  - bending, 156
  - tension, 156
- Crosstie, 132
- Damped oscillator, 27
- Damping ratios, 29
- Definitions, A-212
  - site class, 60
- Deflection
  - equations, 25
  - eccentric link, 144
- Deformation
  - elastic, 89
  - inelastic, 89
- Design
  - base shear, simplified, 84
  - coefficients v. structural system, A-221
  - response spectrum, 42
  - value, lateral load, bolt, A-236-A-239
  - value, nail, A-230
  - value, withdrawal, nail, A-235
- Detail
  - eccentric link, 143
  - joist/wall, 155, 156, A-206-A-208
  - tilt-up construction, 159

- Diagram
  - moment, 126
  - shear, 126
- Diaphragm
  - action, rigid, 109
  - chord, 150
  - plywood, allowable shear, 151, 152
  - ratio, 153
  - roof and building, 107
  - shear stress distribution, 116
  - sheathing, plywood, 150
- Dimensions
  - bolt, 232
  - lag screw, 233
  - nail, 234
  - wood screw, A-234
- Discontinuous wall, 135
- Distribution of story shear, 85
- Dowel fastener, dimensions, 232
- Drag strut, 114
- Drift, 43
  - effect of variables on, 44
  - limitations, story, 90
  - story, 44
  - story, limit, 89
  - total, 43
- Dual system, 65
- Ductile joint, concrete, 129
- Duration of strong-phase shaking, 13
- Earthquake
  - chronology, A-215
  - frequency of occurrence, 14
  - number per year, 14
  - terminology, 1
- Eccentric
  - braced frames, 143
  - link, construction 143
  - link, deflection, 144
- Eccentricity, 46
- Effect
  - of variables on drift, 44
  - P*-delta, 45
- Effects by location, 17
- El Centro
  - accelerogram, A-219
  - log tripartite plot, 40
- Elastic
  - deformation, 89
  - response spectrum, 37, 38
- End link beam, 144
- Energy, strain, 41
- Engineering authority, 135
- Factor
  - adjustment, timber, A-231
  - conversion, 211
  - importance, 59
  - mode shape, 34
  - undamped magnification, 30
- Failures, beam-column, Northridge earthquake, A-242
- Faults
  - California, 6
  - types, 5
- Fixed piers, 25
- Flange and web, girder, 116
- Flexural
  - member, concrete, 133
  - member, transverse confinement, 135
- Forces
  - overturning, wall, 119
  - resisting, wall, 119
- Frame
  - building, system, 64
  - eccentric braced, 143
  - joint, ductile, concrete, 129
  - masonry, wall, 146, 147
  - moment-resisting, 65
- Frames, braced, types, 143
- Framing
  - detail, joist/wall, 155, 156, A-206 A-208
  - members, 114
  - opening, 157
- Frequency of earthquake occurrence, 14
- Girder
  - web and flange, 116
  - quadrangular, 165
  - Vierendeel, 165
- Glossary, 212
- Ground acceleration, peak, 13
- Harmonic oscillator, simple, 24
- Hex lag screw dimensions, A-233
- Hinge, plastic, behavior, 141
- History, California earthquake, A-215
- Holdowns, commercial, A-225–A-229
- Hook, seismic, 132
- Hoop, 132
- Hysteresis loop, 41
- Importance factor, 59
- Inelastic deformation, 89
- Intensity
  - scale, Mercalli, 9
  - Mercalli and acceleration, 13
- Irregularities
  - plan, 69, 72
  - vertical, 69, 70
- Isolation
  - bearing, 162
  - base, 161
- Isoseismal map, 10
- Joint
  - ductile, concrete, 129
  - moment-resisting, 138
- Joist/wall framing detail, 156
- Lag screw, hex, dimensions, A-233
- Lateral load, allowable, nail, A-230
- Ledger and joist tie, 156
- Limit, story drift, 89
- Limitations, story drift, 90
- Link
  - beam center, 144
  - beam end, 144
  - eccentric, construction, 143
  - eccentric, deflection, 144
- Lithosphere plates, 3
- Load
  - allowable, nail, 230
  - allowable, shear, bolt, A-236–A-239
  - combinations, 75
  - withdrawal, nail, A-235
- Location, earthquake effects, 17
- Log tripartite plot, 39, 40
- Loop, hysteresis, 41
- Magnification factor, undamped, 30
- Magnitude, Richter, correction nomograph, 11
- Map
  - acceleration, 18-19
  - isoseismal, 10
  - seismic risk, 18-19
- Masonry wall frame, 146, 147
- Maximum diaphragm ratio, 153
- Member
  - boundary, concrete, 131
  - flexural, concrete, 133
- Members, framing, 114
- Mercalli intensity
  - and acceleration, 13
  - intensity scale, 9
- Method
  - cantilever, 124
  - portal, 123
- Minimum seismic response coefficient, 78
- Mode shape factors, 34
- Mode shapes, 32
- Modified Mercalli intensity scale, 9
- Moment
  - diagram, 126
  - frame, special truss, 140
  - overturning, 48, 93
  - torsional, 89
- Moment-resisting
  - frame, 65
  - joint, steel, 138
- Motion
  - critically damped, 28
  - overdamped, 28
  - underdamped, 28
- Nail
  - allowable load, A-230
  - dimensions, A-234
  - withdrawal load, A-235
- Nomenclature, xv
- Nomograph, Richter magnitude correction, 11
- Nonbuilding structures, 101, 102
- Normalized response spectrum, 43
- Northridge earthquake
  - connection failures, A-242
  - obsolete connection detail, A-241
- Number of earthquakes per year, 14
- Obsolete beam-column connection, A-241
- Occupancy category, 59
- Occurrence, frequency of earthquake, 14
- Opening, framing, 157
- Openings, stacked, 109
- Oscillator
  - simple harmonic, 24
  - with damping, 27
- Overdamped motion, 28
- Overturning
  - forces, wall, 119
  - moment, 48, 93
- Panel zone, 139
- Parameters, period, 73
- Parts and portions, coefficients, 97
- P*-delta effect, 45
- Peak ground acceleration, 13
- Period parameters, 73
- Permitted analytical procedures, 81
- Pier, rigidity, A-217, A-218
- Piers
  - cantilever, 25
  - fixed, 25
- Pilaster, 118
- Plan irregularities, 69, 72
- Plastic hinge behavior, 141

- Plates, 3
- Plot, log tripartite, 39, 40
- Plywood diaphragm  
allowable shear, 151, 152  
sheathing, 150
- Portal method, 123
- Procedure, seismic design, 58
- Procedures, analytical, permitted, 81
- Protected zone, 141
- Quadrangular girder, 165
- R*-values, nonbuilding structures, 101, 102
- Ratio, diaphragm, 153
- Ratios, damping, 29
- Rectangular tube section, 142
- Redundancy requirements, 67
- Reinforcement  
column, 135  
flexural member, 133
- Repair, connection, steel, A-246
- Requirements, redundancy, 67
- Resisting forces, wall, 119
- Response  
of simple harmonic oscillator, 24  
spectra, 61  
spectrum, design, 42  
spectrum, elastic, 37, 38  
spectrum, normalized, 43
- Richter magnitude correction  
nomograph, 11
- Rigid diaphragm action, 109
- Rigidity of piers, A-218
- Roof diaphragm and building, 107
- Scale, Mercalli intensity, 9
- Screw, wood, dimensions, A-234
- Section  
angle, 142  
circular, 142  
rectangular tube, 142
- Seismic  
acronyms and abbreviations, A-220  
coefficient v. site class, 62  
design procedure, 58  
hook, 132  
response coefficient, minimum, 78  
risk map, 18-19  
tie, 153, 155, 208  
waves, types, 7
- Separation, building, 92
- Shaking, duration of strong-phase, 13
- Shape factors, mode, 34
- Shapes, mode, 32
- Shear  
allowable load, nail, 230  
allowable, plywood diaphragm, 151, 152  
base, design, simplified, 84  
diaphragm, 126  
load, allowable, bolt, A-236-A-239  
stress distribution, diaphragm, 116  
torsional, 48  
wall, concrete, 131  
wall-frame interaction system, 66
- Sheathing, plywood diaphragm, 150
- SidePlate connection, 138
- Simple harmonic oscillator, 24
- Simplified design base shear, 84
- Simpson Strong-Tie, A-225-A-229
- Sinker nail, A-230, A-234
- Site class  
definitions, 60  
seismic coefficient, 62
- Special truss moment frame, 140
- Spectra, response, 61
- Spectrum  
design response, 42  
elastic response, 37, 38
- Spike (*see* Nail)
- Stability coefficient, 94
- Stacked openings, 109
- Steel  
connection repair, A-246  
moment-resisting joint, 138
- Stiffness equations, 25
- Story drift, 44  
limit, 89  
drift limitations, 90
- Story shear, distribution of, 85
- Strain energy, 41
- Straps and ties, commercial, A-225-A-229
- Strong-phase shaking, duration of, 13
- Structural system, 64  
period parameters, 73  
v. design coefficients, A-221
- Structures, nonbuilding, 101, 102
- Strut  
drag, 114  
length, 154  
length, limitation, 154
- Subdiaphragm, 154  
limited strut length, 154
- Subduction, zone of, 3
- Subscripts, xxi
- Symbols, xvii  
weld, A-224
- System  
bearing wall, 64  
building frame, 65  
cantilevered-column, 65  
dual, 65  
moment-resisting frame, 65  
shear wall-frame interaction, 66  
structural, 64  
structural v. design coefficients, A-221
- Tectonic plates, 3
- Tension, cross-grain, 156
- Terminology, earthquake, 1
- Tie  
-down, 208  
-rod, 208  
seismic, 153, 155, 208
- Ties, commercial, A-225-A-229
- Tilt-up construction, 159
- Timber adjustment factors, A-231
- Torsional  
moment, 89  
shear, 48
- Total drift, 43
- Transverse confinement, 134, 135
- Tripartite plot, log, 39, 40
- Truss  
special, moment frame, 140  
Vierendeel, 140, 165  
X-, 140
- Tube, rectangular, section, 142
- Types of  
braced frames, 143  
faults, 5  
seismic waves, 7
- Undamped magnification factor, 30
- Underdamped motion, 28
- Vertical  
distribution of story shear, 85  
irregularities, 69, 70
- Vierendeel  
girder, 165  
truss, 140, 165
- Wall  
bearing, 64  
detail, 155, 156, 206-208  
discontinuous, 135  
frame, masonry, 146, 147  
shear, concrete, 131  
seismic, types, 7  
with openings, 110
- Web and flange, girder, 116
- Weld symbols, A-224
- Withdrawal load, nail, A-235
- Wood screw dimensions, A-234
- X-truss, 140
- Zone  
of subduction, 3  
panel, 139

# INDEX BY SEISMIC BUILDING CODE

---

All references in this index refer to sections within the named code. Page numbers immediately followed by (fig.), (tbl.), or (ftn.) indicate a figure, table, or footnote in this book, respectively.

## ACI 318-05

7.10.5.2, 135 (fig.)  
9.3, 131  
9.3.4, 131  
12.15.1, 133  
12.15.2, 134  
21 (Ch.), 129  
21.1, 131, 132 (fig.)  
21.2.3, 131  
21.2.4, 132  
21.2.5, 132  
21.2.6, 134  
21.2.6.1, 135  
21.2.7, 134  
21.2.7.2, 134  
21.3, 130, 132, 133 (fig.)  
21.3.1.1, 132  
21.3.1.2, 132, 133 (fig.)  
21.3.1.3, 132  
21.3.1.4, 132  
21.3.2, 133  
21.3.2.1, 133 (fig.)  
21.3.2.2, 133 (fig.)  
21.3.2.3, 133, 133 (fig.), 135 (fig.)  
21.3.3, 131  
21.3.3(R), 135 (fig.)  
21.3.3.1, 132 (fig.), 134 (fig.)  
21.3.3.2, 132, 133 (fig.)  
21.3.3.4, 132, 133 (fig.)  
21.3.3.5, 134 (fig.)  
21.3.3.6, 134 (fig.)  
21.4, 135 (fig.)  
21.4.2.2, 134  
21.4.3.2, 134, 135 (fig.)  
21.4.4, 135 (fig.)  
21.4.4.1, 135 (fig.)  
21.4.4.1(c), 135 (fig.)  
21.4.4.2, 134, 135 (fig.)  
21.4.4.3, 135 (fig.)  
21.4.4.4, 135 (fig.)  
21.4.4.5, 135, 135 (fig.)  
21.5, 136  
21.5.1.3, 133 (fig.)

21.5.1.4, 136  
21.5.3.1, 136  
21.6, 130  
21.7.2, 131  
21.7.2.2, 131  
21.7.4, 160  
21.7.6, 131  
21.9, 135  
21.9.4, 135  
21.9.5.5, 135  
21.11, 130

## ACI 530-05

1.14.2.2.2.1, 146  
1.14.5.2.3, 146  
1.14.5.2.3(b), 146  
1.14.6.3, 146  
1.14.6.5, 146  
1.14.6.6, 146  
1.14.7.2, 146  
2.3.5.2.2, 147  
2.3.5.2.3, 147

## AISC 341 Part I

1 (Sec.), 137  
4.1, 137  
6 (Sec.), 138  
7.4, 141 (fig.)  
8.3, 138  
9 (Sec.), 139  
9.2a, 140, 141  
9.5, 139  
9.6, 139  
9.7, 141  
9.7a, 141  
11 (Sec.), 138  
11.2, 139  
11.5, 139

12 (Sec.), 139  
12.2, 140  
12.3, 140  
12.4, 140

13 (Sec.), 142  
13.2d, 142  
13.4b, 142

14 (Sec.), 142  
14.2d, 142  
14.3, 142  
14.5b, 142

15 (Sec.), 143  
15.2b, 143

## ASCE/SEI7-05

2.3.2, 88, 197, 132  
2.4.1, 88, 197, 198, 199

6 (Ch.), 56  
6.2, 56

7 (Ch.), 57

11.4.4, 78  
11.4.7, 62 (tbl. ftn.)

12 (Ch.), 23  
12.1.3, 64  
12.2, 64  
12.2.1, 130  
12.2.2, 71  
12.2.3.1, 71, 172  
12.2.5.1, 65  
12.2.5.3, 65  
12.3, 130  
12.3.1, 45 (ftn.)  
12.3.1.3, 71 (ftn.), 114  
12.3.2, 23, 68  
12.3.3, 69, 71  
12.3.3.2, 104  
12.3.3.4, 104  
12.3.4, 66  
12.3.4.1, 66

- 12.3.4.2, 66, 67, 68  
 12.4.2, 74  
 12.4.2.2, 88  
 12.4.2.3, 131  
 12.4.3, 74  
 12.4.3.1, 74  
 12.4.3.2, 100  
 12.5, 88, 89  
 12.5.3, 71, 104  
 12.6, 51 (ftn.), 83  
 12.7.2, 77  
 12.7.3, 71  
 12.8, 44, 57, 80, 81 (tbl.), 105, 174  
 12.8.1, 44  
 12.8.1.1, 186, 187, 197  
 12.8.2, 73  
 12.8.2.1, 21, 72, 73  
 12.8.3, 85, 86  
 12.8.4, 71  
 12.8.4.2, 89  
 12.8.4.3, 104  
 12.8.5, 48  
 12.8.6, 44, 89  
 12.8.7, 94, 95  
 12.8.9.2, 46  
 12.9, 57, 80, 81 (tbl.), 104, 203  
 12.9.1, 33, 104  
 12.9.2, 104  
 12.9.3, 33, 104, 105  
 12.9.4, 57, 104, 105  
 12.9.7, 45  
 12.10.1, 107  
 12.10.1.1, 108, 203  
 12.10.2, 100, 114  
 12.10.2.1, 130  
 12.10.11, 120, 121  
 12.11, 131  
 12.11.2, 97 (tbl. ftn.), 131, 156  
 12.11.2.2.3, 155, 156  
 12.12, 43 (ftn.), 126  
 12.12.1, 71  
 12.12.1.1, 90 (tbl. ftn.)  
 12.12.2, 117  
 12.12.3, 90 (tbl. ftn.), 92, 93, 130  
 12.12.4, 57, 102, 130  
 12.13.4, 93  
 12.14, 84, 203  
 12.14.1.1, 84  
 12.14.7.1, 130  
 12.14.7.3, 130  
 12.14.8.5, 90  
 13 (Ch.), 95  
 13.1.3, 96  
 13.3, 95  
 13.5.3, 96  
  
 14.2.2.12, 130  
 14.4, 146  
 14.4.7.3, 146  
  
 15 (Ch.), 64, 100  
 15.4.2, 100, 103  
 15.4.3, 100  
 15.7.6, 100  
  
 16 (Ch.), 81 (tbl.)  
 16.2.2, 71  
  
 17 (Ch.), 161 (ftn.), 163  
 17.4.1, 163  
 17.5, 163  
 17.5.4.3, 163  
 17.5.6, 163  
 17.6, 163  
 17.6.2.1, 163  
  
 17.6.3.3, 163  
 17.6.3.4, 163  
  
 18 (Ch.), 163  
  
 21.2.1, 104  
  
 23 (Ch.), 102  
  
 Eq. 6-1, 56  
 Eq. 12.4-1, 74, 76, 77  
 Eq. 12.4-7, 74  
 Eq. 12.8-1, 80, 175, 186, 187  
 Eq. 12.8-2, 78, 79, 80, 120, 121, 175, 197  
 Eq. 12.8-3, 78, 82, 83, 175  
 Eq. 12.8-4, 78  
 Eq. 12.8-5, 78, 79, 80, 82, 83, 197  
 Eq. 12.8-6, 78, 79, 82, 83, 197  
 Eq. 12.8-7, 72, 79, 80, 82, 83, 171, 185, 186  
 Eq. 12.8-11, 85  
 Eq. 12.8-12, 85  
 Eq. 12.8-14, 89  
 Eq. 12.8-15, 89  
 Eq. 12.8-16, 94, 95  
 Eq. 12.10-1, 203  
 Eq. 12.11-1, 131, 156  
 Eq. 12.14-11, 84  
 Eq. 12.14-13, 87, 88  
 Eq. 13.3-1, 95  
 Eq. 13.3-2, 95, 99  
 Eq. 13.3-3, 95, 99  
 Eq. 15.4-5, 100  
 Eq. 17.5-1, 163  
 Eq. 17.5-2, 163  
 Eq. 17.5-7, 163  
 Eq. 17.5-9, 163  
  
 Fig. 6-2, 56  
  
 Table 1-1, 58, 59, 61, 79  
 Table 11.5-1, 59, 204  
 Table 12.2-1, 63, 64, 65, 67, 68, 71, 72, 76, 77, 90, 91, 92, 93, 94, 95, 74, 119, 142, 172, 174, A-221  
 Table 12.3-1, 68, 69, 71, 80, 104, 202  
 Table 12.3-2, 68, 69, 70, 104, 202  
 Table 12.3-3, 66, 67 (tbl.)  
 Table 12.6-1, 69, 71, 80, 81 (tbl.), 83  
 Table 12.8-1, 73  
 Table 12.8-2, 72, 73 (tbl.), 79, 80, 171  
 Table 12.12-1, 90, 150  
 Table 13.5-1, 95, 96, 97 (tbl.), 202  
 Table 15.4-1, 100  
 Table 15.4-2, 100, 102, 173  
  
**IBC-06**  
 16 (Ch.), 23, 145, 149  
 1604.10, 57  
 1605, 75 (tbl.)  
 1605.2, 57, 74, 145, 149  
 1605.2.1, 74, 75 (tbl.), 137, 138  
 1605.3, 74, 137, 145, 149  
 1605.3.1, 75 (tbl.), 105, 203  
 1605.3.2, 105, 137, 138  
 1605.3.4, 75 (tbl.)  
 1605.4, 75 (tbl.), 145  
 1609, 56  
 1613-1623, 55  
 1613.5, 59, 61  
 1613.5.2, 59  
 1613.5.3, 61, 174  
 1613.5.4, 61, 174  
  
 1613.5.5, 59, 60, 202  
 1613.5.5.1, 202  
 1613.5.6, 63  
 1630.1.1, 13  
  
 17 (Ch.), 59  
 1704, 145  
 1708.1, 145  
  
 18 (Ch.), 55  
  
 19 (Ch.), 55  
 1908, 55, 130  
 1908.1.13, 130  
  
 21 (Ch.), 55  
 2101, 145  
 2102, 145  
 2103, 145  
 2104, 145  
 2104.3, 145  
 2105, 145  
 2106, 55, 145  
 2106.3, 145  
 2106.4, 145  
 2106.5, 145  
 2106.5.1, 108, 121  
 2106.6, 145  
 2107, 56 (tbl.), 145  
 2107.4, 146  
 2108, 56 (tbl.), 145  
 2109, 145  
 2109.1.1, 147  
  
 22 (Ch.), 55, 137  
 2205, 55, 137  
 2205.2, 137  
 2210, 144  
  
 23 (Ch.), 55, 149  
 2302, 153  
 2304, 149  
 2305, 55, 149  
 2305.1.2, 150  
 2305.1.5, 150  
 2305.2.2, 149  
 2305.2.4, 150  
 2305.3, 151  
 2306, 56 (tbl.), 149  
 2306.1, 154  
 2306.3.3, 150  
 2306.3.4, 150  
 2306.3.5, 150  
 2306.4, 150, 151  
 2306.4.3, 150  
 2307, 56 (tbl.), 149  
 2308, 149  
 2308.8.5, 153  
 2308.9.4, 157  
 2308.9.4.1, 157  
 2308.11.3.3, 157  
 2308.12.4, 157  
  
 Eq. 16-1, 75 (tbl.)  
 Eq. 16-2, 75 (tbl.)  
 Eq. 16-3, 75 (tbl.)  
 Eq. 16-4, 75 (tbl.)  
 Eq. 16-5, 75 (tbl.)  
 Eq. 16-6, 75 (tbl.)  
 Eq. 16-7, 75 (tbl.)  
 Eq. 16-8, 75 (tbl.)  
 Eq. 16-9, 75 (tbl.)  
 Eq. 16-10, 75 (tbl.)  
 Eq. 16-11, 75 (tbl.)  
 Eq. 16-12, 75 (tbl.)

- Eq. 16-13, 75 (tbl.)  
 Eq. 16-14, 75 (tbl.)  
 Eq. 16-15, 75 (tbl.)  
 Eq. 16-16, 75 (tbl.)  
 Eq. 16-17, 75 (tbl.)  
 Eq. 16-18, 75 (tbl.)  
 Eq. 16-19, 75 (tbl.)  
 Eq. 16-20, 75 (tbl.)  
 Eq. 16-21, 75 (tbl.)  
 Eq. 16-22, 75 (tbl.)  
 Eq. 16-23, 75 (tbl.)  
 Eq. 16-37, 61, 96, 99, 174  
 Eq. 16-38, 61, 174  
 Eq. 16-39, 61, 78, 96, 99, 174  
 Eq. 16-40, 61, 78, 174  
 Eq. 16-41, 59  
 Eq. 16-42, 60  
 Eq. 16-43, 60  
 Eq. 16-44, 60  
 Eq. 23-1, 116
- Fig. 1613, 201  
 Fig. 1613.5(1), 18 19, 174, 201  
 Fig. 1613.5(1 14), 58, 60  
 Fig. 1613.5(2), 174, 201  
 Fig. 1613.5(3), 174
- Table 1613.5(2), 79  
 Table 1613.5.2, 59, 60 (tbl.), 61, 76,  
 77, 79, 84, 85, 87, 88, 202  
 Table 1613.5.3(1), 61, 62 (tbl.), 76,  
 77, 79, 87, 88, 174, 201  
 Table 1613.5.3(2), 61, 62 (tbl.), 174,  
 201
- Table 1613.5.6(1), 63, 119  
 Table 1613.5.6(2), 63, 119  
 Table 1616.3(1), 79  
 Table 1616.3(2), 79  
 Table 1911, 56 (tbl.)  
 Table 1912, 56 (tbl.)  
 Table 2305.1.5, 150 (ftn.)  
 Table 2305.2.3, 117, 153, 203  
 Table 2305.3.4, 203  
 Table 2306.3.1, 105, 115 (ftn.), 120,  
 121, 150, 151 (tbl.), 153  
 Table 2306.4.1, 150, 151, 152 (tbl.)  
 Table 2308.9.3(1), 157
- NDS-05**
- 11 (Ch.), 154  
 11.5.2, 154  
 11.5.4, 154
- Table 10.3.1, 155, A-231  
 Table 11A, 154, A-236  
 Table 11B, 154  
 Table 11C, 154  
 Table 11D, 154  
 Table 11E, 154, A-240  
 Table 11F, 154, A-238  
 Table 11N, 154, A-230  
 Table 11.2C, 154, A-235  
 Table L1, A-232  
 Table L2, A-233  
 Table L3, A-234  
 Table L4, A-234