

INDEX

- 4-phenylcyclohexene (4-PC), 30-8
- A**
- AAC (*see* Autoclaved aerated concrete)
- AASHTO girder, 24-5
- Abatement, 2-27
- Aboveground drainage, 5-6
- Absorption
- refrigeration, 28-3
 - sound, 33-6
- Acceleration, 23-3
- Accelerator, 20-2, 36-6
- Access
- control, 32-17
 - easement, 2-19
 - floor system, 17-2
- Accessibility (*see also* Barrier-free design)
- in programming, 3-17
 - site, 5-9
- Accessibility/Ramp (vignette), 45-1
- Accessible
- and Usable Buildings and Facilities, ICC/ANSI A117.1, 55-2, 55-4, 56-1
 - route, 56-1, 56-9
- Accessories, for concrete, 36-5, 36-10
- Accessory
- building, 2-27
 - lighting, 32-14
 - use area, 55-11
- Accidental torsion, 23-13
- Acid wash concrete finish, 36-9
- Acoustical
- ceiling, 43-8
 - ceiling tile, as a sustainable building material, 30-10
 - design, rules of thumb, 33-6, 33-7
 - perfume (*see* White sound)
 - wall panel, 43-10
- Acoustics, 24-8
- open office, 33-11
 - planning concepts, 33-12
 - room, 33-12
- ACQ (*see* Ammoniacal copper quaternary)
- Action
- arch, 21-4, 21-5, 24-2, 25-4, 25-5
 - beam, 25-4, 25-5, 25-7
 - dome, 25-4
 - slab, 25-7
- Active
- circulation, solar water heating, 31-14
 - smoke control, 31-18
 - solar collector, 5-6
 - solar design, 29-14
- Activity grouping, 3-17
- Actuator, 28-13
- ACZA (*see* Ammoniacal copper zinc arsenate)
- ADA (*see* Americans with Disabilities Act)
- Adaptive reuse, 2-19, 30-15
- Add-alternate, 51-6
- Addenda, 51-2, 51-4
- Addition
- algebraic force, 12-7, 12-8
 - graphic force, 12-7, 12-8
- Adhesive, 30-8
- as a sustainable building material, 30-8
 - for metal, 38-3
- Adjacency
- diagram, 3-3, 3-4
 - matrix, 3-3, 3-4
- Admixture, 20-1, 20-2
- for dampproofing, 41-1
 - types, 36-6
- Ad valorem tax, 2-20
- Advertisement for bids, 51-1, 51-3
- Aerodynamic effect, 22-4
- A-frame, 24-6
- AFUE (*see* Annual fuel utilization efficiency)
- Agency, 50-1, 53-3
- Aggregate, 20-1, 20-2, 21-4
- coarse, 20-2
 - concrete, 36-5
 - fine, 20-2
 - lightweight, 20-10
- Agora, 2-1
- AHJ (*see* Authority having jurisdiction)
- AIA (*see also* American Institute of Architects)
- A101, Standard Form of Agreement Between Owner and Contractor, where the basis of payment is a stipulated sum, 50-8
 - A201, General Conditions of the Contract, 50-5, 50-9, 52-1, 52-2, 52-4, 52-5, 28-4, 28-6
 - A201Cma, General Conditions of the Contract for Construction, Construction Manager-Adviser Edition, 50-2
 - A701, Instructions to Bidders, 51-3
 - B141, Standard Form of Agreement Between Owner and Architect with Standard Form of Architect's Services, 50-3, 50-4, 50-7, 51-1, 28-5
 - G706, Contractor's Affidavit of Payment of Debts and Claims, 52-6
 - G707, Consent of Surety Company to Final Payment, 52-6
- Air
- barrier, 29-7
 - chamber, 31-7
 - contaminants, 30-11
 - entraining agent, 20-2, 36-6
 - infiltration, 29-6
 - lock, 29-6
 - movement, for human comfort, 27-3
 - supported structure, 25-6
 - to-air heat exchanger, 28-11
 - quality, 2-16
 - water system, 28-6
- Alarm
- barrier-free design, 56-9
 - fire, 32-18
 - system, 32-16
- Albedo, 2-15, 2-17, 5-11
- Algebraic force addition, 12-7, 12-8
- Alkalinity in concrete, 36-8
- Alkali-silica reaction (ASR) 36-8

- All
 - air system, 28-4
 - glass doors, 42-5, 42-6
 - risk insurance, 53-6
 - water system, 28-6
- Allowable
 - axial compression stress, 19-11, 19-13
 - bearing pressure, 15-7
 - bending stress, 19-4
 - bolt
 - bearing, 16-8, 16-10
 - shear, 16-8, 16-9
 - building height, 55-14, 55-15
 - deflection, 13-9, 18-8
 - floor area, 55-14, 55-15
 - joist span, 18-11, 18-12
 - load on beams, 19-5, 19-9
 - soil bearing capacity, 15-3, 15-5
 - steel
 - column load, 19-14
 - stress, 17-3, 19-3, 19-4
 - stress, 17-3
 - axial compression, 19-11, 19-13
 - bending, 18-5
 - compression, 18-10
 - design (ASD), 11-5, 17-1, 17-2, 19-1, 22-8, 23-24
 - shear, 18-7, 18-8
 - steel, 17-3, 19-3, 19-4
 - wood, 17-3
 - wood
 - bending stress, 18-5
 - compression stress, 18-10
 - design values, 18-2, 18-3
 - shear stress, 18-7
 - stress, 17-3
- Allowance, 50-10, 51-6
- Alternate, 51-5
- Alternating current, 32-2, 32-4
- Alternative energy
 - effects on building planning, 5-4
 - source
 - geothermal, 29-15
 - photovoltaics, 29-15
 - solar design, 29-11
 - wind, 29-15
- Altitude angle, 29-12
- Aluminum, 38-6
 - conductor, 32-3
 - door and frame, 42-4
- Amenities, 2-27
- American
 - Association of State Highway and Transportation Official (AASHTO), 24-5
 - Concrete Institute (ACI), 11-5, 15-8, 17-2, 17-4, 20-1, 20-11, 21-7
 - Conference of Governmental Industrial Hygienists (ACGIH), 30-15
 - Forest and Paper Association (AF&PA), 16-5, 16-6, 18-3, 18-4
 - Institute of Architects (AIA), 50-3
 - Institute of Steel Construction (AISC), 12-6, 13-2, 13-9, 14-2, 16-8, 16-9, 16-10, 16-12, 16-13, 16-16, 16-17, 17-4, 19-3, 19-6, 19-7, 19-8, 19-12, 19-13, 19-14
 - Lumber Standards Committee, 18-1, 39-2
 - National Standards Institute (ANSI), 55-4
 - Society for Testing and Materials (ASTM), 16-8, 19-2, 55-4
 - standard
 - beam, 19-2, 19-3
 - channel, 19-2, 19-3
 - channel sections, 38-8
 - I-beams, 38-8
 - Americans with Disabilities Act (ADA), 55-2, 56-1
 - Ammoniacal copper
 - quatarnary (ACQ), 39-12
 - zinc arsenate (ACZA), 39-12
 - Amortization, 2-27
 - Ampacity, 32-3
 - Ampere, 32-1
 - Amplification, 33-1
 - Amplitude, 32-2
 - Analysis
 - dynamic, 23-2
 - structural, 11-7
 - earthquake, 23-17
 - method, 23-1
 - simplified, 23-2
 - static method, 11-7
 - wind, 22-4
 - Anchorage, 17-1
 - Anchor tenant, 2-27
 - Angle
 - bracket connection, 22-14
 - double, 14-2
 - of load, 16-2
 - of repose, 15-6, 15-11
 - steel, 19-2, 19-3
 - Annealing of metal, 38-3
 - Annual fuel utilization efficiency (AFUE), 28-13
 - Anodizing, 38-6
 - ANSI (see American National Standards Institute)
 - Anticlastic
 - shape, 25-6
 - shell, 25-5
 - Apex, 10-8
 - Appearance grade, 18-2
 - Application for payment, 52-5
 - Applied concrete finish, 36-9
 - Appraisal, 2-27
 - Approved equal language, 49-2
 - Approximate period, 23-20, 23-21
 - Aquifer, 2-27, 31-1
 - Arbitration, 50-7, 52-5, 50-12
 - Arch, 10-7, 21-5, 24-6
 - action, 21-4, 21-5, 24-2, 25-4, 25-5, 37-7
 - circular, 24-6
 - concrete, 24-1, 24-6
 - Gothic, 24-6
 - lamella, 25-2
 - parabolic, 24-6
 - radial, 24-6
 - steel, 24-1, 24-6
 - three
 - centered, 24-6
 - hinged, 10-8
 - true, 24-6
 - types, 24-6
 - wood, 24-1, 24-6
 - Architect
 - as owner's agent, 50-1, 53-3
 - duties, 53-4
 - insurance, 53-5
 - responsibilities, 50-4, 50-11, 51-1, 52-5, 53-4
 - scope of services, 50-4
 - Architectural
 - components, 23-24
 - finishes for concrete, 36-9
 - grade, 18-11
 - mesh, 38-13
 - services, during pre-design, 2-26
 - woodwork, 40-1, 40-4
 - cabinetwork, 40-5
 - code requirements, 40-13
 - finishes, 40-14
 - flush paneling, 40-7
 - laminates, 40-12
 - stile and rail paneling, 40-9
 - trim, 40-13
 - veneer, 40-4
 - Woodwork Institute, 40-4
 - Architectural Woodwork Quality Standards*, 40-4
 - Area, 12-5, 13-10, 18-1, 18-2
 - hurricane-prone, 22-4, 22-7
 - metropolitan, 22-2
 - net, 14-2, 16-2, 16-11
 - shear, 16-11
 - tension, 16-11
 - of refuge, 55-27
 - or room protection devices, 32-17
 - projected method, 22-5, 22-7
 - suburban, 22-2, 22-4
 - tributary, 11-5
 - urban, 22-4
 - Arterial street, 2-13
 - Articulation
 - class (AC), 33-11
 - index (AI), 33-1, 33-11
 - Asbestos, 30-16
 - ban in construction, 30-16
 - ASHRAE Standard
 - 62-2001, Ventilation for Acceptable Indoor Air Quality, 30-14
 - 62.2-2003, Ventilation and Acceptable Indoor Air Quality in Low-Rise Residential Buildings, 30-14
 - 90.1, Energy Standard for Buildings Except Low-Rise Residential Buildings, 30-19
 - Aspdin, Joseph, 36-1
 - Asphaltic concrete, 35-7

- ASR (see Alkali-silica reaction)
- Assemblies, construction, fire resistance, 55-6
- Assembly, 24-8, 25-9
- Assessed
valuation, 2-20
value, 2-27
- Assessment, special district, 2-21
- ASTM (see also American Society for Testing and Materials)
- D2859, Standard Test Method for Flammability of Finished Textile Floor Covering Materials, 43-15
- D5116, Standard Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products, 30-15
- D6670, Standard Practice for Full-Scale Chamber Determination of Volatile Organic Emissions from Indoor Materials/Products, 30-15
- E-84, Standard Test Method for Surface Burning Characteristics of Building Materials, 55-5, 55-6, 55-9
- E-119, Standard Methods of Fire Tests of Building Construction and Materials, 55-5
- E1333, Standard Test Method for Determining Formaldehyde Concentrations in Air and Emission Rates from Wood Products Using a Large Chamber, 30-15
- E1991, Standard Guide for Environmental Life Cycle Assessment of Building Materials/Products, 30-19
- E2114, Standard Terminology for Sustainability Relative to the Performance of Buildings, 30-19
- E2129, Standard Practice for Data Collection for Sustainability Assessment of Building Products, 30-19
- Astragal, 42-11
- Atmospheric effect, 22-4
- Attenuation, 33-1
- Audio detector, 32-17
- Auger boring, 35-3
- Authority having jurisdiction (AHJ), 55-2
- Autoclaved aerated concrete (AAC), 30-5, 36-6
- Automatic
closing, 55-27
closing door, 42-14
door bottom, 42-11
sprinkler system, 55-14
- Automobile
circulation, 5-8
insurance, 53-6
- Award of bid, 51-3
- Axial organization, 3-4
- Azimuth, 5-3
angle, 29-12
- B**
- Backflow preventer, 31-15
- Background noise, 33-5
- Backwater valve, 31-15
- Bagasse, 30-6
- Balance
match, 40-8, 40-9
-point temperature, 29-16
- Ballast, 32-12
roof, 41-10
- Balloon framing, 21-5, 39-5
- Ball penetration test, 36-7
- Bamboo flooring, 30-4, 43-12
- Bar
chart, 3-14
deformed, 20-3
epoxy-coated bar, 20-10
steel, 19-3
- Barrel vault, 25-2, 25-4
- Barrier-free design
accessible route, 56-1, 56-9
alarm, 56-9
bathtub, 56-6, 56-7
carpet, 56-6
detectable warning, 56-9
doors and hardware, 42-15
doorway, 56-2, 56-3
drinking fountain, 56-6, 56-7
floor surface, 56-6
handrail, 56-9
hardware, 56-4
lavatory and sink, 56-6
maneuvering clearance, 56-2, 56-3
mirror, 56-6
opening force, 56-4
parking, 5-10, 5-11
plumbing fixtures, 56-4
protruding object, 56-9, 56-10
ramp, 56-7, 56-9
seating, 56-11, 56-12
shower, 56-6, 56-8
signage, 56-9
stair, 56-7, 56-9
telephone, 56-10
toilet room, 56-4
toilet stall, 56-4, 56-5
urinal, 56-5
wheelchair clearance, 56-2
- Base bid specification, 49-2
- Base line, 5-12
- Base shear, 23-17, 23-21
distribution, 23-22
- Basic
flexure formula, 18-5, 19-4
wind speed, 22-2, 22-3
- Batch system, 31-14
- Batt insulation, 41-3
- Battery, 32-7
- Beam, 13-1, 13-2, 13-3, 13-9
action, 25-4, 25-5, 25-7
allowable load on, 19-5, 19-9
- American standard, 19-2, 19-3
-and-girder
concrete system, 10-4
steel system, 10-2, 10-3
and stringer, 18-2
bond, 21-3
cantilever, 13-3, 13-9
concrete, 20-5, 20-6, 20-11
grade, 15-5
moment capacity, 20-7
continuous, 13-3, 20-11, 20-12
curved, 24-5
doubly reinforced, 20-10
edge, 20-12, 20-13
effective depth, 20-6
fixed-end, 13-3, 13-9
framed connection, 16-12, 16-13, 16-14
glued-laminated, 18-11, 24-1, 24-4
grade, 15-7
inverted tee, 10-5
L-shaped, 10-5
notched, 18-9
overhanging, 13-3
plywood box, 10-2
rectangular, 10-5
simply supported, 13-3, 13-9
steel, 19-3
design, 19-4
-to-beam connection, 16-18
-to-column connection, 22-14
-to-girder connection, 16-12
under-reinforced, 20-6
wood, 18-5
- Bearing
allowable
bolt, 16-8, 16-10
pressure, 15-7
soil capacity, 15-3, 15-5
-type connection, 16-7, 16-9, 16-10, 16-13
wall system, 23-6, 23-7
wood, 18-10
- Bedroom community, 2-27
- Behavior setting, 3-8
- Belled pier, 15-7
- Beltway, 2-6
- Bending
allowable
stress, 19-4
wood stress, 18-5
footing, 15-7, 15-8
of metal, 38-2
reinforcement, 17-5
stiffness, 12-6
stress, 12-2, 13-2
- Benefit assessment (see Business improvement districts)
- Bent, 22-9
- Bentonite, 15-5, 15-7
panel, 41-2
- Bessemer, Henry, 38-1
- BIBS (see Blow-in-blanket system)

- Bid
 - award, 51-3
 - forms, 51-4
 - opening, 51-2
 - security, 51-5
- BID (*see* Business improvement district)
- Bidder's representation, under AIA A701, 51-3
- Bidding
 - advertisement, 51-1, 51-3
 - documents, 51-2, 51-3
 - phase, 3-13
 - procedures, under AIA A701, 51-4
 - requirements, 49-1
- Biological
 - contaminant, 30-11
 - exposure indices, 30-15
- Biometric devices, 32-18
- Bio-plastics, 30-7
- Bioswale, 2-17
- Bituminous coating, dampproofing, 41-1
- Black
 - body, 32-14
 - water, 30-1, 31-14
 - water recycling, 30-3
- Blighted area, 2-27
- Blocked diaphragm, 22-12, 22-13
- Block flooring, 43-12
- Blocking, 39-7
- Blow-in-blanket system (BIBS), 41-5
- Blueprint matching, 40-8, 40-10
- Board, 39-3
 - insulation, 41-3
 - oriented strand, 10-1
 - particle, 10-1
- BOCA National Building Code, 55-1, 55-3
- Bogardus, James, 38-2
- Boiler, 28-2, 28-3
 - fuel economizer, 28-10
 - recuperative gas, 28-10
- Boilerplate, 2-27
- Bolt, 38-3, 39-10
 - allowable
 - bearing, 16-8, 16-10
 - shear, 16-8, 16-9
 - high-strength, 16-8
 - lag, 16-4
 - spacing, 16-12
 - steel, 16-7, 16-9, 16-10
 - type N, 16-8, 16-9
 - type X, 16-8, 16-9
 - unfinished, 16-8
 - wood, 16-4
 - design value, 16-4, 16-5, 16-6
- Bond
 - beam, 21-3, 37-7
 - labor and material payment, 51-5
 - performance, 51-5
 - types, 2-21
 - under General Conditions of the Contract, 50-13
- Bonding pattern, 37-3, 37-4
- Bookmatching, 40-7, 40-9
- Borehole test, 35-1
- Boring, 15-1
 - core, 15-1
 - log, 2-12, 15-1, 15-2, 35-1, 35-2
- Bottom chord, 14-1, 25-3
 - grid, 25-2
- Boulton, Matthew, 38-1
- Boundary survey, 5-12, 5-14
- Bow, 39-2
- Bowstring truss, 14-1
- Box
 - girder, 24-5
 - nail, 16-3
- Brace
 - chevron, 22-11
 - K, 22-11
 - knee, 22-11
 - X, 22-11
- Braced
 - concentric frame, 23-7, 23-9
 - eccentric frame, 23-7, 23-9
 - frame, 23-6, 23-7, 23-9
- Bracing of excavations, 35-5, 35-6
- Brake forming, 38-2
- Branch circuit, 32-6
- Brasilia, 2-6
- Brass, 38-7, 38-12
- Brazing, 38-3
- Breadbox heater, 31-14
- Breast board, 35-5
- BRI (*see* Building-related illness)
- Brick, 37-2
 - cleaning, 37-8
 - construction, 37-5
 - coursing, 37-3
 - joints, 37-3, 37-5
 - restoration, 37-8
 - types, 37-2
- Bridging, 14-1, 18-9, 39-7
- Brightness, 32-8
 - ratio, 32-9
- British thermal unit, 27-1, 41-2
- Brittle material, 23-6
- Broadacre City, 2-4
- Bronze, 38-7, 38-12
- Broom finish, 36-10
- Btu (*see* British thermal unit)
- Bubble diagram (*see* Adjacency diagram)
- Buckle, 13-9
- Buckling, 25-2
- Budget
 - in programming, 3-9
 - methods of developing, 3-11
- Buffer zone, 2-27
- Building
 - area, programming, 3-2
 - automation system, 28-12
 - brick, 37-2
 - Code Requirements for Reinforced Concrete (ACI-318), 17-4, 17-5
 - commissioning, 28-12, 30-13
 - configuration, 23-11
 - corner, 22-8
 - cost, 3-10
 - deflection, 21-9
 - department requirements for drawings, 48-8
 - disposal, 30-15
 - drain, 31-15
 - drift, 11-6
 - economy, 24-7, 25-9
 - envelope, 10-6, 21-7, 27-6, 29-7
 - frame system, 23-7, 23-9
 - function, 24-6, 25-9
 - height, allowable, 55-14, 55-15
 - insulation, 41-2
 - Layout (vignette), 8-1
 - location on property, 55-16
 - Materials Directory, UL, 55-4, 55-6
 - materials
 - evaluating for sustainability, 30-4
 - local, 30-4
 - recycled, 30-15
 - salvaged, 30-5
 - sustainable, 30-3, 39-9, 43-12
 - material weight, 11-2
 - movement, 21-9, 23-14
 - in detailing, 48-4
 - orientation, 5-3, 29-1
 - parts, 23-23
 - portion factor, 22-4, 22-6
 - product certification, for sustainability, 30-18
 - rating systems, 30-18
 - related illness (BRI), 30-12
 - Research Establishment (BRE)
 - Environmental Assessment Method, 30-18
 - Section (vignette), 54-1
 - sections, 48-7
 - sewer, 5-7, 31-15
 - shading, 5-3, 5-5, 29-4, 29-11
 - shape, 22-10, 24-8, 29-2
 - stiffness, 23-6
 - style, 10-13
 - surveys, documenting, 2-23
 - weight, 23-17, 23-21
- Building code
 - adjuncts, 55-3
 - administrative requirements, 55-10
 - enforcement, 55-2
 - history, 55-1
 - in programming, 3-15
 - legal basis, 55-2
 - model, 55-3
 - requirements (*see also* Regulations)
 - accessory use area, 55-11
 - all-glass doors, 42-6
 - allowable building height, 55-14, 55-15
 - allowable floor area, 55-14, 55-15
 - as part of detailing, 48-3
 - common path of egress travel, 55-18, 55-19
 - construction type, 55-13
 - corridor, 55-21
 - corridor continuity, 55-22
 - dead end, 55-22

- definitions, 55-27
- door, 42-13, 55-22
- drawing information, 48-8
- egress system, 55-16
- electrical system, 55-27
- exit, 55-16, 55-17
- exiting through intervening spaces, 55-20
- fire detection and suppression, 55-26
- fire-resistive rating, doors, 55-23
- fire-resistive rating requirements, 55-7
- glazing, 42-20, 55-25
- guards, 55-25
- hardware, 42-14
- high-rise buildings, 55-25
- incidental use area, 55-12, 55-13
- location on property, 55-16
- maximum travel distance, 55-19
- means of egress, 55-16
- mechanical systems, 55-26
- mixed occupancy, 55-11, 55-18
- number of exits required, 55-18
- occupancy, 55-10
- occupancy groups, 55-11
- occupancy separation, 55-11
- occupant load, 55-17
- plumbing systems, 55-26
- separation of exits, 55-20
- sound ratings, 55-27
- stairways, 55-24
- wood finish, 40-13
- wood trim, 40-13
- Built-up
 - roofing, 41-9
 - steel section, 19-15, 24-2
- Bulk plane restriction, 2-18
- Bull float finish, 36-10
- Burnham, Daniel, 2-4
- Busduct, 32-3
- Bush hammering, 36-9
- Business
 - improvement district (BID), 2-21
 - organization, types, 53-1
- Busway, 32-3
- Butt joint, 16-15, 16-16
- BXT™ cable, 32-3
- C**
- Cabinetwork, 40-5
 - types, 40-6
- Cable
 - structure, 25-7, 25-8
 - suspended, 10-10, 25-8
- Caisson foundation, 15-6, 15-7
- Calcium chloride test, 36-8
- California
 - Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65), 30-14
 - South Coast Air Quality Management District, 30-8, 30-11
- Calthorpe, Peter, 2-4
- Camber, 24-4
- Canada Green Building Council, 30-18
- Canadian
 - National Building Code, 55-2
 - National Fire Code, 55-2
 - Standard Form of Contract for Architectural Services, CCAC Document 6, 50-3, 51-1, 53-5
- Candlepower, 32-8
 - distribution curve, 32-13
- Cantilever, 25-3
 - beam, 13-3, 13-9
 - footing, 15-6
 - wall, 15-11
- Capital expenditure, 2-27
- Carbon fiber concrete, 36-7
- Card reader, 32-17, 42-12
- Carpet, 30-8, 43-15
 - and Rug Institute (CRI), 30-8
 - as a sustainable building material, 30-8
 - barrier-free design, 56-6
 - wool, 30-4
- Casehardening of metal, 38-3
- Cash flow, 2-27
- Cast
 - iron, 38-4
 - Iron Age, 38-2
 - iron pipe, 31-15
 - stone, 37-11
- Cast-in-place
 - concrete, 10-3
 - wall, 21-7
- Catalyzed lacquer, 40-14
- Catch basin, 2-17, 5-7, 35-7
- Catchment area, 2-8
- Catenary curve, 10-10, 25-8
- Caulking, 41-11
- Causes of action, under AIA Document B141, 50-6
- Cavity wall, 21-3, 37-5, 37-6
 - construction, 10-5
- CC&Rs, 2-27
- CCA (see Chromated copper arsenate)
- CCA 5, Management Contract Form
 - Between Owner and Construction Manager, 50-2
- CCAC Document 6, Canadian Standard Form of Contract for Architectural Services, 50-3, 51-1, 53-5
- CCDC 2, Stipulated Price Contract, 50-8, 50-9, 53-4, 53-6
- C corporation, 53-2
- Ceiling
 - acoustical, 43-8
 - acoustical tile, 30-10
 - seismic restraint, 43-10
- Cellular metal floors, 32-4
- Cellulose insulation, 30-7, 41-3, 41-5
- Cement, 20-1, 20-2 (see also Portland cement)
 - high-early, 20-4
 - portland, 20-2, 21-4
 - types, 36-5
- Cementitious coating, 41-1
- Center match, 40-8, 40-9
- Center
 - of gravity, 12-5
 - of mass, 23-14, 23-25
 - of rigidity, 23-14
- Central
 - organization, 3-4
 - Park, New York, 2-4
- Centroid, 12-5
- Ceramic
 - tile, 30-9, 43-5
 - tile, as a sustainable building material, 30-9
 - veneer (see Terra cotta)
- Certificate of occupancy, 2-28
- Certified
 - rehabilitation, 2-25
 - wood products, 30-6
- CFC (see Chlorofluorocarbon)
- Chain of custody, 30-7
- Chair (concrete formwork), 36-5
- Change
 - in service, 50-6
 - in the work, 52-2
 - in the work, under General Conditions of the Contract, 50-12
 - order, 50-12, 52-2
- Channel
 - American standard, 19-2, 19-3
 - slab, 24-5
- Character, in programming, 3-17
- Check
 - lumber defect, 39-2
 - property description, 5-12
 - valve, 31-6
- Chemical
 - finishes of metal, 38-3
 - resistant laminate, 40-12
- Chevron brace, 22-11
- Chicago
 - construction, 38-2
 - fire of 1871, 55-2
- Chiller
 - dual-condenser, 28-9
 - gas-fired absorption-based, 28-9
- Chlorofluorocarbon (CFC), 28-3, 29-6, 30-7, 41-3
- Chlorosulfonated polyethylene (CSPE)
 - roofing, 41-10
- Chord, 22-9, 22-12
 - bottom, 14-1, 25-2, 25-3
 - force, 22-12
 - parallel, 24-4
 - pitched, 24-4
 - steel joist configurations, 24-4
 - top, 14-1, 25-2, 25-3
- Chromated copper arsenate (CCA), 30-7
 - phase out, 39-12
- Chronic inhalation reference exposure level (REL), 30-11
- Circular
 - arch, 24-6
 - frame dome, 25-3
 - stairway, 44-7, 55-24
- Circulating system, hot water, 31-12

- Circulation
 - automobile, 5-8
 - in space planning, 3-6
 - patterns, 3-6, 3-7
 - in space planning, 3-4
 - pedestrian, 5-8
 - service, 5-9
- Cistern, 30-2
- Cité industrielle, 2-3, 36-1
- City
 - Beautiful movement, 2-4
 - development pattern, 2-4
 - forms, historic, 2-1,
 - planning, 2-1
 - Renaissance, 2-2
 - United States, 2-3
- Cladding, 22-8
- Claim, 52-4
 - for additional time, 52-4
 - for concealed or unknown conditions, 52-5
 - third-party, 28-4
- Classified label, 55-4 (*see also* Listed label)
- Clay, 2-12, 15-1, 15-7
 - masonry compressive strength, 21-2
 - roof tile, 41-8
 - tile, 37-10
- Clean Air Act (CAA)
 - of 1970, 30-10, 30-16
 - of 1990, 41-3
- Cleaning
 - brick, 37-8
 - final, 52-6
- Clearance, in detailing, 48-3
- Climate
 - design for, 27-8
 - influences on site planning, 2-14, 5-1, 5-4
- Climatic
 - regions, 5-4, 5-5, 27-8, 29-1, 29-3
 - zone, 28-8
- Clo, 27-3
- Closed
 - loop system, 29-15
 - active, 31-14
 - solar water heating, 31-13
 - specification, 49-2
- Closer, 42-9
- Cluster housing, 2-27
- Clustered organization, 3-4
- CMU (*see* Concrete masonry unit)
- Coarse aggregate, 20-2
- Coatings for metal, 38-3
- Codes (*see also* Building code requirements, individual topics)
 - in programming, 3-15
- Coefficient
 - of absorption, 33-6
 - of earth pressure, 15-12
 - of expansion, 11-7
 - of heat transmission, 27-1
 - of linear expansion, 12-3
 - of performance (COP), 28-13
 - of thermal expansion, 10-7
 - of metals, 38-4
 - of transmission, 32-7
 - of utilization (CU), 32-15
- response modification, 23-7, 23-8, 23-20
- seismic
 - response, 23-17
 - site, 23-19
 - site, 23-17
- Cohesive soil, 15-12
- Cold
 - drawn steel wire, 20-3
 - lain asphalt, 35-7
- Collinear force, 12-1, 12-2, 12-7
- Collector
 - solar, 29-14
 - streets, 2-13
- Color
 - in lighting, 32-9
 - rendering index (CRI), 32-15
 - temperature, 32-12, 32-14
- Colorthrough laminate, 40-12
- Columbia, Maryland, new town, 2-4
- Columbian Exposition, 2-4
- Column, 13-9
 - allowable steel load, 19-14
 - capitals, 10-4
 - concrete, 20-13
 - discontinuous, 23-16
 - end condition, 13-10, 13-11, 18-10, 19-11
 - independent footing, 15-6, 15-9
 - intermediate, 13-10
 - precast, 10-5
 - short, 13-10
 - slender, 13-10
 - spiral, 20-14
 - steel, 19-11 19-12, 19-14
 - tied, 20-13
 - to-beam connection, 16-12
 - to-column connection, 16-18
 - wood, 18-11
- Combined
 - footing, 15-6
 - load, 13-9
 - specular and diffuse reflection, 32-7
 - stress, 12-2
- Combustible, 55-27
 - construction, 17-5
- Comfort chart, 27-4
- Commissioning, building, 28-12
- Common
 - area, 2-27
 - brick, 37-2
 - path of egress travel, 55-18, 55-19, 55-27
 - wire
 - nail, 16-3
 - spike, 16-3
- Communication
 - in programming, 3-17
 - systems, 32-16
- Community planning, 2-1
- Compact
 - fluorescent (CF) lamps, 32-12
 - section, 19-4
 - stress, 17-4, 19-4
- Compaction of soil, 35-5
- Compartmentation, 31-17
- Compensation methods
 - for architects, 50-7
 - for contractors, 50-9
- Component factor, 22-8
- Components, 23-23
- Composite
 - construction, 10-6
 - open-web joist, 10-6, 10-7
 - section, 16-19
 - steel deck, 10-6, 10-7
 - wood veneer, 30-6
- Compressed straw, 30-8
- Compression, 14-1, 14-3
 - allowable
 - axial stress, 19-11, 19-13
 - wood stress, 18-10
 - flange, 19-4
 - ring, 25-8
 - steel, 20-10
 - stress, 12-2, 13-1
 - /tension diagonal, 23-9, 23-10
- Compressive
 - concrete
 - member, 20-13
 - strength, 20-2, 20-5
 - masonry strength, 21-2
 - clay, 21-2
 - concrete, 21-2
 - refrigeration, 28-3
 - specified
 - concrete strength, 17-4
 - strength, 21-1
- Compressor, 28-3
- Concealed conditions, 52-5
- Concentrated load, 11-3, 11-4, 13-3, 13-5, 13-6, 13-9
- Concentric braced frame, 23-7, 23-9
- Concept
 - design, 3-16
 - in programming, 3-16
 - programmatic, 3-16
- Concrete, 20-1
 - accessories, 36-11
 - admixtures, 36-6
 - aggregates, 36-5
 - American Institute (ACI), 11-5, 15-8, 17-2, 17-4, 20-1, 20-11, 21-7
 - arch, 24-1, 24-6
 - as a sustainable building material, 30-5
 - autoclaved aerated, 30-5
 - basic materials, 36-5
 - beam, 20-5, 20-6, 20-11
 - and-girder system, 10-4
 - moment capacity, 20-7
 - block, 37-8
 - detailing, 37-9
 - Building Code Requirements for Reinforced (ACI-318), 17-4, 17-5
 - carbon fiber, 36-7
 - cast-in-place, 10-3
 - column, 20-13
 - compaction, 20-4

- compressive
 - member, 20-13
 - strength, 20-2, 20-5
- conduit embedded, 17-5
- connection, 16-17
- construction load, 17-5
- crushing, 20-6
- curing, 20-4, 36-7
- deflection, 20-11
- design, 20-5
 - strength of, 20-2, 20-4
- finishing, 36-9
- flange, 20-12
- flat
 - plate system, 10-4
 - slab system, 10-4
- flexural design, 20-7
- form, 36-1, 36-2
 - insulated, 41-6
- foundation wall, 15-8
- grade beam, 15-5
- history, 36-1
- insert, 36-11
- joint, 36-10
- joist system, 10-4
- lightweight structural, 20-2
- lintel, 21-5
- masonry
 - compressive strength, 21-2
 - unit (CMU), 37-8
- minimum 17-5
- moisture migration through, 36-3
- new products, 36-6
- one-way systems, 10-3
- paving, 35-7
- placement, 20-4
- placing, 36-9
- post-tensioned, 10-5, 20-14, 24-5
- precast, 10-3, 20-14, 36-11
 - connection, 16-18
 - wall, 21-7, 21-8
- prestressed, 20-14, 24-5, 36-12
 - girder, 24-1
- pretensioned, 20-14
- reinforced construction, 10-6
- reinforcement, 36-4
- required shear strength, 20-9
- sealers, 36-11
- shear, 20-9
- slab, 20-13, 36-3
 - and steel beam, 10-6, 10-7, 16-19
 - finishes, 36-10
- specified compressive strength, 17-4
- strength, 36-6
- structural system, 10-3
- support face, 20-9
- testing, 17-4, 20-5, 36-7
- topping, 24-5
- two-way, 10-3
- waffle slab system, 10-4
- wall, 21-7
 - strength, 21-7
- water-cement ratio, 36-5
- web, 20-12
- Concurrent force, 12-1, 12-2, 12-7, 12-8
- Condenser, 28-3
- Conditional use permit, 2-19, 2-28
- Condominium, 2-28
- Conductance, 27-1, 27-6, 41-2
- Conduction, 27-2, 27-6, 41-2
- Conductivity, 2-15, 27-1, 27-6, 41-2
- Conductor, 32-2
 - electric, 32-3
 - in conduit, 32-3
- Conduit, 48-2
 - electrical, 32-3
- Cone (in the retina), 32-7
- Connection, 22-14, 24-8
 - angle bracket, 22-14
 - beam
 - to-beam, 16-18
 - to-column, 22-14
 - to-girder, 16-12
 - bearing-type, 16-7, 16-9, 16-10, 16-13
 - column
 - to-beam, 16-12
 - to-column, 16-18
 - concrete, 16-17
 - coped, 16-12
 - footing to wall, 16-18
 - framed beam, 16-12, 16-13, 16-14
 - keyed, 16-18
 - main member, 16-4, 16-5, 16-6
 - moment, 16-12
 - resisting, 22-11, 22-15, 24-2
 - precast concrete, 16-18
 - rebar, 16-18
 - rigid, 24-9
 - semirigid, 22-15
 - side member, 16-4, 16-5, 16-6
 - slip-critical, 16-8, 16-9, 16-10, 16-14
 - steel, 16-7
 - wall
 - panel, 21-7
 - to-slab, 16-18
 - welded, 16-15, 22-14
 - wood, 16-1
- Connector, 16-1
 - groups, 16-1
 - lateral load, 16-3
 - shear, 16-19
 - plate, 16-7
 - spacing, 16-3
 - split ring, 16-7
 - timber, 16-7
- Consent of Surety Company to Final Payment, AIA G707, 52-6
- Conservation easement, 2-19
- Consideration of bids, under AIA A701, 51-4
- Constant-volume system, 28-5
- Construction
 - American Institute of Steel Construction (AISC), 12-6, 13-2, 13-9, 14-2, 16-8, 16-9, 16-10, 16-12, 16-13, 16-16, 16-17, 17-4, 19-3, 19-6, 19-7, 19-8, 19-12, 19-13, 19-14
 - by owner, under General Conditions of the Contract, 50-12
- cavity wall, 10-5
- change directive, 50-12, 52-2
- combustible, 17-5
- composite, 10-6
- concrete load, 17-5
- details, 48-1
- double wythe, 10-5, 10-6
- drawing, 48-1, 48-6
 - phase, 3-13
 - building department information, 48-8
- CAD layering, 48-6
- content, 48-6
- coordination, 48-6
 - sequential organization, 48-6
 - sheet organization, 48-6
- ease, 24-8
- glued-laminated, 10-1
- heavy timber, 17-5
- joint, 21-10, 36-10
 - brick, 37-4
- lift-slab, 10-3
- limitations, 10-12
- manager, 50-2
- materials, fire resistance, 55-6
- National Design Specification for Wood (NDS), 16-3, 17-3, 18-9
- noncombustible, 17-5
- observation, 24-10, 52-3
- platform, 21-6
- procurement services, under AIA Document B141, 50-5
- reinforced concrete, 10-6
- requirement, 17-4
- schedule, 3-13, 52-2
- single wythe, 10-5, 10-6
- Specifications Canada, 49-3
- Specifications Institute, 49-3
- time, 24-7
- tolerances, 48-3
- trade sequence, as part of detailing, 48-3
- type, 55-6, 55-13
- wall, 21-1
- Consultant coordination, 2-26, 48-8
- Consumer Product Safety Commission (CPSC), 55-2
- Contingency costs, 3-11
- Continuity, 20-12
- Continuous beam, 13-3, 20-11, 20-12
- Contour
 - interval, 2-10
 - lines, 2-10, 5-1, 5-2, 5-3
 - representation on plans, 2-11, 5-9
- Contract
 - administration services, under AIA Document B141, 50-5
 - administration, under General Conditions of the Contract, 50-11
 - documents, 50-1, 50-9
 - effect on bids, 51-5
 - forms, 49-1
 - sum, definition, 50-8

- time, under General Conditions of the Contract, 50-12
- types, 50-1
- Contractor's
 - Affidavit of Payment of Debts and Claims, AIA G706, 52-6
 - insurance, 53-6
 - responsibilities, 52-4, 52-6
 - responsibilities, under General Conditions of the Contract, 50-10
- Contrast, 32-9
- Control joints,
 - brick, 37-4
 - concrete, 36-10
 - in sidewalks, 35-7
- Controller, 28-13
- Convection, 27-2, 27-6, 41-2
- Convenience outlet (*see* Duplex receptacle)
- Convergent photogrammetry, 2-23
- Conversion varnish, 40-14
- Convertibility, programming concept, 3-8
- Conveyance, 2-28
- Cool climate, design response, 27-8, 29-3
- Cooling
 - by absorption, 28-3
 - by refrigeration, 28-3
 - displacement ventilation, 28-10
 - evaporative, 28-4
 - extract-air window, 28-12
 - ground-coupled heat exchanger, 28-12
 - ground-source heat pump, 29-15
 - loads, 29-2
 - solar-powered absorption, 28-9, 29-15
 - thermal energy storage, 28-11
 - water-loop heat pump, 28-10
- Co-op, 2-28
- Cooperative, 2-28
- Coordination
 - between architect and consulting engineers, 48-7, 48-8
 - consultant, 2-26
 - drawings with specifications, 48-9
 - of construction drawings, 48-6
 - project management, 53-6
 - regulatory agencies during pre-design, 2-26
 - security system design, 48-2
 - with consultants' work, 48-8
- Coordinator, 42-11
- COP (*see* Coefficient of performance)
- Coped
 - connection, 16-12
 - flange, 17-4
- Coplanar force, 12-2, 12-8
- Copper, 38-7
 - azole, 39-12
 - conductor, 32-3
 - piping, 31-3
 - roof, 41-8
- Coproduct, 30-19
- Copyright, 53-5
- Core
 - boring, 15-1
 - cylinder test, 20-4, 20-5, 36-7
- Cored slab, 36-12
- Cork flooring, 43-14
 - as a sustainable building material, 30-9
- Corporate space standards, 3-1
- Corporation, 53-2
- Correction of bidding documents, under AIA A701, 51-4
- Corridor, 55-21, 55-27
 - construction, 55-21
 - continuity, 55-22
 - door encroachment, 55-21
 - openings, 55-21
 - width, 55-21
- Cost
 - approach, land value, 2-20
 - as part of detailing, 48-4
 - control, 3-18, 51-5
 - indexes, 3-12
 - influences, 3-10
 - information sources, 3-12
 - of HVAC systems, 28-8
 - of project, 50-2
 - of the work, definition, 50-6
 - of the work, under AIA Document B141, 50-4
 - plus fee method, 50-3, 50-7, 50-9
 - types, 3-10
- Costa, Lucio, 2-6
- Cost factors, 24-7, 25-9
- Cotton batt insulation, 30-4
- Counterfort wall, 15-11
- Countertop, 40-6
- Covenants
 - conditions, and restrictions (CC&Rs), 2-27
 - restrictive, 2-19
- Cover plate, 19-15, 24-2
- CPM (*see* Critical path method)
- CPSC (*see* Consumer Product Safety Commission)
- CPTED (*see* Crime prevention through environmental design)
- Creep, 10-7
- Creosote, 39-12
- CRI (*see* Carpet and Rug Institute or Color rendering index)
- Cribbing, 35-5
- Cricket, 41-10
- Crime prevention through environmental design (CPTED), 2-8
- Cripple stud, 21-6
- Critical
 - moment section, 15-8
 - net section, 16-2
 - path method (CPM), 3-14
 - shear section, 15-8, 20-9
- Crook, 39-2
- Crowding, 2-7
- Crown of road, 5-9
- Crystalline cells, 29-16
- CSPE (*see* Chlorosulfonated polyethylene)
- CU (*see* Coefficient of utilization)
- Cul-de-sac, 2-28
- Cultural influence, 10-14
- Cup (lumber defect), 39-2
- Curing concrete, 36-7
- Curtain
 - board, 31-18
 - wall, 21-1, 21-9, 42-20
 - system, 10-6
- Curved beam, 24-5
- Cylinder
 - mold, 20-5
 - test, 20-4, 20-5, 36-7
- D**
 - Dampproofing, 41-1
 - Darby, Abraham, 38-1
 - Daylight factor, 29-9, 29-11, 29-16
 - Daylighting, 29-2, 29-9, 29-12
 - effective aperture, 29-10
 - glazing types, 29-10
 - light shelves, 29-10
 - visible light transmittance, 29-10
 - window-to-wall ratio, 29-10
 - dBa, 33-1
 - DCLF (*see* Design cooling load factor)
 - Dead
 - end, 55-22
 - load, 10-11, 11-1, 17-2, 20-5, 21-7, 21-8, 23-21
 - restrictions, 2-19
 - Deadband, 28-13
 - Decibel, 33-1, 33-2
 - addition, 33-3
 - Decking
 - metal, 38-10
 - wood, 10-1, 18-13, 39-10
 - laminated, 18-13
 - solid, 18-13
 - Declination angle, 29-12
 - Decoration, fire-resistive standards, 55-9
 - Dedication, 2-28
 - Deduct-alternate, 51-6
 - Deep long-span joist, 10-3, 19-16, 24-1, 24-3
 - Deep-well jet pump, 31-2
 - Defensible space, 2-8
 - Deflection, 13-3, 13-9, 18-8, 24-1, 24-9
 - allowable, 13-9, 18-8
 - amplification factor, 23-7, 23-25
 - building, 21-9
 - concrete, 20-11
 - immediate, 20-11
 - limitation, 20-11
 - long-term, 20-9, 20-11
 - maximum, 13-9
 - steel design, 19-10
 - Deformation, 12-3
 - Deformed bar, 20-3
 - Degree day, 28-2
 - Deluge system, 31-19
 - Demand control ventilation, 30-19
 - Demising wall, 2-28
 - Densification, 35-5
 - Density, 2-7, 3-17
 - Departmental organization, 53-3
 - Depth-to-span ratio, 24-1
 - Descriptive specification, 49-2

- Design
 - allowable
 - stress (ASD), 11-5, 17-1, 17-2, 19-1, 22-8, 23-24
 - wood values, 18-2, 18-3
 - award-build, 50-2
 - build contract, 50-3
 - concepts, 3-16
 - concrete, 20-5
 - cooling load factor (DCLF), 27-7
 - delegation, 50-11
 - development, 3-13
 - diaphragm, 22-12
 - equivalent temperature difference (DETD), 27-7
 - flexural concrete, 20-7
 - intent, in detailing, 48-1
 - load and resistance factor (LRFD), 17-1, 19-1, 22-8, 23-24
 - Minimum Loads for Buildings and Other Structures (ASCE7), 22-2, 22-3, 22-5, 22-6, 22-7, 23-20, 23-21
 - National Specification for Wood Construction (NDS), 16-3, 17-3, 18-9
 - one-way system, 24-6
 - process, phases, 3-13
 - response displacement, 23-25
 - services, under AIA Document B141, 50-4
 - seismic, 23-1
 - category, 23-3, 23-20
 - spectral response, 23-17, 23-20
 - steel
 - beam, 19-4
 - column, 19-12, 19-14
 - deflection, 19-10
 - shear, 19-10
 - strength, 11-5, 17-1, 22-8, 23-24
 - method, 20-1
 - of concrete, 20-2, 20-4, 36-6
 - time scheduling, 3-13
 - two-way system, 25-9
 - wood bolt value, 16-4, 16-5, 16-6
 - working stress, 17-1
- Despoil, 2-28
- Detail, construction, 48-1
- Detailing
 - building code requirements, 48-3
 - building movement and substrate attachment, 48-4
 - clearances, 48-3
 - conformance to industry standards, 48-4
 - construction trade sequence, 48-3
 - costs, 48-4
 - design intent, 48-1
 - durability and maintainability, 48-3
 - fabrication and installation methods, 48-3
 - material availability, 48-4
 - process, 48-1
 - resistance to moisture and weathering, 48-5
 - safety, 48-2
 - security, 48-2
 - structural integrity, 48-2
 - sustainability, 48-5
 - tolerances, 48-3
- DETD (*see* Design equivalent temperature difference)
- Detectable warnings, barrier-free design, 56-9
- Detention, 30-19
- Development
 - fees, 2-21
 - length, 15-8, 16-18, 20-10
 - pattern
 - city, 2-4
 - effects on social behavior, 2-7
 - rights, 2-28
- Dew point, 27-1, 27-7, 41-6
 - line, 27-4
- Diagonal
 - bridging, 19-16
 - cracking, 20-9
 - tension, 15-7
 - stress, 20-9
 - web, 25-3
- Diagram
 - free-body, 12-9
 - moment, 13-5, 13-6, 13-7
 - shear, 13-4, 13-5, 13-6
- Diaphragm, 22-9, 22-12, 22-13, 23-11
 - blocked, 22-12, 22-13
 - design, 22-12
 - discontinuity, 23-13
 - flexible, 23-11, 23-13
 - horizontal, 22-12
 - load distribution, 23-11
 - rigid, 23-11
 - unblocked, 22-13
 - wood, 22-13
- Differential movement, 21-9
- Diffraction of sound, 33-12
- Diffuse reflection, 32-7
- Diffusion, 36-3
 - of sound, 33-12
- Dimension
 - lumber, 39-3
 - stone, 37-14
- Dimensioning of lumber, 39-3
- Direct
 - contact water heater, 28-9
 - current, 32-1, 32-4
 - expansion system (DX), 28-4
 - gain system, 29-13
 - glare, 32-9
 - lighting system, 32-13
 - system
 - graywater recycling, 30-3
 - solar water heating, 31-13
 - upfeed pumping system, 31-3
- Directionality factor, 22-5
- Discontinuous
 - column, 23-16
 - shear wall, 23-15
- Discount rate, 30-17
- Displacement
 - design response, 23-25
 - inelastic response, 23-25
 - lateral, 22-2, 22-14
 - ventilation, 28-10
- Disposal
 - of buildings, 30-15
 - of gypsum wallboard, 43-3
- District, 2-6
- Diversity, 2-8
- DLH-series joist, 19-15, 19-16
- Documentation
 - of contract administration, 52-4
 - project management, 53-9
- Dome, 25-3
 - action, 25-4
 - circular frame, 25-3
 - frame, 25-3, 25-4
 - geodesic, 25-2, 25-3, 25-4
 - Schwedler, 25-4
 - shear stress, 25-5
 - thin shell, 25-2
- Door
 - as a sustainable building material, 30-8
 - building code requirements, 42-13
 - egress, 55-22
 - elevator, 44-5
 - encroachment, 55-21, 55-23
 - fire-resistive rating, 55-23
 - glass, 42-5
 - lock, electric, 32-17
 - major components, 42-1
 - opening force, 55-23
 - openings, 42-1
 - overhead coiling, 42-7
 - revolving, 42-7
 - sectional overhead, 42-7
 - size for egress, 55-22
 - steel, 42-4
 - swing, 55-23
 - types, 42-2, 42-3, 42-5
 - wood frames, 42-5
- Doorway, barrier-free design, 56-2, 56-3
- Double
 - angle, 14-2
 - deck elevators, 44-5
 - envelope glazing, 28-12, 29-9
 - glazing, 29-8
 - shear, 16-2, 16-4, 16-6, 16-9
 - skin
 - inflatable structure, 10-11
 - structure, 25-6
 - tee, 24-5
 - wythe construction, 10-5, 10-6
- Doubly
 - curved, 25-4, 25-5
 - surface, 25-6
 - reinforced beam, 20-10
- Doughnut circulation pattern, 3-6
- Dowel, 16-18
- Downfeed system, water supply, 31-3, 31-5
- Downflow furnace, 28-2
- Downspout, 31-17

- Downzoning, 2-28
- Drain, 31-17
 - back system, 31-14
 - down system, 31-14
 - field, 31-17
- Drainage, 15-3
 - aboveground, 5-7
 - capacity, 5-7
 - easement, 30-19
 - of soil, 35-4
 - parking, 5-10, 5-11
 - pipng, 31-15
 - sanitary, 31-14
 - site, 2-12, 5-6, 35-6
 - slope, recommended, 2-10
 - storm, 31-14, 31-16
 - surface water, 35-7
 - system design, 31-16
 - underground, 5-6, 5-7
- Drain tile, 15-3
- Drawing
 - coordination with specifications, 48-9
 - of metal, 38-2
- Drift, 22-14, 23-24
 - building, 11-6
 - limitations, 23-25
 - maximum, 22-2, 22-14
 - story, 23-25
 - wind, 22-2
- Drilled pier, 15-7
- Drinking fountain, barrier-free design, 56-6, 56-7
- Driven pile, 15-7
- Drop panel, 10-4
- Dry
 - bulb temperature, 27-1, 27-3
 - pipe system, 31-19
 - sample borings, 35-3
- Drywall (*see* Gypsum wallboard)
- Drywell, 31-17
- Dual
 - condenser chiller, 28-9
 - duct system, 28-5
 - system, 23-18, 23-11
- Duany, Andres, 2-4
- Ductile, 10-2
- Ductility, 19-1, 23-6, 38-5
- Ductwork sizing, 28-8
- Dumbbell circulation pattern, 3-6
- Duplex receptacle, 32-6
 - location, 32-6
- Durability
 - and maintainability, in detailing, 48-3
 - for sustainability, 30-5
- Duties
 - implied, 28-4
 - of the architect, 28-3
- DX (*see* Direct expansion system)
- Dynamic
 - analysis, 23-2
 - buffer zone, 29-9
 - forces, 23-1
 - load, 11-7
 - structural analysis, 11-7
- Dynamically sensitive, 22-4
- E**
- Earth
 - crust, 23-2
 - sheltering, 29-4
- Earthquake, 23-1
 - analysis, 23-17
 - method, 23-1
 - characteristics, 23-2
 - damage, 23-1
 - effects, 23-3
 - induced vibration, 23-25
 - load, 11-6, 17-2
 - maximum considered, 23-3, 23-20
 - measurement, 23-2
 - resistant structure, 23-1
 - simplified analysis, 23-2
- Earthwork, 35-5
- Easement, 2-19, 2-28
 - access, 2-19
 - conservation, 2-19
 - drainage, 30-19
 - joint use, 2-19
 - scenic, 2-19
 - support, 2-19
 - utility, 2-19
- Eccentric braced frame, 23-7, 23-9
- Ecological design, 30-1
- Ecology, 2-15
- Economic analysis, site, 2-19
- Economizer
 - cycle, 28-6, 28-9
 - boiler fuel, 28-10
- Eco-roof, 29-5
- Edge, 2-6
 - beam, 20-12, 20-13
 - distance, 16-2, 16-3, 16-11
- EDM (*see* Electromagnetic distance measurement)
- EER (*see* Energy efficiency ratio)
- Effective
 - aperture, 29-10, 29-16
 - beam depth, 20-6
 - depth, 15-8
 - flange width, 20-12, 20-13
 - length, 14-2, 18-10, 19-12
 - factor, 18-10, 21-7
 - temperature (ET), 27-3
- Efficacy, 32-10
- Efficiency, 22-10, 24-7
 - ratio, 3-2
- Efflorescence, 37-7
- Egress
 - doors, 55-22
 - system, 55-16
- EIFS (*see* Exterior insulation and finish system)
- EIS (*see* Environmental impact statement)
- Elastic limit, 12-3, 23-6
- Electric
 - arc process, 16-15
 - elevator, 44-1
 - heating, 28-7
 - insulation, types, 32-3
 - lock, 32-17
 - metallic tubing (EMT), 32-3
 - power supply, 32-4
 - service, primary, 32-4
 - strike, 32-17
- Electrical
 - circuit, 32-2
 - drawing, 48-7
 - impedance test, 36-8
 - system, building code requirements, 55-27
 - system materials, 32-2
- Electricity, 32-1
 - as energy source, 28-1
 - primary distribution, 32-5
 - secondary distribution, 32-6
- Electrochromic glazing, 29-8, 42-18
- Electrolysis, 38-4
- Electromagnetic
 - distance measurement (EDM), 2-23
 - lock, 32-18
- Electronic
 - ballast, 32-12
 - hardware, 42-12
- Elevation
 - exterior, 48-7
 - interior, 48-7
- Elevator
 - design, 44-3
 - doors, 44-5
 - electric, 44-1
 - freight, 44-6
 - hydraulic, 44-1
 - lobby design, 44-4
 - machine rooms, 44-6
 - operation and control, 44-2
 - safety devices, 44-2
- Elliptical reflector (ER) lamp, 32-11
- EMA (*see* Energy management system)
- Embodied energy, 30-4, 30-20
- Embossing of metal, 38-2
- Emergency
 - lighting, 32-16
 - power supply, 32-7
- Eminent domain, 2-28
- Emissivity, 27-3, 41-5
- Emittance (*see* Emissivity)
- EMS (*see* Energy management system)
- Enclosed building, 22-4
- Encroachment, 2-28
- End
 - distance, 16-2, 16-3
 - frame, 25-5
 - grain withdrawal, 16-3
 - rotation, 13-10, 13-11, 18-10, 19-11, 19-12
 - translation, 13-10, 13-11, 18-10, 19-11, 19-12
- Energy, 32-1
 - budgets, 32-16
 - conservation, 28-2, 3-18 (*see also* Energy efficiency, Sustainable building design)
 - air barrier, 29-7
 - boiler fuel economizer, 28-10

- building automation system, 28-12
 - cool roof system, 41-10
 - daylighting, 29-9
 - direct-contact water heater, 28-9
 - displacement ventilation, 28-10
 - dual-condenser chiller, 28-9
 - economizer cycle, 28-6, 28-9
 - electric, 32-5
 - energy recovery ventilator, 28-11
 - energy transfer wheel, 28-11
 - extract-air window, 28-12
 - gas-fired absorption-based chiller, 28-9
 - glazing, 29-7
 - ground-coupled heat exchanger, 28-12
 - heat pipe, 28-11
 - heat transfer equipment, 28-11
 - insulation, 29-6
 - mechanical system components, 28-9
 - power budget, 32-9, 32-16
 - recuperative gas boiler, 28-10
 - solar-powered absorption cooling, 28-9
 - thermal energy storage, 28-11
 - water-loop heat pump, 28-10
 - water-to-water heat exchanger, 28-11
 - efficiency (*see also* Energy conservation, Sustainable building design)
 - air locks, 29-5
 - building orientation, 29-1
 - building shading, 29-3
 - building shape, 29-2
 - daylighting, 29-9
 - double envelope, 29-9
 - earth sheltering, 29-4
 - glazing, 29-7, 42-18
 - green roofs, 29-5
 - insulation, 29-6
 - landscaping, 29-3
 - ratio (EER), 28-13
 - weather sealing, 29-6
 - efficient glazing, 42-18
 - management system (EMS), 28-12, 28-13
 - Policy Act (EPACT) of 1992, 32-10, 32-11, 32-12
 - recovery ventilator, 28-11
 - sources, 28-1
 - transfer wheel, 28-11
 - Engineered wood products, 39-7
 - English truss, 24-3
 - Enthalpy, 27-1, 27-4
 - heat exchanger, 28-11
 - line, 27-4
 - Envelope attachment, 24-9
 - Environmental
 - Claims Certification program, 30-18
 - controls, 3-18
 - design (*see* Sustainable building design)
 - impact statement (EIS), 2-15
 - Protection Agency, 2-15, 30-10, 30-11, 30-17, 39-12
 - psychology, 2-7, 3-8
 - tobacco smoke (ETS), 30-11
 - EPA (*see* Environmental Protection Agency)
 - EPACT (*see* Energy Policy Act of 1992)
 - EPDM (*see* Ethylene propylene diene monomer)
 - Epicenter, 23-2
 - Epoxy-coated bar, 20-10
 - Equilibrium, 12-1, 13-4, 14-3
 - Equipment
 - cost, 24-7
 - heat
 - gains, 27-7
 - generating, 28-2
 - Equity, 2-28
 - Equivalent
 - fluid weight, 15-12
 - lateral
 - force method, 23-1, 23-2, 23-17
 - load, 23-3
 - thickness, 37-9
 - Erection, 24-8, 25-9
 - speed, 24-7
 - Erosion control, 30-2
 - Errors and omissions insurance (*see* Professional liability insurance)
 - Escalator, 44-6
 - ET (*see* Effective temperature)
 - Ethylene propylene diene monomer (EPDM) roofing, 41-10
 - Euler's equation, 13-10
 - Evaluating
 - building materials, sustainability, 30-4
 - existing structures, 2-22
 - Evaporation, 27-2
 - Evaporative
 - cooler, 27-5
 - cooling, 28-4
 - Evaporator, 28-3
 - Exaction, subdivision, 2-21
 - Excavation, 35-5
 - Exculpatory clause, 49-9
 - Exfiltration, 29-7
 - Existing
 - buildings, surveying, 2-22
 - structures, evaluating, 2-22, 2-24
 - Exit, 55-16, 55-17
 - access, 55-16, 55-17
 - access travel distance, 55-19
 - court, 55-27
 - discharge, 55-16, 55-17
 - enclosure, 55-27
 - number, 55-18
 - passageway, 55-27
 - separation, 55-20
 - stairway, 55-24
 - width, 55-20
 - Exiting (*see also* Means of egress)
 - through intervening spaces, 55-20
 - Expanding grid pattern, 2-5
 - Expansibility, programming concept, 3-8
 - Expansion joint, 41-11
 - brick, 37-4
 - concrete, 36-11
 - concrete paving, 35-7
 - metal, 38-11
 - Expansive soil, 15-5
 - Exposure factor, 22-4, 22-5
 - Expressway, 2-13
 - Extensive green roof, 29-5
 - Exterior
 - elevation, 48-7
 - insulation and finish system (EIFS), 41-13
 - stairway, 5-9, 5-10
 - External load dominated building, 29-2
 - Extinguishing agents, 31-20
 - Extract-air window, 28-12
 - Extruded
 - expanded polystyrene (XEPS), 41-3, 41-5, 41-6
 - polystyrene, 41-3
 - Extruding of metal, 38-2
 - Eye, in vision, 32-7
- F**
- Fabrication
 - methods, in detailing, 48-3
 - of metal, 38-2
 - Facade-integrated photovoltaics, 5-6
 - Facing brick, 37-2
 - Factor
 - building portion, 22-4, 22-6
 - component, 22-8
 - cost, 24-7, 25-9
 - deflection amplification, 23-7, 23-25
 - directionality, 22-5
 - effective length, 18-10, 21-7
 - exposure, 22-4, 22-5
 - flat use, 18-4
 - gust, 22-4, 22-5
 - height, 22-4, 22-5
 - importance, 22-5, 22-7, 23-17, 23-18
 - load, 20-5
 - and resistance design (LRFD), 17-1, 19-1, 22-8, 23-24
 - duration, 16-1, 17-3, 18-5
 - repetitive use, 17-3, 18-2, 18-4, 18-11
 - response modification, 23-17
 - safety, 20-5
 - size, 17-3, 18-4, 18-10
 - strength reduction, 20-6
 - stress intensity, 20-6
 - topographic, 22-5
 - wet service, 18-4
 - wind stagnation, 22-5
 - Factory and shop lumber, 39-3
 - Facts, in programming, 3-16
 - Fair market value, 2-28
 - Fan pressure, 29-7
 - Fasteners, for lumber, 39-10, 39-12
 - Fastest-mile wind, 22-2
 - Fast-track, 50-2
 - scheduling, 3-15
 - Federal Historic Preservation Tax
 - Incentives program, 2-25
 - Federal Reserve Bank (Minneapolis), 10-10

- Fee
 - architect's, 50-7
 - in lieu, 30-20
 - projection, 53-6
- Ferrous metal 38-4
- Fiber, 13-2
 - saturation point, 18-5, 39-4
- Fiberglass
 - insulation, 41-3, 41-5
 - reinforced gypsum, 43-5
- Field
 - administration, 52-3
 - circulation pattern, 3-6
 - measuring, 2-23
 - pattern, 2-5
 - report, 52-3
 - tests, 52-4
 - weld, 16-16
- Fill, 15-3
 - soil, 35-4
- Fillet weld, 16-15, 16-16
- Final
 - cleaning, 52-6
 - payment, 52-6
- Financing
 - methods, 2-20
 - public works, 2-20
- Fine aggregate, 20-2
- Fingerjointed trim, 40-1
- Finish
 - architectural woodwork, 40-14
 - carpentry, 39-1, 40-1
 - grading, 40-1
 - fire resistive standards, 55-9
 - floor, 21-6
 - grading, 35-5
 - hardware, 42-12
 - materials, tests for flammability, 55-5
- Finishing
 - metal, 38-3
 - of concrete, 36-9
- Fink truss, 24-3
- Fire
 - area, 55-8
 - assembly, 55-27
 - barrier, 55-8, 55-27
 - containment, 31-17
 - damper, 31-18, 55-6
 - detection, 32-18, 55-26
 - door assembly, 55-27
 - exit hardware, 55-27
 - extinguisher, 31-20
 - extinguishing agents, 31-20
 - partition, 55-7, 55-27
 - openings, 55-8
 - protection, 24-8, 28-8, 31-17
 - rating, 55-27
 - rated, 55-28
 - doors, 42-13
 - glazing, 42-14, 42-19, 42-20
 - gypsum wallboard, 43-2
 - laminated, 40-12
 - rating, of masonry, 37-9
 - resistance, 10-12, 55-28
 - rated glazing, 42-14, 42-20
 - rated walls and partitions, 55-7
 - rating, 10-6, 55-28
 - resistive
 - assemblies, tests for, 55-5
 - construction, 55-28
 - rating, doors, 55-23, 55-24
 - rating requirements, 55-7
 - standards, 55-6
 - decorations and trim, 55-9
 - finishes, 55-9
 - retardant
 - treatment, 17-3
 - wood treatment, 16-2
 - sprinkler system, 31-19
 - suppression, 55-26
 - Tests of Door Assemblies, NFPA 252, 55-5
 - Tests of Door Assemblies, UL 10B, 55-4
 - wall, 55-8, 55-14
 - zone, 55-13
- Fireproofing, 17-5
- Firestop, 39-7
- Fittings, water piping, 31-6
- Fixed
 - end beam, 13-3, 13-9
 - fee, 50-7
 - price method, 50-2
- Fixture, 2-28
 - unit, 31-8, 31-9, 31-10
- Flame
 - resistance, 55-28
 - spread, 55-28
 - index, 55-9, 55-28
 - rating, 55-6
- Flammability
 - carpet, 43-15
 - requirements of floor coverings, 55-9
 - tests, 55-5
 - for interior finishes, 55-6
- Flammable, 55-28
- Flange, 24-2
- Flashing, 41-11
 - details, 41-12
 - masonry, 37-5
- Flat
 - head screw, 16-3
 - plate collectors, 29-14
 - plate heat recovery unit, 28-11
 - sawing, 40-1
 - truss, 14-1
 - steel, 24-1
 - wood, 24-1
 - use factor, 18-4
- Flex, 32-3
- Flexibility, programming concept, 3-8, 3-17
- Flexible
 - components, 23-24
 - diaphragm, 23-11, 23-13
 - metal-clad cable, 32-3
 - structure, 22-4
- Flexural
 - concrete design, 20-7
 - shear, 15-7, 15-8
 - strength, 10-6
 - stress, 13-10
- Flexure, basic formula, 18-5, 19-4
- Flitch, 40-5
- Float
 - finish, 36-10
 - glass, 42-16
- Floating, 36-10
- Floor
 - area, allowable, 55-14, 55-15
 - area ratio (FAR), 2-7, 2-18
 - coverings, flammability requirements, 55-9
 - drain, 31-16
 - plan, 48-6
 - surface, barrier-free design, 56-6
- Flooring
 - carpet, 30-8, 43-15
 - cork, 30-9, 43-14
 - laminated, 43-13
 - linoleum, 30-9, 43-14
 - radiant panel test (NFPA 253), 55-9
 - resilient, 43-13
 - rubber, 43-14
 - seamless, 43-14
 - stone, 43-8
 - types for sustainability, 30-8
 - vinyl, 30-9, 43-14
 - wood, 30-9, 43-11
- Flow chart, water piping, 31-11
- Flue-gas desulfurization, 30-9, 43-3
- Fluorescent lamp, 32-10, 32-11
- Flush
 - bolts, 42-11
 - doors, 42-2, 42-5
 - paneling, 40-7
- Flutter echo, 33-13
- Fly ash, 30-5, 36-6
- Flying forms, 36-2
- Focusing collectors, 29-14
- Footcandle, 32-8
- Forest
 - Certification Program of SCS, 30-19
 - Conservation Program, 30-6
 - Stewardship Council (FSC), 30-6, 30-10
 - Stewardship Council principles, 30-6
- Form
 - concrete, 30-5, 36-1
 - insulated concrete, 41-6
 - liner finish, 36-9
 - ties, 36-2
- Formaldehyde, 30-8, 30-11, 39-9
 - free
 - free medium-density fiberboard (MDF), 30-6, 30-10
 - in furnishings, 30-10
 - levels, in panel products, 30-6
- Formwork, concrete, 36-1
- Four-way switch, 32-7
- Frame
 - steel door, 42-4
 - wood door, 42-5
- Frameless glazing system, 42-20

- Framing
 for gypsum wallboard, 43-3
 with lumber, 39-4
- Freestanding light fixture, 32-14
- Freight elevators, 44-6
- French drain, 35-7
- Frequency of sound, 33-1, 33-2
- FSC (*see* Forest Stewardship Council)
- Fuel source, 28-1
 selection, 28-2
- Full
 -mortar bed tile installation, 43-6
 wall schedule, 53-7
- Flutter, 25-6
- Folded plate, 10-9, 25-2, 25-7
- Footing
 bending, 15-7, 15-8
 cantilever, 15-6
 combined, 15-6
 friction, 15-12
 heel, 15-11
 independent column, 15-6, 15-9
 key, 15-11, 15-12
 shear, 15-7
 sliding, 15-12
 spread, 15-6, 15-8
 strap, 15-6
 toe, 15-11
 -to-wall connection, 16-18
 wall, 15-6, 15-8
- Force, 12-1
 algebraic addition, 12-7, 12-8
 chord, 22-12
 collinear, 12-1, 12-2, 12-7
 component, 12-8
 concurrent, 12-1, 12-2, 12-7, 12-8
 coplanar, 12-2, 12-8
 distribution, 23-22
 dynamic, 23-1
 equivalent lateral method, 23-1, 23-2, 23-17
 graphic addition, 12-7, 12-8
 horizontal component, 14-3
 lateral distribution, 22-9
 nonconcurrent, 12-2
 normal method, 22-5, 22-7
 parallel, 12-2
 perpendicular, 12-2
 polygon, 14-5, 14-6
 resultant, 12-7, 12-8
 seismic resisting system, 23-7, 23-8
 shear, 13-2
 structural, 12-2
 vertical component, 14-3
- Form-resistant structure, 25-6
- Foundation, 15-1
 caisson, 15-6, 15-7
 concrete wall, 15-8
 masonry wall, 15-8
 mat, 15-6
 pile, 15-6, 15-7
 raft, 15-6
 sill, 17-4
 systems, 15-6
- Four-section hyperbolic paraboloid, 25-6
- Frame
 A, 24-6
 braced, 23-6, 23-7, 23-9
 building system, 23-7, 23-9
 circular dome, 25-3
 concentric braced, 23-7, 23-9
 dome, 25-3, 25-4
 eccentric braced, 23-7, 23-9
 end, 25-5
 gabled, 10-9, 24-6
 glued-laminated rigid, 24-1, 24-3
 intermediate moment-resisting, 23-8, 23-10
 moment-resisting, 22-11, 23-10
 system, 23-8, 23-10
 ordinary moment-resisting, 23-8, 23-10
 portal, 22-11
 rigid, 10-8, 24-2, 24-3
 space, 10-9, 23-6, 25-2
 support, 25-3
 special moment-resisting, 23-8, 23-10
 steel rigid, 24-1, 24-2
 triangulated space, 10-9
 Tudor, 24-6
 two-way truss space, 25-2
- Framed
 beam connection, 16-12, 16-13, 16-14
 tube, 22-12
- Framing
 balloon, 21-5
 lateral system, 22-11
 method, 22-10
 plank-and-beam, 10-1, 10-2
 platform, 21-5, 21-6
- Free-body diagram, 12-9
- Friction
 footing, 15-12
 skin, 15-6
- Frost, 15-5
 line, 15-5
- Fuller, Buckminster, 25-4
- Fundamental period, 11-7, 22-2
- Funicular shape, 10-7, 24-6, 25-4
- Furnace, 28-2
- Furnishings, as sustainable building materials, 30-10
- Furniture-mounted luminaire, 32-14
- G**
- Gabled frame, 10-9, 24-6
- Gage line, 14-2
- Galvanic
 action, 38-4, 48-4
 series, 38-4
- Gantt chart, 3-14
- Garden
 City, 2-3
 roof, 29-5
- Garnier, Tony, 2-3, 36-1
- Gas
 -fired absorption-based chiller, 28-9
 for glazing fill, 29-8
 natural, 28-1
- Gate valve, 31-6
- Gaudi, Antonio, 10-8
- Geared traction elevator, 44-1
- Gearless traction elevator, 44-1
- General
 and supplementary conditions, 49-1
 Conditions of the Contract for
 Construction, Construction Manager-
 Adviser Editions, AIA A201Cma,
 50-2
 Conditions of the Contract, AIA A201,
 49-1, 50-5, 50-9, 50-12, 52-1, 52-2,
 52-4, 52-5, 28-4, 28-6
 liability insurance, 53-5
 obligation bond, 2-21
 overhead, 3-12
 partnership, 53-2
 tax, 2-20
- Generator, 32-7
- Geodesic dome, 25-2, 25-3, 25-4
- Geotextile, 41-2
 material, 35-7
- Geothermal power, 29-15
- GFI (*see* Ground fault interrupter)
- GFIC (*see* Ground-fault circuit interrupter)
- Girder
 AASHTO, 24-5
 box, 24-5
 joist, 24-1, 24-4
 designation, 24-4
 plate, 19-15, 24-2
 prestressed concrete, 24-1
 steel, 24-1, 24-1
 tapered, 24-2
 transfer, 24-2
- Glare, 32-9
- Glass (*see also* Glazing), 42-16
 block, 37-11
 break detector, 32-17
 building code requirements, 42-20
 doors, 42-5
 double, 29-8
 fiber insulation, 30-7
 -fiber-reinforced gypsum, 43-5
 fire-rated, 42-19
 in fire doors, 42-14
 installation details, 42-19
 insulating, 29-8
 low-emittance, 29-8
 -reinforced gypsum, 43-4
 sound control with, 33-9
 types, 42-16
- Glaziers points, 42-19
- Glazing (*see also* Glass), 42-16
 building code requirements, 42-20, 55-25
 double, 29-8
 envelope, 29-9
 electrochromic, 29-8, 42-18
 fire-rated, 42-19
 gaskets, 42-19
 photochromic, 29-8
 selection, for daylighting, 29-10

- spectrally selective, 29-8
- stops, 42-19
- switchable, 29-8
- tape, 42-19
- thermochromic, 29-9
- transition-metal hydride electrochromic, 29-9
- Globe
 - thermometer, 27-3
 - valve, 31-6
- Glued-laminated
 - beam, 18-11, 24-1, 24-3, 24-4
 - construction, 10-1
 - wood, 39-9
 - member, 18-11
- Glulam (*see* Glued-laminated wood)
- Goals, in programming, 3-16
- Gothic arch, 24-6
- Grade beam, 15-7
- Gradient
 - height, 22-2
 - velocity, 22-4
- Grading, 35-5
 - of lumber, 39-2
- Grain size and shape of soil, 35-3
- Graphic
 - force addition, 12-7, 12-8
 - method, 14-3, 14-6
- Grass slope, recommended, 2-10
- Gravel, 2-12
- Gravel fill, 15-3, 15-5
- Gravity
 - load, 11-1
 - wall, 15-11
- Graywater, 30-1, 31-14
 - recycling, 30-2
- Great Fire of 1666 (London), 55-1
- Greek cities, 2-1
- Green
 - building (*see* Sustainable building design)
 - roof, 29-5
 - Seal, 30-18
 - GS-11, product standard for paint, 30-10, 30-19
 - GS-13, product standard for windows, 30-8, 30-19
 - label, 30-8
- Greenguard Environmental Institute, 30-11, 30-14, 30-18
- Greenhouse design (passive solar), 29-14
- Grey
 - cast iron, 38-5
 - water (*see* Graywater)
- Grid
 - circulation pattern, 3-6
 - organization, 3-4
 - pattern, 2-5
- Gridiron street system, 2-3
- Grinding concrete finish, 36-9
- Groove weld, 16-15, 16-16
- Gross
 - building area, 3-2
 - shear stress, 17-4, 19-4
 - tension stress, 17-4, 19-4
- Ground
 - coupled cooling, 28-13
 - coupled heat exchanger, 28-12
 - coupling, 5-5
 - fault circuit interrupter (GFCI), 32-6
 - fault interrupter (GFI), 32-6
 - lease, 2-28
 - light, 29-16
 - motion, 23-3, 23-4, 23-5
 - source heat pump, 29-15
 - wave, 23-2
- Grounding, 32-6
- Groundwater, 2-12, 15-3
- Group
 - automatic elevator control, 44-2
 - interaction, influence on space planning, 3-9
- Grout, 21-4, 37-1
 - cleaned concrete finish, 36-9
- Grouting
 - high-lift, 21-4
 - low-lift, 21-4
- GSHP (*see* Ground-source heat pump)
- Guaranteed maximum price, 50-3, 50-9
- Guard, building code requirements, 55-25
- Guardrail (*see* Guard)
- Guide meridian, 5-12
- Gusset plate, 14-2
- Gust factor, 22-4, 22-5
- Gutter, 31-17, 35-7
- Gypsum
 - block, 37-10
 - board lath, 43-1
 - decks, 36-7
 - wallboard, 43-2
 - as a sustainable building material, 30-9
 - synthetic, 30-9
- Gyration, radius of, 12-5, 12-7, 13-10, 14-2, 18-10, 19-11
- H**
- Half-round slicing, 40-5
- Hall, Edward T., 2-8, 3-8
- Halogenated agents, 31-20
- Halon, 31-20
- Handicapped design (*see* Barrier-free design)
- Handing of a door, 42-1, 42-2
- Handling capacity of elevators, 44-3
- Handrail
 - barrier-free design, 56-9
 - in corridors, 55-21
 - stair, 55-24, 55-25
- Hankinson formula, 16-2, 16-4
- Hard
 - steel trowel finish, 36-10
 - wired, 32-6
- Hardboard, 39-7
- Hardness, of water, 31-1
- Hardware, 42-7
 - astragal, 42-11
 - automatic door bottoms, 42-11
 - barrier-free design, 56-4
 - building code requirements, 42-14
 - closer, 42-9
 - coordinator, 42-11
 - electric lock, 32-17
 - electronic, 42-12
 - finishes, 42-12
 - flush bolt, 42-11
 - hinge, 42-7, 42-8
 - latchset and lockset, 42-9
 - panic, 42-9
 - pivot, 42-9, 42-11
 - threshold, 42-12
 - weather stripping, 42-12
- Hardwood, 39-1, 40-1
- Hausmann, George-Eugène, 2-2
- Hazardous material, 50-12
 - mitigation, 30-16
 - under AIA Document B141, 50-6
- HDPE (*see* High-density polyethylene)
- Headed anchor stud, 16-19
- Header, 21-6
- Heartwood, 40-1
- Heat
 - absorbing glass, 42-17
 - exchanger
 - air-to-air, 28-11
 - energy recovery, 28-11
 - energy transfer wheel, 28-11
 - enthalpy, 28-11
 - flat-plate, 28-11
 - for gray water, 30-3
 - ground-coupled, 28-12
 - heat pipe, 28-11
 - runaround coil, 28-11
 - water-to-water, 28-12
 - gain
 - calculation, 27-7
 - from equipment, 27-8
 - from lighting, 27-7
 - generating equipment, 28-2
 - island effect, 41-11
 - latent, 27-1, 27-7, 27-8
 - loads, 27-5, 29-2
 - loss calculation, 27-6
 - of hydration, 20-4, 36-7
 - pipe, 28-11
 - pump, 28-1
 - ground-source, 29-15
 - water-loop, 28-10
 - sensible, 27-1, 27-7
 - specific, 27-2
 - strengthened glass, 42-16
 - transfer, 41-2
 - transfer equipment, 28-11
- Heating (*see also* HVAC systems)
 - seasonal performance factor (HSPF), 28-13
- Heavy timber construction, 17-5, 39-9
- Hectare, 5-15
- Height
 - factor, 22-4, 22-5
 - to-span ratio, 25-2
 - zoning, 2-28

- Helmholtz resonator, 33-8
 Henry Fitz-Elwyne Assize of Buildings, 55-1
 HERS (see Home energy rating system)
 Hertz, 33-1
 HFCs (see Hydrofluorocarbons)
 Hierarchy, 3-17
 High
 -carbon steel, 19-2
 -density polyethylene (HDPE), 30-7
 -early cement, 20-4
 -intensity discharge (HID) lamp, 32-12
 -lift grouting, 21-4
 -pressure decorative laminate (HPDL), 40-12
 -pressure sodium (HPS) lamp, 32-12
 -rise building, 55-25
 defined, 31-18
 -strength
 bolt, 16-8
 steel, 19-2
 steel strand, 24-5
 -velocity system, 28-5
 Highest and best use, 2-19
 Hinge, 42-7, 42-8
 Historic
 landmark, 2-25
 Preservation Service, 2-24
 preservation treatments, 2-25
 structure, evaluating, 2-24
 structure, survey, 2-26
 History
 building codes, 55-1
 city planning, 2-1
 of concrete, 36-1
 of metal, 38-1
 Holding pond, 5-7
 Hole
 lead screw, 16-3
 long slotted, 16-8, 16-9
 oversized, 16-8, 16-9
 short slotted, 16-8, 16-9
 standard round, 16-8, 16-9
 Hollow
 brick, 37-3
 -core doors, 42-5
 core slab, 10-5
 metal doors, 42-4
 Home
 base, in programming, 3-17
 energy rating system (HERS), 28-13
 run, 48-7
 Honeycombing, 20-4, 36-9
 Hooke, Robert, 12-3
 Hooke's law, 12-3
 Hoop, 25-3, 25-4
 Horizontal
 alignment, roads, 2-13
 bridging, 19-16
 diaphragm, 22-12
 exit, 55-28
 force component, 14-3
 furnace, 28-3
 irregularities, 23-11, 23-13
 joint
 reinforcing, 37-9
 reinforcement, 10-5, 21-3
 load distribution, 23-11
 masonry reinforcement, 10-6
 shear, 13-2, 18-7
 stress, 18-7
 wind load, 21-7, 21-8
 Hose stream test, 55-5
 Hot
 -arid climate, design response, 27-9, 29-3
 -humid climate, design response, 27-9
 -humid, design response, 29-3
 water supply, 31-8
 Hourly billing rates, 50-7
 House
 drain, 31-15
 sewer, 31-15
 Howard, Ebenezer, 2-3
 Howe truss, 24-3
 HPDL (see High-pressure decorative laminate)
 HSPF (see Heating seasonal performance factor)
 Human
 behavior, 2-7, 3-8
 comfort, 27-2
 interaction, 3-9
 metabolism, 27-2
 sensitivity to sound, 33-3
 Humidity
 as component of human comfort, 27-3
 ratio, 27-5
 Hurricane-prone area, 22-4, 22-7
 HVAC system, 28-4
 air-water, 28-6
 all-air, 28-4
 all-water, 28-6
 constant volume, 28-5
 direct expansion, 28-4
 dual-duct, 28-5
 economizer cycle, 28-6
 high-velocity, 28-5
 multizone, 28-6
 reheat, 28-5
 selection, 28-7
 sizing, 28-8
 terminal reheat, 28-5
 variable air volume, 28-4
 zone reheat, 28-6
 Hydrated lime, 21-4
 Hydration, 20-2, 36-5
 Hydraulic elevator, 44-1
 Hydrochlorofluorocarbons (HCFCs), 29-6
 EPA phase out, 30-7, 41-3, 41-5
 Hydrofluorocarbons (HFCs), 28-3
 Hydrologic soil group, 30-20
 Hydrostatic pressure, 11-8, 15-3, 35-3, 35-6, 35-7, 41-2
 Hygrometer test, 36-8
 Hypalon, 41-10
 Hyperbolic paraboloid, 25-2, 25-5
 Hypocenter, 23-2
- I**
 IAQ (see Indoor air quality)
 IBC (see International Building Code)
 ICC (see Impact insulation class)
 ICC/ANSI A117.1, Accessible and Usable Buildings and Facilities, 55-2, 55-4, 56-1
 Ignition test, vertical, 55-9
 I-joint, 30-6, 39-7
 Illuminance, 32-8
 Illuminating Engineering Society (IES), 32-8
Image of the City, The, 2-6
 Imageability, 2-6
 Immediate deflection, 20-11
 Impact
 assessment, 30-3
 hammer test, 36-7
 insulation class (IIC), 33-1, 33-11
 building code requirements, 55-27
 load, 11-7
 noise control, 33-11
 Impedance, 32-1, 32-2
 Implied duties, 28-4
 Importance factor, 22-5, 22-7, 23-17, 23-18
 Improvement
 analysis, 30-3
 ratio, 2-28
 Incandescent lamp, 32-10, 32-11
 Incidental use area, 55-12, 55-13
 Income approach, land value, 2-20
 Incremental unit, 28-4
 Indemnification, 50-11
 clause, 28-4
 Independent column footing, 15-6, 15-9
 Indirect
 gain system, 29-14
 heating, 31-12
 lighting systems, 32-13
 system, solar water heating, 31-13
 Indoor air
 contaminants, 30-11
 quality (IAQ), 28-11, 30-10
 biological contaminants, 30-11
 carpet, 30-8
 causes of poor, 30-12
 standards, 30-14
 strategies for good, 30-13
 symptoms of poor, 30-12
 Induction system, 28-6
 Industrial
 grade, 18-11
 Revolution, 2-2
 Industry standards, 55-4
 in detailing, 48-4
 Inelastic response displacement, 23-25
 Inertia, 23-3
 moment of, 12-5, 12-6, 13-10, 18-1, 18-2
 Infiltration, 27-8, 29-7
 basin, 2-17
 costs, 3-11
 storm water, 30-20

- Inflatable structure, 10-11
- Inflection point, 13-7, 13-8
- Infrared detector, 32-17
- Inorganic board insulation, 41-3
- Inserts, concrete, 36-11
- Insolation, 27-1
- Installation methods, in detailing, 48-3
- Instant start fluorescent lamps, 32-12
- Instructions to Bidders, AIA A701, 51-3
- Instruments of service, under AIA Document B141, 50-5
- Insulated concrete forms, 41-6
- Insulating glass, 29-8, 42-17
- Insulation, 25-9, 29-6
 - as a sustainable building material, 30-7
 - batt, 41-3
 - board, 41-3
 - building, 41-2
 - cellulose, 30-7, 41-3
 - electric, 32-3
 - fiberglass, 41-3
 - glass fiber, 30-7
 - inorganic board, 41-3
 - loose-fill, 41-3
 - mineral-fiber, 30-7
 - moveable, 29-7
 - organic board, 41-3
 - perlite, 30-7
 - plastic fiber, 41-3
 - reflective, 41-5
 - R-value, 41-4
 - sprayed fiber, 41-5
 - sprayed foam, 41-5
 - super, 29-7
 - transparent, 29-7
 - vermiculite, 30-7
- Insurance
 - all-risk, 53-6
 - architect's, 53-5
 - automobile, 53-6
 - contractor's, 53-6
 - general liability, 53-5
 - owner's, 53-6
 - personal injury protection, 53-5
 - professional liability, 53-5
 - property, 53-5
 - types, 53-5
 - under General Conditions of the Contract, 50-13
 - workers' compensation, 53-6
- Integrated part load value (IPLV), 28-13
- Intensity, 33-1
 - level, 33-1
- Intensive green roofs, 29-5
- Interior
 - elevation, 48-7
 - finish, tests, 55-6
 - Layout (vignette), 9-1
- Intermediate
 - column, 13-10
 - metal conduit (IMC), 32-3
 - moment-resisting frame, 23-8, 23-10
 - payment, 52-5
- Internal
 - load dominated building, 29-2, 29-3
 - pressure, 22-4
- International
 - Building Code (IBC), 11-2, 11-3, 11-4, 11-5, 11-7, 11-8, 15-3, 15-5, 17-1, 17-3, 17-4, 17-5, 18-8, 18-9, 19-1, 19-3, 21-2, 22-12, 22-13, 23-1, 23-4, 23-5, 23-7, 23-8, 23-9, 23-12, 23-13, 23-18, 23-19, 23-20, 55-1, 55-2, 55-3, 55-16
 - Energy Conservation Code, 29-6
 - Plumbing Code, 31-8, 55-26
 - Standard Organization, 30-19
- Interpretation of bidding documents, under AIA A701, 51-4
- Interval (elevator design), 44-4
- Intervening spaces, exiting through, 55-20
- Intimate distance, 2-8
- Intrusion detection, 32-16
- Intumescent materials, 31-21
- Inventory analysis, 30-3
- Inverse
 - condemnation, 2-28
 - square law, 33-2
- Inverted
 - membrane roof, 41-9
 - tee beam, 10-5
- Invert elevation, 5-7
- Ionization detector, 32-18
- IPLV (see Integrated part load value)
- I-shaped joist, 10-1, 10-2
- Isofootcandle chart, 32-15
- Isolated T-section, 20-12, 20-13
- Isolation joints, 36-11
- Isolux chart, 32-15
- J**
 - Jenney, William Le Baron, 38-2
 - Jet pump, 31-2
 - John Hancock
 - Building (Chicago), 10-11
 - Tower (Chicago), 22-12
 - Joinery details, 40-5
 - Joining metal, 38-3
 - Joint
 - butt, 16-15
 - concrete, 36-10
 - construction, 21-10
 - horizontal reinforcement, 10-5, 21-3
 - lap, 16-15
 - metal expansion, 38-11
 - method, 14-3
 - reinforcing, horizontal, 37-9
 - seismic, 23-15
 - tee, 16-15
 - through
 - building expansion, 21-9
 - wall expansion, 21-10
 - use easement, 2-19
 - venture, 53-3
- Joist, 21-6
 - allowable span, 18-11, 18-12
 - composite open-web, 10-6, 10-7
 - concrete system, 10-4
 - DLH-series, 19-15, 19-16
 - girder, 24-1, 24-4
 - designation, 24-4
 - hanger, 16-7
 - I-shaped, 10-1, 10-2
 - K-series, 19-15, 19-16, 19-17
 - LH-series, 19-15, 19-16
 - load table, 19-17
 - long span, 10-3, 19-16, 24-1, 24-3
 - open-web, 24-3
 - steel, 14-1, 19-15, 19-16, 24-3
 - steel system, 10-2, 10-3
 - steel chord configurations, 24-4
 - Steel Institute, 19-16, 19-17, 24-3
 - wood 10-1, 10-2, 18-11
- Jurisdictional wetlands, 2-16
- K**
 - Katz, Peter, 2-4
 - K-brace, 22-11
 - Keene's cement, 43-1
 - Kelly ball test, 36-7
 - Keyed
 - connection, 16-18
 - slab, 16-18
 - Keypad device, 42-12
 - Kiln dry, 18-5
 - King post truss, 24-3
 - Knee brace, 22-11
 - Knot, 39-2
 - K-series joist, 19-15, 19-16, 19-17
 - K-slump test, 36-8
- L**
 - L'Enfant, Pierre Charles, 2-3
 - Labeled door, 42-13
 - Labor and material payment bond, 51-5
 - Labor cost, 24-7
 - Labrouste, Henri, 38-1
 - Lacquer, 40-14
 - Lag
 - bolt, 16-4
 - screw, 16-4
 - Laitance, 36-5
 - Lamella
 - arch, 25-2
 - roof, 25-5
 - Laminate
 - flooring, 43-13
 - for woodwork, 40-12
 - Laminated
 - decking, 18-13
 - glass, 42-17
 - vener lumber, 30-6, 39-8
 - Lamp
 - elliptical reflector, 32-11
 - fluorescent, 32-11, 32-12
 - high-intensity discharge, 32-12
 - high-pressure sodium, 32-12
 - incandescent, 32-11
 - low-pressure sodium, 32-12
 - low-voltage miniature reflector, 32-11
 - lumen depreciation, 32-15
 - metal halide, 32-12
 - parabolic aluminized reflector, 32-11
 - reflector, 32-11
 - tungsten halogen, 32-11

- Land
 - sale leaseback, 2-28
 - value, 2-19, 2-20
 - Landlocked, 2-28
 - Landmark, 2-6
 - Landscape slope, recommended, 2-10
 - Landscaping, 2-17, 5-5, 5-11, 29-3
 - Lap joint, 16-15
 - Laser scanning, 2-24
 - Latchset, 42-9
 - Latent heat, 27-1, 27-7, 27-8
 - Lateral
 - buckling, 18-9
 - connector load, 16-3
 - displacement, 22-2, 22-14
 - force
 - distribution, 22-9
 - resisting element, 22-9
 - resisting system, 23-11
 - framing system, 22-11
 - load, 11-6, 17-2
 - resisting structure, 23-6
 - pressure, 11-7, 15-5, 15-11
 - reinforcement, 20-13
 - support, 18-10, 19-4
 - ties, 20-10, 20-13, 20-14
 - Lath, 43-1
 - Lavatory and sink, barrier-free design, 56-6
 - Law of cosines, 1-2, 12-8
 - Law of sines, 1-2, 12-8
 - Law of Hammurabi, 55-1
 - LCA (see Life-cycle assessment analysis)
 - LCC (see Life-cycle cost analysis)
 - Le Corbusier, 2-4, 2-6, 36-1
 - Leaching field, 31-16
 - Lead, 30-16, 38-7
 - based paint ban, 30-16
 - screw hole, 16-4
 - Leadership in Energy and Environmental Design (LEED), 29-5, 30-1
 - BC, 30-18
 - certification, 30-18
 - in specifications, 49-7
 - credit, 29-5, 29-11, 30-1, 30-4, 30-5, 30-7, 30-8, 30-10, 30-15
 - LEED (see Leadership in Energy and Environmental Design)
 - Leeward wall, 22-4
 - pressure, 22-6
 - Legal
 - basis for building codes, 55-2
 - constraints, land development, 2-17
 - issues for architects, 28-3
 - Length-to-width ratio, 22-11
 - Letchworth, 2-3
 - LH-series joist, 19-15, 19-16
 - Liability, 28-4
 - Lien
 - under General Conditions of the Contract, 50-12
 - waiver, 2-28
 - Life
 - cycle
 - assessment analysis (LCA), 2-20, 30-3
 - cost, 48-4
 - cost analysis (LCC), 2-20, 30-17
 - inventory model, 30-4
 - safety, 31-17
 - Safety Code, 32-16, 55-3
 - Lift-slab construction, 10-3, 36-12
 - Light, 32-7
 - frame construction, 39-5
 - level, 32-8
 - loss factor, 32-15
 - pipe, 29-11
 - quality, 32-14
 - shelf, 29-10, 29-16
 - source, 32-10
 - source, color, 32-9
 - Light-gage metal framing, 38-10
 - Light-gage steel stud, 21-6
 - Lighting
 - calculations, 32-15
 - design, 32-8, 32-12
 - emergency, 32-16
 - fundamentals, 32-7
 - heat gain, 27-7
 - surveillance and deterrence, 48-2
 - systems, 32-13
 - Lightweight
 - aggregate, 20-10
 - structural concrete, 20-2
 - Limited
 - liability company (LLC), 53-2
 - liability partnership (LLP), 53-2
 - Linear organization, 3-4
 - Linoleum, 30-4, 43-14
 - as a sustainable building material, 30-9
 - Lintel, 21-4, 21-5
 - concrete, 21-5
 - masonry, 21-5, 37-6
 - steel, 21-5
 - Liquid
 - and plastic limits of soil, 35-3
 - applied roofing, 41-11
 - Listed label (Underwriters Laboratories), 55-4 (see also Classified label)
 - Live load, 10-11, 11-2, 17-2, 20-5
 - reduction, 11-3, 17-2
 - LLC (see Limited liability company)
 - LLP (see Limited liability partnership)
 - Load, 11-1, 12-1
 - allowable
 - on beams, 19-5, 19-9
 - steel column, 19-14
 - and resistance factor design (LRFD), 17-1, 19-1, 22-8, 23-24
 - angle of, 16-2
 - combinations, 11-5, 17-1, 22-8, 23-24
 - combined, 13-9
 - concentrated, 11-3, 11-4, 13-3, 13-5, 13-6, 13-9
 - concrete construction, 17-5
 - control, 32-5
 - dead, 10-11, 11-1, 17-2, 20-5, 21-7, 21-8, 23-21
 - diaphragm distribution, 23-11
 - duration factor, 16-1, 17-3, 18-5
 - dynamic, 11-7
 - earthquake, 11-6, 17-2
 - equivalent lateral, 23-3
 - factor, 20-5, 32-5
 - gravity, 11-1
 - horizontal
 - 23-11
 - wind, 21-7, 21-8
 - impact, 11-7
 - joist table, 19-17
 - lateral, 11-6, 17-2
 - connector, 16-3
 - resisting structure, 23-6
 - live, 10-11, 11-2, 17-2, 20-5
 - reduction, 11-3, 17-2
 - Minimum Design Loads for Buildings and Other Structures (ASCE 7), 22-2, 22-3, 22-5, 22-6, 22-7, 23-20, 23-21
 - normal duration, 17-3, 18-5
 - oscillating, 22-2
 - parallel to grain, 16-2, 16-5, 16-6
 - partition, 11-2, 17-2
 - perpendicular to grain, 16-2, 16-5, 16-6
 - resonant, 11-7, 22-2
 - roof, 17-2
 - live, 11-5
 - seismic, 17-2, 21-7, 21-9
 - shedding, 32-5
 - snow, 11-3
 - soil, 11-7
 - lateral, 11-8
 - temperature-induced, 11-7
 - uniform, 11-4, 13-3, 13-5, 13-7, 13-9
 - vertical, 11-1
 - water, 11-8
 - wind, 11-6, 17-2
- Load-bearing wall, 21-1
- Loaded edge, 16-2, 16-3
- Loading, 17-1
- Lobby design, for elevators, 44-4
- Local
 - materials, for sustainability, 30-4
 - streets, 2-13
- Lockset, 42-9, 42-10
- Logarithm, 1-2
- London, city plan, 2-2
- Long
 - period, 23-17, 23-19, 23-20
 - period building, 23-6
 - slotted hole, 16-8, 16-9
 - span, 24-1, 24-3
 - joist, 10-3, 19-16, 24-1, 24-3
 - structures, 24-1, 25-1
 - term deflection, 20-9, 20-11
 - term thermal resistance (LTTR), 41-3
- Loose-fill insulation, 41-3
- Loudness, 33-3
- Louvered doors, 42-2

- Low
 -emissivity glass, 29-8, 42-18
 -iron glass, 42-17
 -pressure sodium lamps, 32-12
 -voltage miniature reflector (MR) lamps, 32-11
 -voltage switching, 32-7
- Low-lift grouting, 21-4
- L-shaped beam, 10-5
- LTTR (*see* Long-term thermal resistance)
- Lumber, 39-1
 American Standards Committee, 18-1
 cutting, 40-1
 defects, 39-2
 dimensioning, 39-3
 fasteners, 39-10, 39-12
 for architectural woodwork, 40-4
 framing, 39-4
 grading, 39-2
 machine stress-rated, 18-1, 18-2
 moisture content, 39-4
 sawn, 18-1, 18-2
 shrinkage, 39-4
 species, 39-1
 strength, 39-1
 visually graded, 18-1, 18-2
 dimension, 18-3
- Lumen, 32-8
- Luminaire, 32-13
 dirt depreciation, 32-15
 types, 32-14
- Luminance, 32-8
- Luminous intensity, 32-8
- Lump sum, 50-2
- Lynch, Kevin, 2-6
- M**
- Machine
 room, elevator, 44-6
 -stress-rated lumber, 18-1, 18-2, 39-3
- Magnetic
 contacts, 32-16
 hold-open devices, 42-12
- Maillart, Robert, 36-1
- Main connection member, 16-4, 16-5, 16-6
- Maintainability, for sustainability, 30-5
- Maintenance procedures, for indoor air quality, 30-13
- Malpractice insurance (*see* Professional liability insurance)
- Management
 Contract Form Between Owner and Construction Manager, CCA 5, 50-2
 practice, 53-1
 project, 53-6
- Maneuvering clearances, barrier-free design, 56-2, 56-3
- Manhole, 5-7
- Manual of Steel Construction*, 12-6, 13-2, 13-9, 14-2, 16-8, 16-16, 16-17, 17-4, 19-4
- Many prime contracts, 50-2
- Mapped spectral response, 23-17
- Market
 approach, land value 2-20
 value, 2-28
- Masonry
 as a sustainable building material, 30-5
 bearing wall, 10-5
 cement, 37-1
 clay compressive strength, 21-2
 compressive strength, 21-2
 concrete compressive strength, 21-2
 foundation wall, 15-8
 horizontal reinforcement, 10-6
 lintel, 21-5
 reinforced
 grouted wall, 21-2, 21-3, 21-4
 hollow wall, 21-2, 21-3
 structural system, 10-5
 vertical reinforcement, 10-6
 wall, 21-1
 fire rating, 37-9
 opening, 21-4
- Mass distribution, 23-22
- MasterFormat, 49-3
 04 divisions, 49-4
 changes, 49-3
 contents, 49-5
 technical sections, 49-7, 49-8
- Master specifications, 49-2
- Material
 availability, in detailing, 48-4
 cost, 24-7
 electrical system, 32-2
 safety data sheet (MSDS), 30-13, 49-7
 standards, 55-4
- Mat foundation, 15-6
- Matrix costing, 3-12
- Mat test, 36-8
- Maximum
 considered earthquake, 23-3, 23-20
 deflection, 13-9
 drift, 22-2, 22-14
 longitudinal steel percentage, 20-13
 moment, 13-6, 13-9
 resisting moment, 19-4, 19-5, 19-7, 19-8
 shear, 13-9
 steel amount, 20-6
 travel distance, 55-19
- MCM nomenclature, 32-3
- MCS (*see* Multiple chemical sensitivity)
- MDI urea formaldehyde, 30-6
- Mean radiant temperature (MRT), 27-3
- Means of egress, 55-16
- Measurement, existing buildings, 2-23
- Mechanics
 and materialman's lien, 2-28
 lien, 50-12
- Mechanical
 and Electrical Plan (vignette), 34-1
 drawing, 48-7
 finishes of metal, 38-3
 noise control, 33-12
 room space requirements, 28-8
 system, building code requirements, 55-26
- Mediation, 50-7, 50-12, 52-5
- Medieval city, 2-1
- Medium
 -carbon steel, 19-2
 -density fiberboard, 30-6, 39-7
- Medullary rays, 40-5
- Megalopolis, 2-6
- Membrane, 25-4, 25-6
 dampproofing, 41-1
 roofing, 41-9
 structure, 25-6
- MEPS (*see* Molded expanded polystyrene)
- Meridian, 5-12, 25-3, 25-4
- Met (*see* Metabolic unit), 27-2
- Metabolic unit, 27-2
- Metabolism, 27-2
- Metal
 aluminum, 38-6
 architectural mesh, 38-13
 as a sustainable building material, 30-6
 basic materials, 38-2
 cast iron, 38-4
 copper and copper alloys, 38-7
 decking, 38-10
 doors and frames, 42-2
 fabrications, 38-10
 -faced laminate, 40-12
 fasteners for lumber, 39-10
 finishing, 38-3
 forming processes, 38-1
 framing, lightgage, 38-10
 galvanic action, 38-4
 halide lamps, 32-12
 history, 38-1
 joining, 38-3
 lath, 43-1
 lead, 38-7
 ornamental, 38-11
 perforated, 38-13
 properties of, 38-3
 roofing, 41-8
 stainless steel, 38-5
 steel, 38-5
 structural, 38-8
 stud, 21-6
 wall tie, 21-3
 windows, 42-16
 wrought iron, 38-4
 zinc, 38-7
- Metallocene polyolefin, 30-7
- Meter, watt-hour, 32-5
- Metering, 32-5
- Metes and bounds, 5-15
- Method
 earthquake analysis, 23-1
 equivalent lateral force, 23-1, 23-2, 23-17
 framing, 22-10
 graphic, 14-3, 14-5
 normal force, 22-5, 22-7
 of joints, 14-3
 of sections, 14-3, 14-5
 projected area, 22-5, 22-7
 static analysis, 11-7
 strength design, 20-1

- Methylene-diphenyl isocyanate (MDI), 30-6
- Metric units, xxxv
- Metropolitan area, 22-2
- Building Act of 1844, 55-1
- Microclimate, 2-15, 5-11
- Microwave detector, 32-17
- Mildew, 30-11
- Mild steel, 19-2
- Mill levy, 2-20
- Mineral-fiber insulation, 30-7
- Minimum
- concrete cover, 17-5
- Design Loads for Buildings and Other Structures (ASCE 7), 22-2, 22-3, 22-5, 22-6, 22-7, 23-20, 23-21
- horizontal wall reinforcement, 21-7
- longitudinal steel percentage, 20-13
- member depth, 20-11
- property standards, 2-28
- steel amount, 20-7
- vertical wall reinforcement, 21-7
- web reinforcement, 20-9
- weld size, 16-17
- Minor changes in the work, 52-2
- Mirror, barrier-free design, 56-6
- Mixed
- flow, 3-17
- occupancy, 55-11, 55-18
- Mixing of soil, 35-5
- Model building codes, 55-3
- Modification, 50-1
- of bid, under AIA A701, 51-4
- Modified
- bitumen, 41-10
- Mercalli scale, 23-2, 23-3
- Module size, 25-3
- Modulus
- of elasticity, 12-3, 12-4, 18-8
- section, 12-5, 12-7, 13-2, 18-1, 18-2, 19-4, 19-5, 19-7, 19-8
- Moisture
- change, 21-9
- content, 18-4, 18-5
- in architectural woodwork, 40-13
- in concrete, 36-8
- of lumber, 39-4
- dome test, 36-8
- for sustainability, 30-5
- migration through concrete, 36-3
- protection (sustainable material), 30-7
- resistance, as part of detailing, 48-5
- tests for concrete, 36-8
- Mold, 30-11
- Molded
- expanded polystyrene (MEPS), 41-3, 41-5
- high-density polyurethane foam, 30-6
- Moment, 12-4, 13-2
- concrete beam capacity, 20-7
- connection, 16-12
- critical section, 15-8
- diagram, 13-5, 13-6, 13-7
- maximum, 13-6, 13-9
- resisting, 19-4, 19-5, 19-7, 19-8
- negative, 20-12
- of inertia, 12-5, 12-6, 13-10, 18-1, 18-2
- overturning, 23-25
- resisting
- connection, 22-11, 22-15, 24-2
- frame, 22-11, 23-10
- frame system, 23-8, 23-10
- intermediate frame, 23-8, 23-10
- ordinary frame, 23-8, 23-10
- special frame, 23-8, 23-10
- statical, 13-2
- torsional, 17-1
- Monitoring, 53-8
- Mortar, 21-2, 37-1
- joint, 37-3
- types, 37-1, 37-2
- Mosaic tile, 43-5
- Movable
- equipment costs, 3-10
- insulation, 29-7
- MRT (see Mean radiant temperature)
- MSDS (see Material safety data sheet)
- Multiple
- chemical sensitivity (MCS), 30-12
- of direct personnel expense, 50-7
- of direct salary expense, 50-7
- prime contract, 50-2
- shear, 16-2
- wythe wall, 21-1
- Multizone system, 28-6
- Municipal services, 2-14
- storm sewer system, 31-17
- water supply, 31-2
- N**
- Nail, 16-3, 39-10
- box, 16-3
- common wire, 16-3
- Nash, John, 38-1
- National
- Ambient Air Quality Standard, 30-14
- Appliance Energy Conservation Act of 1987, 28-9
- Building Code, 55-1, 55-3
- Building Code of Canada (NBC), 55-2, 55-3
- Design Specification for Wood Construction (NDS), 16-3, 17-3, 18-10
- Electrical Code (NEC), 32-4, 32-6, 32-16, 55-3
- Emission Standards for Hazardous Air Pollutants (NESHAP), 30-16
- Environmental Policy Act of 1969, 2-15
- Fenestration Rating Council (NFRC), 30-8
- Fire Protection Association (NFPA), 31-20, 55-3, 55-4
- Forest Products Association (NFPA), 16-3, 16-4, 16-7, 18-2, 18-11
- Institute for Occupational Safety and Health (NIOSH), 30-16
- Park Service, 2-24
- VOC Emission Standards for Architectural Coatings, 30-14
- Volatile Organic Compound Emission Standards for Architectural Coatings, 30-10
- Nationally Recognized Testing Laboratory (NRTL), 55-4
- Natural
- energy sources, 28-2
- features, of site, 2-12
- gas, 28-1
- period, 23-3
- ventilation, 5-6
- wood laminate, 40-13
- NBC (see National Building Code of Canada)
- NC (see Noise criteria)
- NEC (see National Electrical Code)
- Needs, in programming, 3-16
- Negative
- moment, 20-12
- pressure, 22-1
- rotation, 12-4, 13-4
- Negligence, 53-4
- Negotiation phase, 3-13
- Neighborhood, 2-9
- Neighbors, in programming, 3-17
- Nervi, Pier Luigi, 36-1
- Net
- area, 14-2, 16-2, 16-11
- assignable area, 3-2
- leasable area, 2-28
- metering, 29-16
- shear area, 16-11
- tension
- area, 16-11
- stress, 17-4, 19-4
- to-gross ratio, 3-2
- Neutral axis, 13-1, 13-2
- New
- town concept, 2-4
- urbanism, 2-4
- Newman, Oscar, 2-8
- Newton's law, 23-3
- NFPA (see also National Fire Protection Association)
- 13, Standard for the Installation of Sprinkler Systems, 31-19
- 14, Standpipe and Hose System, 31-20
- 252, Fire Tests of Door Assemblies, 55-5
- 253, Standard Method of Test for Critical Radiant Flux of Floor Covering Systems Using a Radiant Heat Energy Source (Flooring radiant panel test), 55-9
- 257, Standard on Fire Test for Window and Glass Block Assemblies, 55-5
- 265, Standard Methods of Fire Tests for Evaluating Room Fire Growth Contribution of Textile Wall Covering (Room Corner Test), 55-6, 55-9

- 286, Standard Methods of Fire Tests for Evaluating Room Fire Growth Contribution of Wall and Ceiling Interior Finish, 55-6, 55-9
- 5000 Building Code, 55-3, 55-4
- 701, Standard Methods of Fire Tests for Flame-Resistant Textiles and Films (vertical ignition test), 55-9
- NIC (*see* Noise insulation class)
- Niemeyer, Oscar, 2-6
- Night-cooled mass, 29-16
- NIOSH (*see* National Institute for Occupational Safety and Health)
- Nit, 32-8
- Nocturnal cooling, 29-16
- Node, 2-6
- Noise, 33-1
 - control, mechanical, 33-12
 - control, room, 33-8
 - criteria (NC), 33-1
 - criteria curve, 33-5
 - insulation class (NIC), 33-2
 - reduction, 33-4
 - coefficient (NRC), 33-2, 33-6
 - in a space, 33-7
- Nominal size, 18-1
- Non-bearing wall (*see* Non-load-bearing wall)
- Noncombustible, 55-28
 - construction, 17-5
- Nonconforming use, 2-19
- Noncompact section, 19-4
 - stress, 17-4
- Nonconcurrent force, 12-2
- Nonferrous metal, 38-4, 38-6
- Non-load-bearing wall, 10-6, 21-1
- Nonmetallic sheathed cable, 32-3
- Nonpotable water, 31-1
- Nonrigid elements, 23-24
- Nonsymmetric load-resisting elements, 23-14
- Normal
 - force method, 22-5, 22-7
 - load duration, 17-3, 18-5
 - stress, 12-2
- North American plate, 23-2
- Notched beam, 18-9
- Notification systems, security, 32-18
- NRC (*see* Noise reduction coefficient)
- NRTL (*see* Nationally Recognized Testing Laboratory)
- Numbered keypad, 32-17
- Number of exits required, 55-18
- Nylon 6, 30-8
- O**
- Object protection, 32-17
- Observation, construction, 52-3
- Occupancy, 10-11, 55-10
 - category, 23-18
 - groups, 55-11, 55-12
 - nature, 23-18
 - permit, 2-28
 - separation, 55-11
- Occupant load, 55-17, 55-28
 - factor, 55-17, 55-18
- Occupational Safety and Health Administration (OSHA), 30-11, 30-14, 55-4
- Octave band, 33-2
- Office organization, 53-3
- Offset
 - grid, 25-2, 25-3
 - wall, 23-13, 23-15, 23-16
- Ohm, 32-1
- Ohm's law, 32-1
- Oil, 28-1
 - borne preservatives, 39-12
 - finish for wood, 40-14
- Olmsted, Frederick Law, 2-3, 2-4
- One-way
 - cable structure, 25-8
 - shear, 15-9
 - slab, 20-11, 20-13
 - systems, 24-1, 25-1
 - concrete, 10-3
 - design, 24-6
 - long span, 24-1
 - selecting, 24-6
 - structural, 10-1
 - types, 24-1
- Open
 - country, 22-2, 22-4
 - loop system, 29-15
 - solar water heating, 31-13
 - office acoustics, 33-11
 - specification, 49-2
 - web
 - joist, 24-3
 - matting, 15-3, 15-5
 - steel joist, 10-2, 10-3, 14-1, 19-15, 19-16, 24-3, 38-9
- Opening
 - force, barrier-free design, 56-4
 - in corridors, 55-21
 - in fire barriers, 55-8, 55-8
 - in masonry, 37-6
 - in smoke barriers, 55-9
 - in wood framing, 39-5
 - of bids, 51-2
- Operative temperature, 27-3
- Ordinance of 1785, 2-3
- Ordinary moment-resisting frame, 23-8, 23-10
- Organic, 15-1
 - board insulation, 41-3
- Organization
 - concept, 3-5
 - concept, space planning, 3-4
 - of architect's business, 53-1
 - of architect's office, 53-3
- Orientation
 - building, 5-3, 29-1
 - in programming, 3-17
 - solar, 5-1
- Oriented strand board (OSB), 10-1, 30-4, 39-6
- Ornamental metal, 38-11
- Orthophotography, 2-23
- OSB (*see* Oriented strand board)
- Oscillating load, 22-2
- OSHA (*see* Occupational Safety and Health Administration)
- Outlet (*see* Duplex receptacle)
- Overflow drain, 41-10
- Overhanging beam, 13-3
- Overhead
 - coiling doors, 42-7
 - costs, 3-12
- Oversized hole, 16-8, 16-9
- Overturning, 22-14
 - moment, 23-25
- Owner-Architect Agreement, 2-26, 2-27, 50-3, 50-8, 50-9, 52-1, 52-2, 52-7
- Owner's
 - insurance, 53-6
 - responsibilities, 50-5
 - responsibilities, under General Conditions of the Contract, 50-9
- P**
- Pacific plate, 23-2
- Pad site, 2-28
- Paint, 30-10
- Palm wood flooring, 43-12
- Panel doors, 42-5
- Paneling
 - flush, 40-7
 - stile and rail, 40-9
 - thermoset decorative, 40-13
- Panel point, 14-1, 24-3
- Panic hardware, 42-9, 55-27, 55-28
- Parabolic
 - aluminized reflector (PAR) lamps, 32-11
 - arch, 24-6
 - curve, 10-10, 25-8
- Parallel
 - chord, 24-4
 - truss, 14-1
 - circuit, 32-2
 - force, 12-2
 - to-grain load, 16-2, 16-5, 16-6
- Parapet, 22-8
- Paris, plan for, 2-2
- Parking, 5-10
 - lot drainage, 5-10
- Parquet flooring, 43-12
- Partially seasoned wood, 16-2
- Particleboard, 10-1, 30-6, 39-6
- Partition
 - controlling sound through, 33-9
 - fire resistance, 55-7
 - load, 11-2, 17-2
- Partnering, 53-6
- Partnership, 53-2
 - general, 53-2
- Party wall, 2-28
- Passive
 - circulation, solar water heating, 31-14
 - smoke control, 31-18
 - solar
 - cooling, 5-5
 - design, 29-13
 - heating, 5-4, 5-6
- Path, 2-6

- Patterned glass, 42-17
- Pattern of the street, 2-6
- Paved slope, recommended, 2-10
- Paver tile, 43-5
- Paving, 35-7
 - pervious, 30-2
- Paxton, Joseph, 38-1
- Payment
 - final, 52-6
 - intermediate, 52-5
 - to contractor, 52-5
 - under General Conditions of the Contract, 50-12
- PCBs (see Polychlorinated biphenyls)
- Peak
 - demand control, 32-5
 - hourly demand, 31-9
 - load regulation, 32-5
- Peat, 2-12
- Pedestrian circulation, 5-8
- Penetrating oil finish, 40-14
- Penetrations, in fire-resistive partitions, 55-8
- Pennyweight, 16-3
- Pentachlorophenol (penta), 39-12
- People grouping, 3-17
- Percentage of construction cost, 50-7
- Percolation test, 31-16
- Perforated
 - drain tile, 35-7
 - metal, 38-13
- Performance
 - bond, 51-5
 - under AIA A701, 51-4
 - specification, 49-2, 49-3
- Perimeter protection, devices for, 32-16
- Perimeter stiffness, 23-14, 23-15
- Period, 23-3, 23-20
 - approximate, 23-20, 23-21
 - fundamental, 11-7, 22-2
 - long, 23-17, 23-19, 23-20
 - natural, 23-3
 - short, 23-17, 23-19, 23-20
 - upper limit, 23-20
- Perlite, 30-8, 41-3
- Perm, 36-3
- Permeance, 36-3
- Perpendicular
 - force, 12-2
 - to-grain load, 16-2, 16-5, 16-6
- Perret, Auguste, 36-1
- Perry, Clarence, 2-9
- Personal
 - distance, 2-8
 - injury protection insurance, 53-5
 - space, 2-8
- Personalization of space, 3-8
- Pervious paving, 30-2
- PET (see Polyethylene terephthalate)
- pH
 - level,
 - in concrete, 36-8
 - of water, 31-1
 - test, 36-9
- Phase-change
 - material, 29-14
 - system, 31-14
- Phasing, 3-18
- Philadelphia city plan, 2-3
- Phon, 33-2
- Photochromic glazing, 29-8
- Photoelectric
 - beam, 32-17
 - cell, 32-17
 - detector, smoke, 32-18
- Photogrammetry, 2-23
- Photography, tool for field recording, 2-23
- Photovoltaics, 5-6, 28-2, 29-15
- Pier, 15-6, 15-7
 - belled, 15-7
 - drilled, 15-7
- Pile
 - cap, 15-7
 - driven, 15-7
 - foundation, 15-6, 15-7
 - tapered, 15-7
- Pipe
 - sizing, 31-8, 31-11
 - steel, 19-3
- Piping
 - drainage, 31-15
 - plastic water, 31-6
- Pitch
 - pan, 41-10
 - pocket, 39-2
 - of roof, 41-6
- Pitched
 - chord, 24-4
 - steel truss, 24-1
 - truss, 14-1
 - wood truss, 24-1
- Pivot, 42-9, 42-11
- PLA (see Polylactide)
- Placement, of concrete, 36-9
- Plain
 - sawing, 40-1
 - slicing, 40-5
- Plank
 - and-beam framing, 10-1, 10-2
 - flooring, 43-11
- Planned unit development (PUD), 2-7
- Planning
 - and scheduling, 53-6
 - sustainable building design, 30-1
- Plan shape, 23-14
- Plaster, 43-1
- Plastic
 - as a sustainable building material, 30-6, 30-7
 - fiber insulation, 41-3
 - high-density polyethylene, 30-7
 - limits of soil, 35-3
 - lumber, 30-7
 - metallocene polyolefin, 30-7
 - polyethylene terephthalate (PET), 30-7
 - polylactide (PLA), 30-7
 - polyolefin, 30-7
 - thermoset and thermoplastics, 41-10
 - water pipe, 31-6
- Plasticizer, 20-2, 36-6
- Plate
 - concrete flat system, 10-4
 - cover, 19-15, 24-2
 - folded, 10-9, 25-2, 25-7
 - girder, 19-15, 24-2
 - gusset, 14-2
 - North American, 23-2
 - Pacific, 23-2
 - sill, 21-6
 - slippage, 23-2
 - sole, 21-6
 - steel, 19-3
 - tectonics, 23-2
 - top, 21-6
 - weld, 16-18
 - welding, 21-7, 21-8
- Plater-Zyberk, Elizabeth, 2-4
- Platform
 - construction, 21-6
 - framing, 21-5, 21-6, 39-5
- Plumbing
 - drawings, 48-7
 - fixture
 - barrier-free design, 56-4
 - water conserving, 30-3
 - system, building code requirements, 55-26
- Plywood, 10-1, 39-5
 - box beam, 10-2
 - web joist, 39-7
- PNC (see Preferred noise criteria)
- Pneumatic structure, 25-6
- Point source, lighting calculations, 32-15
- Polychlorinated biphenyls (PCBs), 30-17
- Polycrystalline cell, 29-16
- Polyester wood finish, 40-14
- Polyethylene
 - sheet test, 36-8
 - terephthalate (PET), 30-7, 30-8, 30-10
- Polyisocyanurate (polyiso), 41-3, 41-5
- Polylactide (PLA), 30-7
- Polymer-dispersed liquid crystal film
 - glazing, 42-18
- Polyolefin, 30-7
- Polystyrene, extruded, 41-3
- Polyurethane
 - for insulation, 41-3, 41-5
 - sprayed insulation, 41-3
 - wood finish, 40-14
- Polyvinyl chloride, 30-9
 - roofing, 41-10
- Ponding, 24-9, 41-9
- Portable fire extinguishers, 31-20
- Portal frame, 22-11
- Portland cement, 20-2, 21-4, 36-1, 36-5
- Positive
 - and-beam system, 10-8
 - and timber, 18-2
 - base, 16-7
 - cap, 16-7
 - pressure, 22-1
 - rotation, 12-4, 13-4
 - tensioned concrete, 10-5, 20-14, 24-5
 - tensioning, 20-14
 - steel, 20-2

- Post
 - bid information, under AIA A701, 51-4
 - consumer material, 30-4, 30-20
 - industrial, 30-20
 - material, 30-4
 - tensioned concrete, 36-12
- Potable water, 20-2, 30-1, 31-1
- Power
 - budget, 32-9
 - definition, 32-2
 - factor, 32-1
 - of sound, 33-2
 - supply
 - electric, 32-4
 - emergency, 32-7
- Practice management, 53-1
- Pratt truss, 24-3
- Preaction system, 31-19
- Prebid conference, 51-2
- Precast
 - column, 10-5
 - concrete, 10-3, 20-14, 36-11
 - connection, 16-18
 - wall, 21-7, 21-8
 - structural members, 10-5
- Pre-consumer, 30-20
- Preferred noise criteria (PNC), 33-6
- Preformed panel, 41-8, 41-9
- Preheat fluorescent lamps, 32-12
- Premium grade, 18-11
- Prescriptive specification, 49-2
- Preservation, 2-25
- Preservatives, for lumber, 39-12
- Pressure
 - allowable bearing, 15-7
 - coefficient of earth, 15-12
 - hydrostatic, 11-8, 15-3
 - internal, 22-4
 - lateral, 11-7, 15-5, 15-11
 - leeward wall, 22-6
 - loss in pipes, 31-8
 - negative, 22-1
 - positive, 22-1
 - reducer, 31-7
 - regulator, 31-7
 - roof, 22-6
 - sensor, 32-17
 - side wall, 22-6
 - tank, 31-2
 - wave, 23-2
 - windward wall, 22-6
- Pressurized stairway, 31-18
- Prestressed, 10-5
 - concrete, 20-14, 24-5, 36-12
 - girder, 24-1
 - double tee, 24-1, 24-5
 - single tee, 24-1, 24-5
- Prestressing steel, 20-2, 20-14
- Pretensioned concrete, 20-14, 36-12
- Pretensioning, 20-14
- Primary
 - electrical service, 32-4
 - electric distribution, 32-5
- Prime contract, 50-2
- Principal meridians, 5-12
- Priority, 3-17
- Proctor test, 15-4, 35-5
- Product data, 52-1
- Professional
 - liability insurance, 53-5
 - services
 - costs, 3-10
 - during pre-design, 2-26
- Profit, 3-12
- Pro forma, 2-29
- Programmatic concepts, 3-3, 3-16
- Programming, 3-1
 - building area, 3-2
 - codes and regulations, 3-15
 - process, 3-16
 - space relationships, 3-3
- Progress
 - payments, 50-8, 52-5
 - reports, 50-4
- Project
 - administration services, under AIA
 - Document B141, 50-4
 - closeout, 52-6
 - cost methods, 50-2
 - delivery, 50-1
 - management, 53-6
 - manual, 48-9, 49-1, 51-3
 - overhead, 3-12
 - schedule, 50-4
- Projected area method, 22-5, 22-7
- Propane, 28-1
- Property insurance, 53-5
- Proposition 65, 30-11, 30-12, 30-14
- Proprietary specification, 49-2
- Protection
 - devices, 32-17
 - persons and property, under General
 - Conditions of the Contract, 50-12
- Protruding objects, barrier-free design, 56-9, 56-10
- Proxemics, 3-8
- Psychological influences on space
 - planning, 3-8
- Psychrometric chart, 27-4, 27-5
- Psychrometry, 27-4
- Public
 - distance, 2-8
 - enterprise revenue bonds, 2-21
 - facilities, effects on city planning, 2-9
 - transit, 2-13
 - way, 55-16
 - works financing, 2-20
- PUD (*see* Planned unit development)
- Pump, heat, 28-1
- Punch list, 52-6
- Punching shear, 15-7
- Pythagorean theorem, 12-8

- Q**
- Quadratic equation, 13-9
- Quality
 - of light, 32-14
 - planning, 28-7
- Quarry tile, 43-5
- Quarter slicing, 40-5
- Quartersawing, 40-2
- Queen post truss, 24-3
- Quenching, 38-3

- R**
- Radial
 - arch, 24-6
 - circulation pattern, 3-6
 - organization, 3-4
- Radiant barrier, 41-5
- Radiation, 27-2, 27-6
- Radiative cooling, 5-5, 29-16
- Radius of gyration, 12-5, 12-7, 13-10, 14-2, 18-10, 19-11
- Radon, 30-17
- Rafter, wood-trussed, 14-1, 14-2
- Raft foundation, 15-6
- Railroad shipping, 24-7
- Rainforest Alliance, 30-6
- Rainwater collection, 30-2
- Raker, 35-6
- Ramp, 5-9, 44-9
 - barrier-free design, 56-7, 56-9
 - slope, recommended, 2-10
- Random
 - matching, 40-7, 40-9
 - noise (*see* White sound)
- Range, 5-12
- Rapid start fluorescent lamp, 32-12
- Rate-supported bonds, 2-21
- Ratio
 - depth-to-span, 24-1
 - height-to-span, 25-2
 - length-to-width, 22-11
 - slenderness, 10-6, 13-10, 19-11, 19-12, 21-2
 - span-to-depth, 20-11
 - water-to-cement, 20-2
- Reactance, 32-1
- Reaction, 13-1, 13-5
- Rebar, 20-2, 20-3, 20-4, 36-4
 - connection, 16-18
 - designation, 20-3, 20-4
 - grades, 20-3
- Recessed luminaire, 32-14
- Reclaimed wood, 30-6
- Reconstruction, 2-25
- Record documents, 50-11
- Recovered material, 30-4, 30-20
- Recovery rate, 31-11
- Rectangular
 - beam, 10-5
 - survey system, 2-3
 - tube section, 19-3
- Rectified photography, 2-23
- Recuperative gas boiler, 28-10
- Recyclability, 30-15
- Recycled
 - content, 30-4
 - material, 41-11, 30-15, 43-3
- Recycling, 30-5, 30-15
- REDM (*see* Reflectorless electromagnetic distance measurement)

- Reduction rate, 11-3
- Redundancy, 24-8, 25-1
- Reentrant corner, 23-13, 23-14, 23-15
- Reference standard specification, 49-3
- Reflectance (see Reflectivity)
 - coefficient, 32-7
- Reflected
 - ceiling plan, 48-7
 - glare, 32-9
- Reflection, 33-12
 - types, 32-7
- Reflective
 - glass, 42-17
 - insulation, 41-5
- Reflectivity, 41-5
- Reflector (R) lamp, 32-11
- Reflectorless electromagnetic distance measurement (REDM), 2-23
- Reform movement in city planning, 2-2
- Refrigeration
 - absorption, 28-3
 - compressive, 28-3
 - principles, 28-3
- Regulations (see also Building code requirements)
 - federal, 55-2
 - in programming, 3-15
 - local, 55-2
 - state, 55-2
- Regulatory agency coordination, during
 - pre-design, 2-26
- Rehabilitation, 2-25
 - Standards, Secretary of the Interior, 2-25
- Reheat system, 28-5
- Reinforced
 - Building Code Requirements for Concrete (ACI-318), 17-4, 17-5
 - concrete construction, 10-6
 - doubly, beam, 20-10
 - grouted masonry wall, 21-2, 21-3, 21-4
 - grouted wall, 37-5, 37-6
 - hollow masonry wall, 21-2, 21-3
- Reinforcement
 - anchorage, 20-10
 - bending, 17-5
 - concrete, 36-4
 - horizontal
 - joint, 10-5, 21-3
 - masonry, 10-6
 - lateral, 20-13
 - minimum
 - horizontal wall, 21-7
 - vertical wall, 21-7
 - web, 20-9
 - shear, 20-9
 - spiral, 20-14
 - vertical
 - masonry, 10-6
 - wall, 21-3
 - web, 20-9
- Reinforcing
 - bar, 36-4
 - size, 20-3
 - steel, 20-2
- Rejecting work, 52-3
- REL (see Chronic inhalation reference exposure level)
- Relationships, in programming, 3-17
- Relative
 - humidity test, 36-8
 - solar heat gain (RSHG), 28-14
- Renaissance city planning, 2-2
- Renewable
 - materials, 30-4
 - product, 30-20
- Repetitive use factor, 17-3, 18-2, 18-4, 18-11
- Repointing, 37-8
- Repose, 15-6
- Required concrete shear strength, 20-9
- Resilient flooring, 43-13
- Resistance (see also R-value), 27-1, 27-6
- Resonant load, 11-7, 22-2
- Response modification
 - coefficient, 23-7, 23-8, 23-20
 - factor, 23-17
- Reston, Virginia new town, 2-4
- Restoration, 2-25
 - of brick, 37-8
- Restriction, 2-29
- Restrictive covenant, 2-19, 2-29
- Resultant force, 12-7, 12-8
- Retainage, 50-8, 52-5
- Retaining wall, 11-7, 15-11, 15-12, 21-1
- Retarder, 36-6
- Reusability, 30-5
- Reuse, 30-5
 - of materials, 30-15
- Revenue bond, 2-21
- Reverberation, 33-2, 33-7
 - time, 33-2, 33-7
- Revolving door, 42-7
- Ribbed slab, 20-11
- Rice straw, 30-6
- Richter scale, 23-2, 23-3
- Rift
 - sawing, 40-2
 - slicing, 40-5
- Right
 - of-way, 2-19
 - to carry out the work, 50-10
 - to photograph, under AIA Document B141, 50-6
- Rigid
 - components, 23-24
 - connection, 24-9
 - diaphragm, 23-11
 - elements, 23-24
 - frame, 10-8, 24-2, 24-3
 - steel conduit, 32-3
- Riparian, 2-29
 - rights, 2-29
- Rise
 - and tread of stairs, 44-8, 44-9
 - of-temperature detector, 32-18
- Riser, 55-24
- Risk management, 53-4
- Riveting, 16-7, 16-9
- Road
 - alignment, 2-13
 - layout, 2-13, 5-8
 - types, 2-13
- Rock
 - classification, 37-11
 - wool, 41-3
- Rod (in the retina), 32-8
- Rolling of metal, 38-2
- Romex, 32-3
- Roof
 - accessories, 41-11
 - live load, 11-5
 - load, 17-2
 - panels, preformed, 41-8
 - plan, 48-7
 - Plan (vignette), 47-1
 - pressure, 22-6
 - slope, 11-5
 - types, 41-6, 30-7
- Roofing
 - built-up, 41-9
 - liquid-applied, 41-11
 - membrane, 41-9
 - sheet metal, 41-8
 - single-ply, 41-10
 - tile, 41-8
- Room
 - acoustics, 33-12
 - corner test, NFPA 265, 55-6, 55-9
 - noise control, 33-8
- Root, John, 2-4
- Roping, 44-1
- Rotary slicing, 40-5
- Rotation
 - end, 13-10, 13-11, 18-10, 19-11, 19-12
 - negative, 12-4, 13-4
 - positive, 12-4, 13-4
- Rough
 - carpentry, 39-1
 - form finish, 36-9
 - grading, 35-5
- Round head screw, 16-3
- RSHG (see Relative solar heat gain)
- Rubbed concrete finishes, 36-9
- Rubber flooring, 43-14
 - as a sustainable building material, 30-9
- Runaround coil, 28-12
- Running
 - match, 40-7, 40-9
 - trim, 40-13
- Runoff, 5-6
 - coefficient, 2-12, 5-7
 - storm, 30-2
- R-value, 27-1, 27-6, 29-6, 41-2
 - for insulation, 41-4
- S**
- S corporation, 53-2
- Sabin, 33-2
 - formula, 33-2
- Saddle hanger, 16-7
- Safety, 3-17, 52-4
 - as part of detailing, 48-2
 - devices, elevator, 44-2

- edges for elevators, 44-3
- factor, 20-5
- glazing, 42-20, 42-21
- Sag, 10-10, 25-7, 25-8
- Salvaged building materials, 30-5
- Sample, 52-1
- Sand, 2-12
 - and gravel, 15-1, 20-2
- Sandblasted concrete finishes, 36-9
- Sanitary
 - drainage, 31-14
 - sewer slope, 5-7
- Sash door, 42-2
- Satellite
 - pattern, 2-5
 - tenant, 2-29
- Saturation line, 27-4
- Savannah, Georgia, city plan, 2-3
- Sawn lumber, 18-1, 18-2
- SBS (*see* Sick-building syndrome)
- SBX (*see* Sodium borate)
- Scale
 - Modified Mercalli, 23-2, 23-3
 - Richter, 23-2, 23-3
- Scenic easement, 2-19
- Schedule, 48-7
 - construction, 3-13, 52-2
 - project, 50-4, 50-11
- Scheduling, 3-13
 - critical path method, 3-14
 - fast-track, 3-15
 - Gantt chart, 3-14
 - part of programming, 3-9
 - project management, 53-6
- Schematic design, 3-13
- Schwedler dome, 25-4
- Scientific Certification System (SCS), 30-6, 30-19
- Scissor truss, 14-1
- Screw, 16-3, 38-3, 39-10
 - flat head, 16-3
 - lag, 16-4
 - lead hole, 16-3
 - penetration, 16-3
 - round head, 16-3
 - wood, 16-3
- Scribe, 40-6
- Scrubbed concrete finish, 36-9
- SCS (*see* Scientific Certification System)
- Scupper, 41-10
- Sealant, 41-11
 - properties, 41-14
- Seamless flooring, 43-14
- Sears Tower (Chicago), 10-11, 22-12
- Seaside, Florida, 2-4
- Seasonal energy efficiency ratio (SEER), 28-14
- Seasoned wood, 18-8
- Seating, barrier-free design, 56-11, 56-12
- Secondary electric distribution, 32-6
- Secondhand smoke (*see* Environmental tobacco smoke)
- Secretary of the Interior's Standards for Rehabilitation, 2-25
- Section
 - building, 48-7
 - built-up steel, 19-15, 24-2
 - compact, 19-4
 - stress, 17-4, 19-4
 - composite, 16-19
 - critical
 - moment, 15-8
 - net, 16-2
 - shear, 15-8, 20-9
 - modulus, 12-5, 12-7, 13-2, 18-1, 18-2, 19-4, 19-5, 19-7, 19-8
 - noncompact, 19-4
 - stress, 17-4
 - property, 12-5
 - rectangular tube, 19-3
 - square tube, 19-3
 - standard rolled, 19-15
 - wall, 48-7
- Sections, method of, 14-3, 14-5
- Sectional overhead doors, 42-7
- SectionFormat outline, 49-8
- Security
 - as part of detailing, 48-2
 - controls, 3-18
 - systems, 32-16
- SEER (*see* Seasonal energy efficiency ratio)
- Segregation, 36-9
- Seismic
 - design, 23-1
 - category, 23-3, 23-20
 - force resisting system, 23-7, 23-8
 - joint, 23-15
 - load, 17-2, 21-7, 21-9
 - response coefficient, 23-17
 - restraint for ceilings, 43-10
 - site coefficient, 23-19
 - use group, 23-20
- Selecting
 - one-way systems, 24-6
 - two-way systems, 25-9
- Selective collective elevator control, 44-2
- Self
 - closing door, 42-14, 55-28
 - consolidating concrete, 36-6
- Semidirect lighting systems, 32-13
- Semirigid connection, 22-14
- Sensible heat, 27-1, 27-7
- Separated flow, 3-17
- Separation of exits, 55-20
- Septic tank, 31-16
- Sequence matching, 40-8, 40-10
- Sequential flow, 3-17
- Series circuit, 32-2
- Service
 - access, site planning, 2-14
 - circulation, 5-9, 5-10
 - groupings, 3-17
 - spaces, space planning, 3-6, 3-8
- Setback, 2-18, 23-15
- Sewage disposal, private, 31-16
- Sewer
 - building, 31-15
 - house, 31-15
 - slope, recommended, 2-10
- SGS Systems and Services Certification, Inc., 30-6
- Shading, 29-11
 - coefficient, 29-16, 29-8, 42-17
 - devices, 29-4
- Shadow mask, 29-13
- Shake, 39-2
- Shallow well, 31-2
- Shear
 - allowable
 - bolt, 16-8, 16-9
 - wood stress, 18-7
 - base, 23-17, 23-21
 - distribution, 23-22
 - concrete, 20-9
 - connector, 16-19
 - critical section, 15-8, 20-9
 - diagram, 13-4, 13-5, 13-6
 - discontinuous wall, 23-15
 - dome stress, 25-5
 - double, 16-2, 16-4, 16-6, 16-9
 - flexural, 15-7, 15-8
 - footing, 15-7
 - force, 13-2
 - gross stress, 17-4, 19-4
 - horizontal, 13-2, 18-7
 - stress, 18-7
 - maximum, 13-9
 - multiple, 16-2
 - net area, 16-11
 - one-way, 15-9
 - plane, 16-8
 - plate, 39-11
 - plate connector, 16-7
 - punching, 15-7
 - reinforcement, 20-9
 - required concrete strength, 20-9
 - single, 16-2, 16-4, 16-5, 16-9
 - soil
 - undrained strength, 23-19
 - wave velocity, 23-19
 - steel design, 19-10
 - stress, 12-2, 13-2
 - two-way, 15-7, 15-8, 15-9
 - vertical, 13-2, 13-4
 - wall, 21-1, 22-9, 22-10, 22-11, 22-14, 23-6, 23-7
 - wave, 23-2
- Sheathing, 21-5, 21-6, 39-6
- Sheet
 - flow, 5-6
 - metal roofing, 41-8
- Sheetrock (*see* Gypsum wallboard)
- Shielding effect, 22-2
- Shingle, 41-6
- Shipping, 24-1, 24-7, 25-9
- Shock absorber, 31-7
- Shop drawing, 50-11, 52-1, 52-2
 - review, 24-9
- Shoring, 17-5, 35-5, 35-6
- Short
 - column, 13-10
 - period, 23-17, 23-19, 23-20
 - slotted hole, 16-8, 16-9

- Shower, barrier-free design, 56-6, 56-8
- Shrinkage, in architectural woodwork, 40-13
- SI unit, xxxv
- Sick-building syndrome (SBS), 30-12
- Side
 - connection member, 16-4, 16-5, 16-6
 - grain withdrawal, 16-3
 - wall pressure, 22-6
- Sidewalk, 5-8, 5-9, 35-7
- Siding, wood, 40-2
- Signage, barrier-free design, 56-9
- Signal system, 32-16
- Sill plate, 21-6
- Silt, 2-12, 15-1
- Simplified earthquake analysis, 23-2
- Simply supported beam, 13-3, 13-9
- Single
 - automatic elevator control, 44-2
 - membrane, 25-6
 - ply membrane for waterproofing, 41-1
 - ply roofing, 41-10
 - shear, 16-2, 16-4, 16-5, 16-9
 - tee, 24-5
 - wythe
 - construction, 10-5, 10-6
 - wall, 21-1, 21-2, 21-3, 37-5, 37-6
- Singly curved, 25-4
- SIP (*see* Structural insulated panel)
- Sisal wall covering, 30-10
- Site
 - analysis, 2-13
 - economic, 2-19
 - sustainability, 2-16
 - utilities, 2-14
 - class definition, 23-19
 - coefficient, 23-17
 - Design (vignette), 6-1
 - development, 2-9
 - drainage, 2-12, 5-6, 35-6
 - evaluation, sustainable building design, 2-15
 - features, analysis, 2-12
 - Grading (vignette), 7-1
 - improvements, 35-7
 - plan, 48-6
 - planning
 - climate, 2-14
 - landscaping, 5-5
 - natural cooling, 5-5
 - parking, 5-10
 - pedestrian, 5-8
 - roads, 2-13, 5-8
 - service access, 2-14, 5-9, 5-10
 - solar orientation, 2-14, 5-1, 5-4
 - sustainability building design, 2-16
 - topography, 5-1
 - utilities, 5-7
 - utility availability, 2-14
 - visits, 50-5, 52-3
 - Zoning (vignette), 4-1
- Sitte, Camillo, 2-2
- Size
 - factor, 17-3, 18-4, 18-10
 - minimum weld, 16-17
 - module, 25-3
 - nominal, 18-1
 - reinforcing, 20-3
 - wood, 18-1
- Skin friction, 15-6
 - load dominant buildings, 29-2, 29-3
- Skylight, 42-16
- Sky-lobby concept, 44-5
- S-label, 55-23
- Slab
 - channel, 24-5
 - concrete, 20-13
 - flat system, 10-4
 - hollow core, 10-5
 - keyed, 16-18
 - one-way, 20-11, 20-13
 - on grade, 36-3
 - ribbed, 20-11
 - two-way, 20-13
- Slate roof tile, 41-8
- Slender column, 13-10
- Slenderness ratio, 10-6, 13-10, 19-11, 19-12, 21-2
- Sling psychrometer, 27-3
- Slip
 - critical connection, 16-8, 16-9, 16-10, 16-14
 - forming, 36-2
 - matching, 40-7, 40-9
- Slope
 - analysis, 2-10
 - formula, 2-10
 - green roofs, 29-5
 - of land, 2-10
 - parking lot, 5-10, 5-11
 - pedestrian walks, 5-8, 5-9
 - recommended for various uses, 2-10
 - road, 5-8
 - sanitary sewer, 5-7
 - surface drainage, 5-6, 35-6
- Slump, 20-5
 - test, 20-4, 20-5, 36-7
- SmartWood Program, 30-6
- Smelting, 38-2
- Smoke
 - barrier, 55-9
 - control, 28-8, 31-18
 - developed index, 55-6, 55-9
 - tobacco, 30-11
 - vents, 41-11
- Smokeproof enclosure, 31-18
- Smooth
 - form finish, 36-9
 - rubbed concrete finish, 36-9
- Snow load, 11-3
- Social
 - behavior, 2-7
 - distance, 2-8
 - influence, 10-13
 - influences on space planning, 3-8
- Sociofugal space, 2-7
- Sociopetal space, 2-7
- Sodium borate (SBX), 39-12
- Soft story, 23-12, 23-16, 23-17
- Softwood, 39-1, 40-1
- Soil, 2-12, 15-1
 - allowable bearing capacity, 15-3, 15-5
 - classification, 2-12, 35-1
 - cohesive, 15-12
 - compaction, 15-4
 - densification, 15-5
 - density, 15-4
 - expansive, 15-5
 - group, hydrologic, 30-20
 - lateral load, 11-8
 - load, 11-7
 - load tests, 35-3
 - moisture content, 15-4
 - profile, 23-19
 - shear wave velocity, 23-19
 - stack, 31-15
 - surcharging, 15-5
 - test, 15-3, 35-1
 - treatment, 15-3, 35-4
 - types, 35-3
 - uncompacted, 15-12
 - undrained shear strength, 23-19
 - Unified Classification System (USCS), 15-3, 15-4
 - water in, 15-3, 35-3
- Solar
 - altitude, 5-3
 - angle, 5-3
 - cooling, passive, 5-5
 - design, 29-11
 - active, 29-14
 - collectors, 5-6
 - passive, 29-13
 - heat-gain coefficient (SHGC), 29-8, 29-16, 30-8, 42-17
 - orientation, 2-14, 4-1
 - powered absorption cooling, 28-9
 - water heating, 31-13
- Soldering, 38-3
- Sole plate, 21-6
- Sole proprietorship, 53-1
- Solid
 - block flooring, 43-12
 - core doors, 42-5
 - stock, 40-1
 - surfacing, 40-13
- Solid decking, 18-13
- Sound, 33-2
 - absorption, 33-6
 - coefficient, 33-2
 - rules of thumb, 33-7
 - control, 33-8
 - intensity, 33-2
 - level, 33-3
 - masking, 33-8
 - power, 33-2
 - qualities, 33-2
 - ratings, building code requirements, 55-27
 - transmission, 33-4
 - class (STC), 33-2, 33-4
 - class (STC), building code requirements, 55-27
 - class ratings, 33-5
 - control, 33-8

- South Coast Air Quality Management District
 - California, 30-8, 30-11
 - Rule 1113, Architectural Coatings, 30-14
- Southern Forest Products Association, 18-11
- Soy-based polyurethane foam, 41-5
- Space
 - frame, 10-9, 23-6, 25-2
 - support, 25-3
 - needs, programming, 3-1
 - planning
 - circulation patterns, 3-4
 - guidelines, 3-2
 - organization concepts, 3-4
 - service spaces, 3-6
 - relationships, in programming, 3-3
 - requirements
 - determining, 3-1, 3-2
 - mechanical room, 28-8
 - standards, corporate, 3-1
- Span
 - range, 24-1, 25-2
 - rating, 39-5
 - to-depth ratio, 20-11
- Spandrel glass, 42-18, 42-20
- Special
 - conditions, 50-14
 - district assessments, 2-21
 - moment-resisting frame, 23-8, 23-10
 - tax, 2-21
 - use permit, 2-29
 - wind regions, 22-2, 22-3
- Specific
 - gravity of soil, 35-3
 - heat, 27-2
 - site class, 23-20
- Specification
 - coordination with drawings, 48-9, 49-1
 - organization, 49-3
 - types, 49-2
 - writing guidelines, 49-9
- Specified
 - compressive strength, 21-1
 - concrete compressive strength, 17-4
 - yield point, 19-3
- Specifying for sustainability, 49-7
- Spectral
 - energy distribution, 32-14
 - response acceleration, 23-3, 23-4, 23-5, 23-19
- Spectrally selective glazing, 29-8
- Specular reflection, 32-7
- Speech privacy, 33-10
- Spiral
 - column, 20-14
 - pitch, 20-14
 - reinforcement, 20-14
 - stairway, 38-10, 55-24, 44-8
- Splay corner, 23-15
- Split
 - lumber defect, 39-2
 - ring, 39-11
 - ring connector, 16-7
 - wired receptacle, 32-6
- Spot zoning, 2-29
- Sprayed
 - fiber insulation, 41-5
 - foam insulation, 41-5
 - polyurethane, 41-3
 - on fireproofing, 17-5
- Spread footing, 15-6, 15-8
- Sprinkler system, 31-19
- Square tube section, 19-3
- Stability, 24-9
- Stack
 - pressure, 29-7
 - vent, 31-15
- Stacked elevators, 44-5
- Stain, wood, 40-14
- Stainless steel, 38-5, 38-12
- Stair Design (vignette), 46-1
- Stairs, 55-28
 - and ramps, as vertical transportation, 44-6
 - barrier-free design, 56-7, 56-9
 - circular, 44-7
 - code requirements, 44-7, 44-8
 - configuration, 44-7
 - definition, 55-24
 - design, 44-7
 - exterior, 5-9, 5-10
 - rise and tread, 44-8
 - spiral, 38-10, 44-8
 - width, 55-24
 - winding, 44-7
 - wood, 40-3
- Stairway, 55-24, 55-25, 55-28
 - smoke control, 31-18
- Standard
 - Building Code, 55-1, 55-3
 - Form of Agreement Between Owner and Architect with Form of Architect's Services, AIA B141, 50-3, 50-4, 50-7, 51-1, 28-5
 - Form of Agreement Between Owner and Contractor, where the basis of payment is a stipulated sum, AIA A101, 50-8
 - for the Installation of Sprinkler Systems, NFPA-13, 31-19
 - Method of Test for Critical Radiant Flux of Floor Covering Systems Using a Radiant Heat Energy Source (Flooring radiant panel test), NFPA 253, 55-9
 - Methods of Fire Tests for Evaluating Room Fire Growth Contribution of Textile Wall Covering (Room Corner Test), NFPA 265, 55-6, 55-9
 - Methods of Fire Tests for Evaluating Room Fire Growth Contribution of Wall and Ceiling Interior Finish, NFPA 286, 55-6, 55-9
 - Methods of Fire Tests for Flame-Resistant Textiles and Films (Vertical ignition test), NFPA 701, 55-9
- Methods of Fire Tests of Building Construction and Materials, ASTM E-119, 55-5
- on Fire Test for Window and Glass Block Assemblies, NFPA 257, 55-5
- parallels, 5-12
- penetration resistance, 23-19
- penetration test (SPT), 15-1, 35-1
- rolled section, 19-15
- round hole, 16-8, 16-9
- Test Method for Flammability of Finished Textile Floor Covering Materials, ASTM D-2859, 43-13
- Test Method for Surface Burning Characteristics of Building Materials, ASTM E-84, 55-5, 55-6, 55-9
- Standards
 - fire-resistance, 55-6
 - for Rehabilitation, 2-25
 - industry, 55-4
 - material, 55-4
 - testing, 55-4
 - types, 55-5
 - writing organizations, 55-4
- Standing and running trim, 40-13
- Standpipe, 31-20
 - and Hose System, NFPA 14, 31-20
- Star
 - pattern, 2-5
 - shaped city, 2-2
- Static
 - analysis method, 11-7
 - dissipative laminate, 40-12
 - head, 28-8, 31-3, 31-7
- Statically
 - determinate, 13-3
 - indeterminate, 13-3
- Statical moment, 12-5, 12-6, 13-2
- Statics, 12-1
- Status, influence on space planning, 3-9
- STC (*see* Sound transmission class)
- Steam, 28-1
- Steel, 19-1, 30-6, 38-5
 - allowable
 - column load, 19-14
 - stress, 17-3, 19-3, 19-4
 - American Institute of Steel Construction (AISC), 12-6, 13-2, 13-9, 14-2, 16-8, 16-9, 16-10, 16-12, 16-13, 16-16, 16-17, 17-4, 19-3, 19-6, 19-7, 19-8, 19-12, 19-13, 19-14
 - angle, 19-2, 19-3
 - arch, 24-1, 24-6
 - bar, 19-3
 - beam, 19-3
 - and concrete slab, 10-6, 10-7, 16-19
 - and-girder system, 10-2, 10-3
 - design, 19-4
 - bolts, 16-7, 16-9, 16-10
 - built-up section, 19-15, 24-2
 - camber, 17-5
 - cold-drawn wire, 20-3
 - column, 19-11
 - design, 19-12, 19-14
 - composite deck, 10-6, 10-7

- composition, 19-2
- compression, 20-10
- connection, 16-7
- deflection design, 19-10
- designation, 19-3
- door, 42-4
 - frame, 42-4
- flat truss, 24-1
- girder, 24-1, 24-1
- high
 - carbon, 19-2
 - strength, 19-2, 24-5
- joist chord configurations, 24-4
- Joist Institute, 19-16, 19-17, 24-3
- joist, open-web, 38-9
- light-gage stud, 21-6
- lintel, 21-5
- maximum
 - amount, 20-6
 - longitudinal percentage, 20-13
- medium-carbon, 19-2
- mild, 19-2
- minimum
 - amount, 20-7
 - longitudinal percentage, 20-13
- open-web joist, 14-1, 19-15, 19-16, 24-3
- pipe, 19-3
- pitched truss, 24-1
- plate, 19-3
- ponding, 17-5
- post-tensioning, 20-2
- prestressing, 20-2, 20-14
- reinforcing, 20-2
- rigid frame, 24-1, 24-2
- shear design, 19-10
- structural system, 10-2
- temperature, 20-13
- trowel finish, 36-10
- truss, 24-3
- type, 19-2
- yielding, 20-6
- Steiner tunnel test, 55-5, 55-6
- Stereophotogrammetry, 2-23
- Stiffener, 24-2
- Stiffness
 - bending, 12-6
 - building, 23-6
 - perimeter, 23-14, 23-15
- Stile and rail
 - doors, 42-5
 - paneling, 40-9
- Stipulated
 - Price Contract, CCDC 2, 50-8, 50-9, 28-4, 28-6
 - sum, 50-2, 50-7, 50-9
- Stirrups, vertical, 20-9
- Stone, 37-11
 - cast, 37-11
 - construction, 37-14
 - coursing, 37-12, 37-14
 - finishes, 37-12, 43-8
 - finishes, types, 37-13
 - types, 37-12
 - veneer, 37-12
- Storage
 - of materials, 52-5
 - tank system, hot water, 31-12
- Storefront, 42-16
- Storm
 - drainage, 31-14, 31-16
 - drainage, private, 31-17
 - runoff, 30-2
 - sewer, 5-7, 35-7
 - sewer, municipal, 31-17
 - water management, 30-2
- Story drift, 23-25
- Strain, 12-3
- Strap footing, 15-6
- Straw
 - board, 30-4
 - compressed, 30-8
 - particleboard, 30-6
- Street, types, 2-13
- Strength
 - clay masonry compressive, 21-2
 - concrete
 - compressive, 20-2, 20-5
 - masonry compressive, 21-2
 - wall, 21-7
 - design, 11-5, 17-1, 22-8, 23-24
 - method, 20-1
 - of concrete, 20-2, 20-4
 - flexural, 10-6
 - masonry compressive, 21-2
 - reduction factor, 20-5
 - required concrete shear, 20-9
 - soil undrained shear, 23-19
 - specified
 - compressive, 21-1
 - concrete compressive, 17-4
 - ultimate, 12-3
 - weld, 16-16
- Stress, 12-1, 12-2, 12-3
 - allowable, 17-3
 - axial compression, 19-11, 19-13
 - bending, 19-4
 - design (ASD), 11-5, 17-1, 17-2, 19-1, 22-8, 23-24
 - steel, 17-3, 19-3, 19-4
 - wood, 17-3
 - wood, bending, 18-5
 - wood, compression, 18-10
 - wood, shear, 18-7
 - bending, 12-2, 13-2
 - combined, 12-2
 - compact section, 17-4, 19-4
 - compression, 12-2, 13-1
 - concentration, 23-14
 - diagonal tension, 20-9
 - dome shear, 25-5
 - flexural, 13-10
 - gross
 - shear, 17-4, 19-4
 - tension, 17-4, 19-4
 - horizontal shear, 18-7
 - intensity factor, 20-6
 - net tension, 17-4, 19-4
 - noncompact section, 17-4
 - normal, 12-2
 - shear, 12-2, 13-2
 - temperature, 24-9
 - tension, 12-2, 13-1
 - thermal, 12-3
 - torsion, 12-2
 - Whitney block, 20-6
 - working design, 17-1
- Stressed-skin
 - panel, 10-2
 - structure, 10-10
- Strip flooring, 43-11
- Strong motion accelerograph, 23-3
- Structural
 - clay tile, 37-10
 - components, 23-24
 - cost, 10-12
 - drawings, 48-7
 - dynamic analysis, 11-7
 - force, 12-2
 - glazing gaskets, 42-19
 - grade, 18-2
 - insulated panel (SIP), 30-6, 39-8, 41-6
 - integrity, in detailing, 48-2
 - Layout (vignette), 26-1
 - lightweight concrete, 20-2
 - precast members, 10-5
 - steel, 38-8
 - system
 - concrete, 10-3
 - masonry, 10-5
 - one-way, 10-1
 - selection, 10-11
 - steel, 10-2
 - wood, 10-1
 - tee, 19-2, 19-3, 22-14
- Structure
 - air-supported, 25-6
 - cable, 25-7, 25-8
 - suspended, 25-8
 - suspension, 10-10
 - double skin, 25-6
 - inflatable, 10-11
 - earthquake-resistant, 23-1
 - flexible, 22-4
 - form-resistant, 25-6
 - inflatable, 10-11
 - lateral load resisting, 23-6
 - long span, 25-1, 24-1
 - membrane, 25-6
 - one-way cable, 25-8
 - pneumatic, 25-6
 - stressed-skin, 10-10
 - suspended cable, 25-2
 - suspension, 10-10, 25-7
 - thin-shell, 10-10, 25-3, 25-4
 - wind-resisting, 22-9
- Stub bracket, 22-14
- Stucco, 43-1
- Stud
 - cripple, 21-6
 - headed anchor, 16-19
 - light-gage steel, 21-6
 - metal, 21-6

- wall, 21-5
 - framing, 21-6
 - wood, 21-5
- Studio organization, 53-3
- Study period, 30-17
- Styrene, 30-8
- Subchapter S corporation, 53-2
- Subdivision exactions, 2-21
- Subfloor, 21-6
- Submersible pump, 31-2
- Submittal, 52-1
 - review, 52-1
- Substantial completion, 52-6
- Substitution, 50-10, 51-2
 - under AIA A701, 51-4
- Subsurface conditions, 2-12
- Suburban area, 22-2, 22-4
- Suction, 11-6, 22-1
 - pump, 31-2
- Sump, 35-7
 - pit, 31-15
- Sun
 - chart, 29-13
 - control, 5-3
 - path, 5-1, 5-3
- Sunflower seed board, 30-4
- Superblock, 2-6
- Superflat floors, 36-10
- Superinsulation, 29-7
- Super windows, 29-8
- Supplementary
 - conditions of the contract, 49-1, 50-14
 - general conditions, 50-13
- Supplements to bid forms, 49-1
- Support easement, 2-19
- Surcharging of soil, 35-5
- Surety bond, 50-13
- Surface
 - burning characteristics, 55-9
 - mounted luminaire, 32-14
 - temperature, 27-3
 - water drainage, 35-7
 - wave, 23-2
- Surveying existing buildings, 2-22
- Survey system, United States, 2-3, 5-12, 5-13
- Suspended
 - cable structure, 25-2
 - luminaire, 32-14
 - particle device glazing, 42-18
- Suspension of the contract, under General Conditions of the Contract, 50-14
- Suspension structure, 10-10, 25-7
- Sustainability, 30-1
 - building concepts, 2-16
 - site concepts, 2-16
 - specifying, 49-7
- Sustainable design (*see also* Energy conservation or Energy efficiency)
 - building materials, 30-3, 39-9, 43-12
 - building rating systems, 30-18
 - definition, 30-1, 30-20
 - detailing, 48-5
 - evaluating building materials, 30-4
 - hazardous material mitigation, 30-16
 - indoor air quality, 30-10
 - life-cycle cost analysis, 30-17
 - product certification, 30-18
 - recycling and reuse, 30-15
 - site development, 30-1
 - site evaluation, 2-15
 - site planning, 5-4
 - standards, 30-19
 - water use, 30-1
- Swamp cooler (*see* Evaporative cooling)
- Switch, 32-7
- Switchable glazing, 29-8
- Switchgear, 32-5
- Symmetric building, 23-14
- Synclastic shell, 25-5
- Synthetic gypsum wallboard, 30-9
- System
 - access floor, 17-2
 - bearing wall, 23-6, 23-7
 - building frame, 23-7, 23-9
 - concrete
 - beam-and-girder, 10-4
 - flat plate, 10-4
 - flat slab, 10-4
 - joist, 10-4
 - waffle slab, 10-4
 - curtain wall, 10-6
 - dual, 23-18, 23-11
 - foundation, 15-6
 - integration, 10-11
 - lateral
 - force-resisting, 23-11
 - framing, 22-11
 - moment-resisting frame, 23-8, 23-10
 - one-way, 24-1, 25-1
 - concrete, 10-3
 - design, 24-6
 - long span, 24-1
 - types, 24-1
 - open-web steel joist, 10-2, 10-3
 - post-and-beam, 10-8
 - seismic force resisting, 23-7, 23-8
 - selecting
 - one-way, 24-6
 - two-way, 25-9
 - steel beam-and-girder, 10-2, 10-3
 - one-way, 24-1, 25-1
 - design, 25-9
 - types, 25-2
 - one-way, 24-1, 25-1
- Unified Soil Classification (USCS), 15-3, 15-4
- Système International d'Unités (SI), xxxv
- T**
- TAB (*see* Testing, adjusting, and balancing)
- Tangent, 2-13
- Tankless
 - system, hot water, 31-12
 - water system, 31-3
- Tank system, graywater recycling, 30-3
- Tapered
 - girder, 24-2
 - pile, 15-7
- Task-ambient lighting, 32-13, 32-14
- Tax
 - ad valorem, 2-20
 - general, 2-20
 - incentives, 2-25
 - increment financing, 2-21
 - special, 2-21
 - structure, 2-20
- T-beam, 20-12
- Tearing failure, 16-11
- Technical
 - considerations, 24-8, 25-9
 - specifications, 49-1
- Tee
 - double, 10-5, 24-5
 - inverted beam, 10-5
 - joint, 16-15
 - prestressed
 - double, 24-1, 24-5
 - single, 24-1, 24-5
 - single, 10-5, 24-5
 - structural, 19-2, 19-3, 22-14
- Telephone, barrier-free design, 56-10
- Temperature
 - as component of human comfort, 27-2
 - climate, design response, 27-8, 29-3
 - color, 32-14
 - dry-bulb, 27-1, 27-3
 - effective, 27-3
 - expansion, 24-1
 - induced load, 11-7
 - mean radiant, 27-3
 - movement, 21-9, 24-9
 - operative, 27-3
 - steel, 20-13
 - stress, 24-9
 - surface, 27-3
 - wet-bulb, 27-2, 27-3
- Tempered glass, 42-17
- Tempering of metal, 38-3
- Tendon, 10-5, 20-14, 24-5
- Tension, 14-1, 14-3
 - development length, 20-10
 - diagonal, 15-7, 23-9, 23-10
 - stress, 20-9
 - gross stress, 17-4, 19-4
- net
 - area, 16-11
 - stress, 17-4, 19-4
 - stress, 12-2, 13-1
- Terminal reheat system, 28-5
- Termination
 - of agreement, under AIA Document B141, 50-6
 - of the contract, under General Conditions of the Contract, 50-14
- Terneplate, 38-7, 41-8
- Terra cotta, 37-10
- Terrazzo, 43-7
- Territoriality, 2-7, 3-8

- Test
 - core cylinder, 20-5
 - cylinder, 20-5
 - field, 52-4
 - for interior finish flammability, 55-6
 - percolation, 31-16
 - pit, 15-1, 35-3
 - Proctor, 15-4
 - slump, 20-5
 - soil, 15-3
 - Standard Penetration (SPT), 15-1
 - types, 55-5
 - wind tunnel, 22-2
- Testing
 - adjusting, and balancing (TAB), 28-12, 30-13
 - concrete, 17-4, 20-5, 36-7
 - laboratories, 55-4
 - standards, 55-4
- Textile wall coverings, 55-9
- Thermal
 - drift, 41-3
 - energy storage, 28-11
 - resistance, as part of detailing, 48-5
 - storage wall, 29-14
 - stress, 12-3
- Thermochromic glazing, 29-9
- Thermoplastic, 41-10
 - polyolefin (TPO) roofing, 41-10
- Thermoset
 - decorative paneling, 40-13
 - plastics, 41-10
- Thermosiphon system, 31-14
- Thicknesses, metal, 38-3
- Thin
 - film cells, 29-16
 - glued-laminated framing (*see* Laminated veneer lumber)
 - shell
 - barrel vault, 25-5
 - dome, 25-2
 - structure, 10-10, 25-3, 25-4
- Thinset tile installation, 43-6
- Third-party claims, 53-4
 - under AIA Document B141, 50-6
- Three
 - centered arch, 24-6
 - hinged arch, 10-8
 - part format of specification sections, 49-6
 - second peak gust wind, 22-2
 - way switch, 32-7
- Threshold, 42-12, 42-15
 - Limit Values and Biological Exposure Indices, 30-15
- Throat dimension, 16-15, 16-16
- Through
 - building expansion joint, 21-9
 - wall expansion joint, 21-10
- Thrust, 10-8, 24-6, 25-4, 25-5
- Tieback, 35-6
- Tied column, 20-13
- Ties, 20-13, 20-14
- Tile, 43-5
 - ceramic, 43-5
 - classification, 43-5
 - installation, 43-6
 - roofing, 41-8
 - types, 43-5
 - vinyl composition, 43-14
- Tilt-up
 - construction, 36-12
 - panels, 10-3
- Timber, 39-3
 - connector, 16-7
 - heavy construction, 17-5
- Time
 - claim for additional, 52-4
 - contract, 50-12
- Tinted glass, 42-17
- Titration test, 36-9
- TL (*see* Transmission loss)
- Tobacco smoke, 30-11
- Toilet
 - room, barrier-free design, 56-4
 - stall, barrier-free design, 56-4, 56-5
- Tolerance, 24-9
 - as part of detailing, 48-3
 - of concrete, 36-3
 - programming concept, 3-17
- Tongue-and-groove edging, 18-13
- Ton of refrigeration, 28-4
- Tooled concrete finishes, 36-9
- Tooling, 37-3
- Top
 - chord, 14-1, 25-3
 - grid, 25-2
 - plate, 21-6
- Topographic factor, 22-5
- Topography, 2-9, 2-10, 5-1
- Torchère, 32-14
- Torsion, 23-12
 - accidental, 23-13
 - stress, 12-2
- Torsional
 - development, 23-14
 - irregularity, 23-13
 - moment, 17-1
- Tort, 53-6
- Township, 5-12
- Tow, 36-7
- Toxicity of materials, 30-5
- Toxic Substances Control Act (TSCA) of 1976, 30-16, 30-19
- TPO (*see* Thermoplastic polyolefin)
- Transfer girder, 24-2
- Transformer, 32-5
- Transition-metal hydride electrochromic glazing, 29-9
- Translation, end, 13-10, 13-11, 18-10, 19-11, 19-12
- Transmissibility, 12-1
- Transmission
 - loss, 33-2, 33-4
 - of sound, 33-4
- Transmittance, 32-7
- Transparent insulation, 29-7
- Transportation
 - analysis, 2-13
 - effects on city planning, 2-9
 - public, 2-13
- Transverse reinforcement, 20-10
- Trap, 31-14
- Travel distance, 55-28
 - maximum, 55-19
- Tread, 55-24
- Tremie, 36-9
- Trenching, 35-5
- Triangulated space frame, 10-9
- Tributary area, 11-5
- Trigonometry, 1-2
- Trim, 55-28
 - fire-resistive standards, 55-9
 - wallboard, 43-3
 - wood, 40-13
- Trombe wall, 29-14
- Truck shipping, 24-7
- True arch, 24-6
- Truss, 14-1, 24-3
 - bowstring, 14-1
 - configurations, 24-3
 - English, 24-3
 - Fink, 24-3
 - flat, 14-1
 - steel, 24-1
 - wood, 24-1
 - Howe, 24-3
 - king post, 24-3
 - parallel chord, 14-1
 - pitched, 14-1
 - steel, 24-1
 - wood, 24-1
 - Pratt, 24-3
 - queen post, 24-3
 - scissor, 14-1
 - steel, 24-3
 - two-way frame, 25-2
 - Vierendeel, 24-4
 - Warren, 24-3
 - wood, 10-2, 24-3, 39-8
- Trussed tube, 22-11, 22-12, 23-9
- Trusses, 10-7
- Tube
 - framed, 22-12
 - rectangular section, 19-3
 - square section, 19-3
 - trussed, 22-11, 22-12, 23-9
- Tuck pointing, 37-8
- Tudor frame, 24-6
- Tuned dynamic damper, 11-7
- Tungsten halogen lamps, 32-11
- Turbidity, 31-1
- Turbine square, 2-2
- Twelve Tales of Roman law, 55-1
- Two-pipe circulating system, 31-9
- Two-way
 - concrete, 10-3
 - selecting systems, 25-9
 - shear, 15-7, 15-8, 15-9
 - slab, 20-13
 - switch, 32-6

- system, 24-1, 25-1
 - design, 25-9
 - types, 25-2
- truss space frame, 25-2
- Type
 - N bolt, 16-8, 16-9
 - X bolt, 16-8, 16-9
 - X gypsum wallboard, 43-2
- U**
- UBC (*see* Uniform Building Code)
- UL (*see also* Underwriters Laboratories)
 - 10B, Fire Tests of Door Assemblies, 55-4
 - Building Materials Directory*, 55-4, 55-6
- Ultimate strength, 12-3
- Ultrasonic detector, 32-17
- Unassigned area, 3-2, 3-3
- Unblocked diaphragm, 22-13
- Unbraced length, 19-11
- Uncompacted soil, 15-12
- Unconfined compression, 35-3
- Uncovering and correction of work, 52-3
 - under General Conditions of the Contract, 50-13
- Under-carpet wiring, 32-4
- Underfloor ducts, 32-4
- Underground
 - buildings (*see* Earth sheltering)
 - drainage, 5-6, 5-7
- Underimproved land, 2-29
- Underpinning, 35-6
- Under-reinforced beam, 20-6
- Underslung, 24-4
- Underwriters Laboratories (UL), 55-4, 55-6
- Unfinished bolt, 16-8
- Unified
 - Numbering System, 38-7
 - Soil Classification System (USCS), 15-3, 15-4, 35-3, 35-4
- Uniform
 - Building Code, 55-1, 55-3
 - Federal Accessible Standards Accessible and Usable Buildings and Facilities load, 11-4, 13-3, 13-5, 13-7, 13-9
 - Mechanical Code, 55-1
- Union, 31-6
- Unit
 - cost method, 50-8
 - loading, 15-7
 - masonry, 37-7, 37-8
 - paver, 35-7
 - price, 51-6
- United States
 - city planning, 2-3
 - Consumer Product Safety Commission (CPSC), 30-16
 - Green Building Council, 30-1, 30-18
 - survey system, 5-12, 5-13
- Unknown conditions, 52-5
- Unloaded edge, 16-2, 16-3
- Upfeed system, water supply, 31-3, 31-4
- Upflow furnace, 28-2
- Uplift, 11-6, 22-2, 23-24
- Upper limit period, 23-20
- Urban
 - area, 22-4
 - development patterns, 2-4
- Urinal, barrier-free design, 56-5
- Usury, 2-29
- Utilities
 - analysis, 2-14
 - easement, 2-19
 - site design, 5-7
- V**
- Vacuum breaker, 31-15
- Valuation of land, 2-19
- Value engineering, 3-10
- Valves, water, 31-6
- van der Rohe, Mies, 38-2
- Vapor
 - barrier, 27-7, 29-7, 36-3
 - retarder, 36-3, 41-6
- Variable air volume system (VAV), 28-4
- Variance, 2-19, 2-29
- Varnish, 40-14
- Vaux, Calvert, 2-3
- VAV (*see* Variable air volume system)
- Vector quantity, 12-1
- Vegetated roof cover, 29-5
- Veiling reflection, 32-9
- Velocity of sound, 33-2
- Veneer
 - architectural woodwork, 40-4, 40-5
 - grades, plywood, 39-6
 - stone, 37-12
 - wall, 37-5, 37-6
- Veneered wall, 21-2, 21-3, 21-8
- Vent
 - plumbing, 31-15
 - smoke, 41-11
 - stack, 31-15
- Ventilation, 27-3, 29-2
 - and Acceptable Indoor Air Quality in Low-Rise Residential Buildings, ASHRAE Standard 62.2-2003, 30-14
 - demand control, 30-19
 - displacement, 28-10
 - energy recovery, 28-11
 - for Acceptable Indoor Air Quality, ASHRAE Standard 62-2001, 30-14
 - for indoor air quality, 30-13
 - natural, 5-6
- Venting, plumbing systems, 31-14
- Venturi pump, 31-2
- Vermiculite, 41-3, 30-7, 30-16
- Versatility, programming concept, 3-8
- Vertical
 - alignment, roads, 2-13
 - force component, 14-3
 - ignition test, NFPA 701, 55-9
 - irregularities, 23-11, 23-12
 - load, 11-1
 - load-bearing wall, 21-1
 - masonry reinforcement, 10-6
 - shear, 13-2, 13-4
 - stirrups, 20-9
 - transportation, 44-1
 - wall reinforcement, 21-3
- Vibrator, 20-4
- Vierendeel truss, 24-4
- View analysis, 2-12
- Viewed angle, 27-3
- Vignette
 - Accessibility/Ramp, 45-1
 - Building Layout, 8-1
 - Building Section, 54-1
 - Interior Layout, 9-1
 - Mechanical and Electrical Plan, 34-1
 - Roof Plan, 47-1
 - Site Design, 6-1
 - Site Grading, 7-1
 - Site Zoning, 4-1
 - Structural Layout, 26-1
- Vinyl
 - composition tile, 43-14
 - flooring, 43-14
 - as a sustainable building material, 30-9
- Visible light transmittance (VLT), 29-10, 29-17, 30-8
- Vision, 32-7
- Visual comfort probability, 32-9
- Visually graded
 - dimension lumber, 18-3
 - lumber, 18-1, 18-2VLT (*see* Visible light transmittance)
- Volatile organic compounds (VOCs), 30-5, 30-10, 30-11
 - in carpet, 30-9
 - LEED credit, 30-8
- Volt, 32-1
- Voltage, to buildings, 32-4
- W**
- Waiver
 - of consequential damages, under AIA Document B141, 50-5
 - of rights, under AIA Document B141, 50-6
 - of subrogation, 50-6
- Wales, 35-6
- Wall
 - attachment, 21-7, 21-8, 21-9, 21-10
 - bearing system, 23-6, 23-7
 - cantilever, 15-11
 - cast-in-place, 21-7
 - cavity, 21-3
 - concrete, 21-7
 - foundation, 15-8
 - strength, 21-7
 - construction, 21-1
 - counterfort, 15-11
 - covering
 - sisal, 30-10
 - textile, 55-9
 - curtain, 21-1, 21-9
 - system, 10-6
 - discontinuous shear, 23-15
 - finishes
 - gypsum board, 30-9
 - paint, 30-10

- sisal, 30-9
- stone, 43-8
- fire resistance, 55-7
- footing, 15-6, 15-8
- gravity, 15-11
- leeward, 22-4
 - pressure, 22-6
- load-bearing, 21-1
- masonry, 21-1
 - bearing, 10-5
 - foundation, 15-8
 - opening, 21-4
- metal, 21-3
- minimum
 - horizontal reinforcement, 21-7
 - vertical reinforcement, 21-7
- mounted luminaire, 32-14
- multiple wythe, 21-1
- non-load-bearing, 10-6, 21-1
- offset, 23-13, 23-15, 23-16
- openings, 21-4
- overturning, 15-12
- panel
 - acoustical, 43-10
 - connection, 21-7
 - preformed, 41-8
- precast concrete, 21-7, 21-8
- reinforced
 - grouted masonry, 21-2, 21-3, 21-4
 - hollow masonry, 21-2, 21-3
- retaining, 11-7, 15-11, 15-12, 21-1
- sections, 48-7
- shear, 21-1, 22-9, 22-10, 22-11, 22-14, 23-6, 23-7
- side pressure, 22-6
- single wythe, 21-1, 21-2, 21-3
- stud, 21-5
- tile, 43-5
- to-slab connection, 16-18
- veneered 21-2, 21-3, 21-8
- vertical load-bearing, 21-1
- vertical reinforcement, 21-3
- windward, 22-4
 - pressure, 22-6
- Wane (lumber defect), 39-2
- Warehouse matching, 40-8, 40-10
- Warp, 39-2
- Warranty clause, 50-10
- Warren truss, 24-3
- Wash, 37-6
 - borings, 35-3
- Washington, D. C., city plan, 2-3
- Waste
 - disposal, 31-16
 - stack, 31-15
- Water, 20-1, 20-2
 - cement ratio, 36-3, 36-5
 - conservation, 30-5
 - content of soil, 35-3
 - for concrete, 36-5
 - hammer, 31-7
 - heater, 31-8, 31-9, 31-12
 - direct-contact, 28-9
 - in soil, 35-3
 - jet concrete finish, 36-9
 - load, 11-8
 - loop heat pump, 28-10
 - municipal supply, 31-2
 - pipe sizing, 31-1, 31-8
 - potable, 20-2
 - private supply, 31-2
 - pump, 31-2
 - quality problem, 31-1
 - soil, 15-3
 - supply, 31-1
 - components, 31-3
 - design, 31-3
 - hot, 31-8
 - system design, 31-7
 - table, 2-12, 15-3, 35-3, 35-6
 - to-cement ratio, 20-2
 - to-water heat exchanger, 28-12
 - Tower Place (Chicago), 22-12
 - use, sustainable building design, 30-1
 - well, 31-2
- Waterborne preservatives, 39-12
- Watercourse, 30-20
- Waterproofing, 25-9, 41-1
 - agents for concrete, 36-6
- Waterstop, 41-2
- Waterway, 30-20
- Watt, 32-1
 - hour meter, 32-5
 - James, 38-1
- Wave
 - ground, 23-2
 - pressure, 23-2
 - shear, 23-2
 - soil shear velocity, 23-19
 - surface, 23-2
- Weak story, 23-12
- Weather stripping, 42-12
- Weathering
 - as part of detailing, 48-5
 - steel, 38-6
- Web
 - member, 14-1, 14-2
 - reinforcement, 20-9
- Weep hole, 37-6, 48-5
- Weight
 - building, 23-17, 23-21
 - material, 11-2
 - equivalent fluid, 15-12
- Weld, 16-15
 - dimension, 16-16
 - electrode, 16-15
 - field, 16-16
 - fillet, 16-15, 16-16
 - groove, 16-15, 16-16
 - minimum size, 16-17
 - penetration, 16-15
 - plate, 16-18, 36-11
 - strength, 16-16
- Welded
 - connection, 16-15, 22-14
 - wire fabric, 20-2, 20-3, 20-4, 36-4
 - designation, 20-3, 20-4
- Welding, 16-8, 16-15, 38-3
 - plate, 21-7, 21-8
 - symbol, 16-16
- Well water, 31-2
- Welwyn Garden City, 2-3
- Western framing, 39-5
- Wet
 - bulb temperature, 27-2, 27-3
 - pipe system, 31-19
 - service factor, 18-4
 - wood, 16-2
- Wetlands, 2-16, 2-17, 2-29
- Wheatgrass cabinetry, 30-4
- Wheelchair clearances, 56-2
- White sound, 33-8
- Whitney stress block, 20-6
- Wide flange, 19-2, 19-3
 - properties, 19-6
 - sections, 38-8
- Width
 - of corridors, 55-21
 - of exits, 55-20
- Wind, 22-1
 - analysis, 22-4
 - basic speed, 22-2, 22-3
 - drift, 22-2
 - effects, 22-1
 - fastest-mile, 22-2
 - horizontal load, 21-7, 21-8
 - induced vibration, 23-25
 - influences on site planning, 2-14, 5-4, 5-11
 - load, 11-6, 17-2
 - measurement, 22-2
 - power, 29-15
 - pressure, 29-7
 - resisting structure, 22-9
 - special regions, 22-2, 22-3
 - stagnation factor, 22-5
 - three-second peak gust, 22-2
 - tunnel test, 22-2
 - variables, 22-2
 - velocity, 11-6, 22-4
- Winder stairs, 55-24
- Winding stairways, 44-7
- Window
 - as a sustainable building material, 30-8
 - metal, 42-16
 - parts, 42-15
 - screen, 32-17
 - to-wall ratio (WWR), 29-10, 29-16
 - types, 42-15
 - wood, 42-16
- Windward wall, 22-4
 - pressure, 22-6
- Wire
 - glass, 42-17
 - sizes, 32-3
- Wiring devices, 32-6
- Withdrawal of bid, under AIA A701, 51-4

- Wood
- allowable
 - design values, 18-2, 18-3
 - stress, 17-3
 - bending, 18-5
 - compression, 18-10
 - shear, 18-7
 - arch, 24-1, 24-6
 - as a sustainable building material, 30-6
 - beam, 18-5
 - bearing, 18-10
 - bolt, 16-4
 - design value, 16-4, 16-5, 16-6
 - certified, 30-6
 - column, 18-11
 - connection, 16-1
 - crawl space, 17-4
 - decay protection, 17-4
 - decking, 10-1, 18-13
 - density, 16-1
 - diaphragm, 22-13
 - door frames, 42-5
 - doors and frames, 42-4
 - fire
 - retardant treatment, 16-2
 - stop, 17-5
 - flat truss, 24-1
 - flooring, 43-11
 - as a sustainable building material, 30-9
 - finishes, 43-12
 - grades, 43-12
 - installation, 43-12
 - glued-laminated member, 18-11
 - grading, 18-1
 - joist, 10-1, 10-2, 18-11
 - moisture content, 16-2
 - National Design Specification for Construction (NDS), 16-3, 17-3, 18-10
 - partially seasoned, 16-2
 - pitched truss, 24-1
 - planking, 18-13, 39-10
 - screw, 16-3
 - seasoned, 18-8
 - service condition, 16-2
 - shrinkage, 39-4
 - siding, 40-2
 - sizes, 18-1
 - species, 16-1
 - stairs, 40-3
 - structural system, 10-1
 - stud, 21-5
 - treatment, 39-11
 - trim, 40-13
 - truss, 10-2, 24-3, 39-8
 - trussed rafter, 14-1, 14-2
 - windows, 42-16
 - wet, 16-2
 - Work, 50-6, 50-9
 - rejection of, 52-3
 - uncovering and correction, 52-3
 - Workers' compensation, 53-6
 - Working
 - drawings (*see* Construction drawings)
 - stress design, 17-1
 - Workplane, 29-16
 - Wren, Christopher, 2-2
 - Wright
 - Frank Lloyd, 2-4, 36-1
 - Henry, 2-6
 - Wrought iron, 38-4
 - WWR (*see* Window-to-wall ratio)
 - Wythe, 37-3
- X**
- X-brace, 22-11
 - XEPS (*see* Extruded expanded polystyrene)
- Y**
- Yard lumber, 39-3
 - Yield
 - of water well, 31-2
 - point, 12-3
- Z**
- Zero lot line, 2-29
 - Zinc, 38-7
 - Zonal cavity method, 32-15
 - Zone reheat system, 28-6
 - Zoning, 2-17
 - by law, 2-29
 - ordinances, 2-7, 3-15, 55-1
 - setbacks, 2-18